

設置 形態	タイプ名	電圧	形名	希望小売 価格 (税抜)	風量(強)	機外静圧	対象 床面積 (目安)※1	消費電力	熱交換効率 ※2		騒音	サイズ			重量	接続 パイプ	フィルター 捕集効率	備考	
									温度	冷房(エンタルピ)		高さ	幅	奥行					
天井 埋込	業務用ロスナイ天井埋込形 DCマイコン	100/200V	LGH-N15RXW	¥209,000	150㎡/h	180Pa	15.0㎡	75.0W	74.0%	64.5%	30.0dB	290mm	610mm	780mm	22.0kg	Φ100mm	質量法82%		
		100/200V	LGH-N25RXW	¥229,000	250㎡/h	145Pa	25.0㎡	100.0W	70.0%	63.0%	29.0dB	290mm	735mm	780mm	23.0kg	Φ150mm	質量法82%		
		100/200V	LGH-N35RXW	¥252,000	350㎡/h	185Pa	35.0㎡	140.0W	71.5%	65.5%	28.5dB	330mm	875mm	890mm	32.0kg	Φ150mm	質量法82%		
		100/200V	LGH-N50RXW	¥310,000	500㎡/h	190Pa	50.0㎡	215.0W	71.0%	63.0%	33.5dB	330mm	1,020mm	890mm	36.0kg	Φ200mm	質量法82%		
		100/200V	LGH-N65RXW	¥415,000	650㎡/h	230Pa	65.0㎡	355.0W	71.5%	63.0%	38.0dB	404mm	892mm	984mm	42.0kg	Φ200mm	質量法82%		
		100V	LGH-N80RXV	¥495,000	800㎡/h	190Pa	80.0㎡	420.0W	73.0%	65.0%	36.5dB	404mm	1,004mm	1,144mm	52.0kg	Φ250mm	質量法82%		
		100V	LGH-N100RXV	¥495,000	1,000㎡/h	165Pa	100.0㎡	515.0W	73.0%	65.0%	37.0dB	404mm	1,231mm	1,144mm	57.0kg	Φ250mm	質量法82%		
		200V	LGH-N80RXVD	¥564,000	800㎡/h	190Pa	80.0㎡	420.0W	73.0%	65.0%	36.5dB	404mm	1,004mm	1,144mm	52.0kg	Φ250mm	質量法82%		
		200V	LGH-N100RXVD	¥564,000	1,000㎡/h	165Pa	100.0㎡	515.0W	73.0%	65.0%	37.0dB	404mm	1,231mm	1,144mm	57.0kg	Φ250mm	質量法82%		
		200V	LGH-N150RXVD	¥990,000	1,500㎡/h	245Pa	150.0㎡	850.0W	74.0%	66.0%	38.0dB	808mm	1,004mm	1,144mm	106.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
		200V	LGH-N200RXVD	¥1,128,000	2,000㎡/h	165Pa	200.0㎡	1,030.0W	73.0%	65.0%	39.5dB	808mm	1,231mm	1,144mm	116.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
		業務用ロスナイ天井埋込形 DCリブレスマイコン	100V	LGH-RN15RXV	¥219,000	150㎡/h	180Pa	15.0㎡	75.0W	74.0%	64.5%	30.0dB	290mm	898mm	875mm	23.0kg	Φ100mm	質量法82%	
			100V	LGH-RN25RXV	¥240,000	250㎡/h	145Pa	25.0㎡	100.0W	70.0%	63.0%	29.0dB	290mm	918mm	1,000mm	24.0kg	Φ150mm	質量法82%	
			100V	LGH-RN35RXV	¥265,000	350㎡/h	185Pa	35.0㎡	140.0W	71.5%	65.5%	28.5dB	330mm	1,028mm	1,140mm	33.0kg	Φ150mm	質量法82%	
			100V	LGH-RN50RXV	¥326,000	500㎡/h	190Pa	50.0㎡	215.0W	71.0%	63.0%	33.5dB	330mm	1,058mm	1,285mm	37.0kg	Φ200mm	質量法82%	
			100V	LGH-RN65RXV	¥436,000	650㎡/h	230Pa	65.0㎡	355.0W	71.5%	63.0%	38.0dB	404mm	1,152mm	1,157mm	43.0kg	Φ200mm	質量法82%	
			100V	LGH-RN80RXV	¥520,000	800㎡/h	190Pa	80.0㎡	420.0W	73.0%	65.0%	36.5dB	404mm	1,312mm	1,269mm	53.0kg	Φ250mm	質量法82%	
			100V	LGH-RN100RXV	¥592,000	1,000㎡/h	165Pa	100.0㎡	515.0W	73.0%	65.0%	37.0dB	404mm	1,312mm	1,496mm	58.0kg	Φ250mm	質量法82%	
			200V	LGH-RN15RXVD	¥219,000	150㎡/h	180Pa	15.0㎡	75.0W	74.0%	64.5%	30.0dB	290mm	898mm	875mm	23.0kg	Φ100mm	質量法82%	
			200V	LGH-RN25RXVD	¥240,000	250㎡/h	145Pa	25.0㎡	100.0W	70.0%	63.0%	29.0dB	290mm	918mm	1,000mm	24.0kg	Φ150mm	質量法82%	
	200V		LGH-RN35RXVD	¥265,000	350㎡/h	185Pa	35.0㎡	140.0W	71.5%	65.5%	28.5dB	330mm	1,028mm	1,140mm	33.0kg	Φ150mm	質量法82%		
	200V		LGH-RN50RXVD	¥326,000	500㎡/h	190Pa	50.0㎡	215.0W	71.0%	63.0%	33.5dB	330mm	1,058mm	1,285mm	37.0kg	Φ200mm	質量法82%		
	200V		LGH-RN65RXVD	¥436,000	650㎡/h	230Pa	65.0㎡	355.0W	71.5%	63.0%	38.0dB	404mm	1,152mm	1,157mm	43.0kg	Φ200mm	質量法82%		
	200V		LGH-RN80RXVD	¥520,000	800㎡/h	190Pa	80.0㎡	420.0W	73.0%	65.0%	36.5dB	404mm	1,312mm	1,269mm	53.0kg	Φ250mm	質量法82%		
	200V		LGH-RN100RXVD	¥592,000	1,000㎡/h	165Pa	100.0㎡	515.0W	73.0%	65.0%	37.0dB	404mm	1,312mm	1,496mm	58.0kg	Φ250mm	質量法82%		
	200V		LGH-RN150RXVD	¥1,040,000	1,500㎡/h	245Pa	150.0㎡	850.0W	74.0%	66.0%	38.0dB	808mm	1,277mm	1,249mm	107.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
	200V		LGH-RN200RXVD	¥1,184,000	2,000㎡/h	165Pa	200.0㎡	1,030.0W	73.0%	65.0%	39.5dB	808mm	1,277mm	1,476mm	117.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
	業務用ロスナイ天井埋込形		100V	LGH-N15RX3	¥190,000	150㎡/h	170Pa	15.0㎡	120.0W	74.0%	64.5%	29.0dB	289mm	888mm	769mm	22.0kg	Φ100mm	質量法82%	
			100V	LGH-N25RX3	¥208,000	250㎡/h	135Pa	25.0㎡	142.0W	70.0%	63.0%	30.0dB	289mm	908mm	894mm	23.0kg	Φ150mm	質量法82%	
			100V	LGH-N35RX3	¥229,000	350㎡/h	175Pa	35.0㎡	210.0W	71.5%	64.0%	28.0dB	331mm	1,016mm	1,033mm	32.0kg	Φ150mm	質量法82%	
			100V	LGH-N50RX3	¥282,000	500㎡/h	180Pa	50.0㎡	298.0W	71.0%	63.0%	33.0dB	331mm	1,046mm	1,175mm	36.0kg	Φ200mm	質量法82%	
		100V	LGH-N65RX3	¥377,000	650㎡/h	210Pa	65.0㎡	480.0W	71.5%	63.0%	35.0dB	404mm	1,066mm	1,113mm	48.0kg	Φ200mm	質量法82%		
		100V	LGH-N80RX3	¥450,000	800㎡/h	180Pa	80.0㎡	525.0W	73.0%	65.0%	33.5dB	404mm	1,302mm	1,163mm	58.0kg	Φ250mm	質量法82%		
		100V	LGH-N100RX3	¥513,000	1,000㎡/h	140Pa	100.0㎡	655.0W	73.0%	65.0%	35.0dB	404mm	1,302mm	1,390mm	64.0kg	Φ250mm	質量法82%		
		200V	LGH-N15RX3D	¥190,000	150㎡/h	170Pa	15.0㎡	126.0W	74.0%	64.5%	29.0dB	289mm	888mm	769mm	22.0kg	Φ100mm	質量法82%		
		200V	LGH-N25RX3D	¥208,000	250㎡/h	135Pa	25.0㎡	142.0W	70.0%	63.0%	30.0dB	289mm	908mm	894mm	23.0kg	Φ150mm	質量法82%		
		200V	LGH-N35RX3D	¥229,000	350㎡/h	175Pa	35.0㎡	208.0W	71.5%	64.0%	29.0dB	331mm	1,016mm	1,033mm	32.0kg	Φ150mm	質量法82%		
		200V	LGH-N50RX3D	¥282,000	500㎡/h	180Pa	50.0㎡	300.0W	71.0%	63.0%	34.0dB	331mm	1,046mm	1,175mm	36.0kg	Φ200mm	質量法82%		
		200V	LGH-N65RX3D	¥377,000	650㎡/h	210Pa	65.0㎡	470.0W	71.5%	63.0%	35.5dB	404mm	1,066mm	1,113mm	48.0kg	Φ200mm	質量法82%		
		200V	LGH-N80RX3D	¥450,000	800㎡/h	180Pa	80.0㎡	510.0W	73.0%	65.0%	33.5dB	404mm	1,302mm	1,163mm	58.0kg	Φ250mm	質量法82%		
		200V	LGH-N100RX3D	¥513,000	1,000㎡/h	140Pa	100.0㎡	665.0W	73.0%	65.0%	35.5dB	404mm	1,302mm	1,390mm	64.0kg	Φ250mm	質量法82%		
		200V	LGH-N150RX3D	¥900,000	1,500㎡/h	235Pa	150.0㎡	1,050.0W	74.0%	66.0%	39.0dB	808mm	1,267mm	1,166mm	120.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
		200V	LGH-N200RX3D	¥1,025,000	2,000㎡/h	125Pa	200.0㎡	1,330.0W	73.0%	65.0%	39.0dB	808mm	1,267mm	1,393mm	132.0kg	Φ250mm	質量法82%	接続パイプ(室外側)は角270*700	
		業務用ロスナイ天井埋込形 加湿付	100V	LGH-N15RKX2	¥406,000	150㎡/h	130Pa	15.0㎡	133.0W	74.0%	68.0%	29.0dB	298mm	1,288mm	770mm	33.0kg	Φ100mm	質量法82%	
			100V	LGH-N25RKX2	¥440,000	250㎡/h	90Pa	25.0㎡	162.0W	74.0%	68.0%	29.0dB	298mm	1,338mm	894mm	36.0kg	Φ150mm	質量法82%	
			100V	LGH-N35RKX2	¥490,000	350㎡/h	85Pa	35.0㎡	198.0W	75.0%	70.0%	29.5dB	331mm	1,416mm	1,033mm	44.0kg	Φ150mm	質量法82%	
			100V	LGH-N50RKX2	¥602,000	500㎡/h	130Pa	50.0㎡	330.0W	74.0%	68.0%	33.0dB	331mm	1,446mm	1,175mm	50.0kg	Φ200mm	質量法82%	
	100V																		

設置 形態	タイプ名	電圧	形名	希望小売 価格 (税抜)	風量(強)	機外静圧	対象 床面積 (目安)※1	消費電力	熱交換効率 ※2		騒音	サイズ			重量	接続 パイプ	フィルター 捕集効率	備考			
									温度	冷房(エンタルピ)		高さ	幅	奥行							
130		電気シャッター	フラットインテリア ハネル	100V	VL-100ZSD2	¥74,800	87㎡/h	0Pa	8.7㎡	44.0W	63.0%	43.0%	38.0dB	440mm	455mm	204mm	6.5kg	Φ100mm	質量法82%		
131			フラット格子 ハネル	100V	VL-100ZSDK2	¥74,800	87㎡/h	0Pa	8.7㎡	44.0W	63.0%	43.0%	38.0dB	440mm	455mm	204mm	6.5kg	Φ100mm	質量法82%		
132			フラット格子 ハネル	100V	VL-100ZSDK2-BR	¥74,800	100㎡/h	0Pa	10.0㎡	44.0W	63.0%	43.0%	38.0dB	213mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
133			フラットインテリア ハネル	100V	VL-150ZSD2	¥126,500	130㎡/h	0Pa	13.0㎡	43.0W	62.0%	42.0%	38.5dB	440mm	455mm	293mm	7.0kg	Φ100mm	質量法82%		
134			フラット格子 ハネル	100V	VL-150ZSDK2	¥126,500	130㎡/h	0Pa	13.0㎡	43.0W	62.0%	42.0%	38.5dB	440mm	455mm	293mm	7.0kg	Φ100mm	質量法82%		
135		電気シャッター 急速排気付 雑ガスセン サー付	フラットインテリア ハネル	100V	VL-200ZSD2	¥80,300	48㎡/h	0Pa	4.8㎡	23.0W	76.0%	58.0%	27.0dB	440mm	455mm	204mm	6.5kg	Φ100mm	質量法82%		
136			フラットインテリア ハネル	100V	VL-200ZSA2	¥91,300	100㎡/h	0Pa	10.0㎡	23.0W	76.0%	58.0%	27.0dB	213mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
137		電気シャッター 急速排気付	フラット格子 ハネル	100V	VL-200ZSDK2	¥80,300	48㎡/h	0Pa	4.8㎡	23.0W	76.0%	58.0%	27.0dB	440mm	455mm	204mm	6.5kg	Φ100mm	質量法82%		
138			フラット格子 ハネル	100V	VL-200ZSDK2-BR	¥80,300	100㎡/h	0Pa	10.0㎡	23.0W	76.0%	58.0%	27.0dB	213mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
139			フラットインテリア ハネル	100V	VL-250ZSD2	¥148,500	139㎡/h	0Pa	13.9㎡	57.0W	60.0%	40.0%	39.5dB	440mm	455mm	293mm	7.0kg	Φ100mm	質量法82%		
140			フラット格子 ハネル	100V	VL-250ZSDK2	¥148,500	139㎡/h	0Pa	13.9㎡	57.0W	60.0%	40.0%	39.5dB	440mm	455mm	293mm	7.0kg	Φ100mm	質量法82%		
141		電気シャッター無	フラットインテリア ハネル	100V	VL-100ZS2	¥63,800	100㎡/h	0Pa	10.0㎡	44.0W	63.0%	43.0%	38.0dB	213mm	455mm	527mm	6.0kg	Φ100mm	質量法82%		
142			フラット格子 ハネル	100V	VL-100ZSK2	¥63,800	100㎡/h	0Pa	10.0㎡	44.0W	63.0%	43.0%	38.0dB	213mm	455mm	527mm	6.0kg	Φ100mm	質量法82%		
143			フラット格子 ハネル	100V	VL-100ZSK2-BR	¥63,800	100㎡/h	0Pa	10.0㎡	44.0W	63.0%	43.0%	38.0dB	213mm	455mm	527mm	6.0kg	Φ100mm	質量法82%		
144			フラットインテリア ハネル	100V	VL-130ZS2	¥78,100	113㎡/h	0Pa	11.3㎡	39.0W	64.0%	44.0%	37.0dB	440mm	455mm	293mm	6.5kg	Φ100mm	質量法82%		
145			フラット格子 ハネル	100V	VL-130ZSK2	¥78,100	113㎡/h	0Pa	11.3㎡	39.0W	64.0%	44.0%	37.0dB	440mm	455mm	293mm	6.5kg	Φ100mm	質量法82%		
146			フラット格子 ハネル	100V	VL-130ZSK2-BR	¥78,100	130㎡/h	0Pa	13.0㎡	39.0W	64.0%	44.0%	37.0dB	302mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
147			フラットインテリア ハネル	100V	VL-150ZS2	¥110,000	150㎡/h	0Pa	15.0㎡	43.0W	62.0%	42.0%	38.5dB	302mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
148			フラット格子 ハネル	100V	VL-150ZSK2	¥110,000	150㎡/h	0Pa	15.0㎡	43.0W	62.0%	42.0%	38.5dB	302mm	455mm	527mm	6.5kg	Φ100mm	質量法82%		
149		インテリア	天井材 使用可能	100V	VL-160ZS3	¥154,000	210㎡/h	0Pa	21.0㎡	56.0W	58.0%	37.0%	41.5dB	558mm	560mm	280mm	16.5kg	Φ150mm	質量法82%		
150			取替専用	100V	VL-120Z2	¥84,700	145㎡/h	0Pa	14.5㎡	48.0W	68.0%	52.0%	40.0dB	567mm	580mm	293mm	11.0kg	Φ100mm	質量法82%		
151		Jファン	フラット格子 ハネル	100V	VL-08ZJ	¥57,500	54㎡/h	0Pa	5.4㎡	13.5W	65.0%	45.0%	35.0dB	213mm	455mm	526mm	6.0kg	Φ100mm	質量法82%		
152			フラット格子 ハネル	100V	VL-08ZJ-BR	¥57,500	54㎡/h	0Pa	5.4㎡	13.5W	65.0%	45.0%	35.0dB	213mm	455mm	526mm	6.0kg	Φ100mm	質量法82%		
153			フラット格子 ハネル	100V	VL-12ZJ	¥59,500	64㎡/h	0Pa	6.4㎡	44.5W	64.0%	44.0%	28.0dB	213mm	455mm	527mm	6.0kg	Φ100mm	質量法82%		
154			フラット格子 ハネル	100V	VL-12ZJ-BR	¥59,500	64㎡/h	0Pa	6.4㎡	44.5W	64.0%	44.0%	28.0dB	213mm	455mm	527mm	6.0kg	Φ100mm	質量法82%		
155		壁掛1パイプ	寒冷地区仕様	引き紐	100V	VL-10S3-D	¥34,800	52㎡/h	0Pa	5.2㎡	22.5W	65.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
156				壁スイッチ	100V	VL-10ES3-D	¥38,700	52㎡/h	0Pa	5.2㎡	22.5W	65.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
157				ワイヤレス リモコン	100V	VL-10SR3-D	¥48,600	47㎡/h	0Pa	4.7㎡	23.5W	65.0%	37.0%	37.5dB	245mm	522mm	168mm	5.0kg	Φ100mm	質量法82%	
158			準寒冷地・温 暖地仕様	引き紐	100V	VL-08S3	¥32,500	41㎡/h	0Pa	4.1㎡	19.0W	66.0%	41.0%	31.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
159				壁スイッチ	100V	VL-08ES3	¥36,300	46㎡/h	0Pa	4.6㎡	19.0W	69.0%	39.0%	32.0dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
160				ワイヤレス リモコン	100V	VL-08SR3	¥46,200	46㎡/h	0Pa	4.6㎡	20.0W	69.0%	39.0%	32.0dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
161				引き紐	100V	VL-10S3	¥32,500	52㎡/h	0Pa	5.2㎡	22.5W	61.0%	38.0%	37.0dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
162				引き紐	100V	VL-10S3-BE	¥32,500	52㎡/h	0Pa	5.2㎡	22.5W	61.0%	38.0%	37.0dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
163				壁スイッチ	100V	VL-10ES3	¥36,300	56㎡/h	0Pa	5.6㎡	23.0W	66.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
164				壁スイッチ	100V	VL-10ES3-BE	¥36,300	56㎡/h	0Pa	5.6㎡	23.0W	66.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
165				ワイヤレス リモコン	100V	VL-10SR3	¥46,200	56㎡/h	0Pa	5.6㎡	24.0W	66.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
166				ワイヤレス リモコン	100V	VL-10SR3-BE	¥46,200	56㎡/h	0Pa	5.6㎡	24.0W	66.0%	37.0%	37.5dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
167			準寒冷地・温 暖地仕様 急速排気付	壁スイッチ	100V	VL-12ESH3	¥45,100	39㎡/h	0Pa	3.9㎡	15.5W	72.0%	41.0%	28.0dB	245mm	522mm	196mm	5.0kg	Φ100mm	質量法82%	
168				ワイヤレス リモコン	100V	VL-12SRH3	¥55,000	39㎡/h	0Pa	3.9㎡	16.0W	72.0%	41.0%	28.0dB	245mm	522mm	168mm	5.0kg	Φ100mm	質量法82%	
169			脱臭機能付	壁スイッチ	100V	VL-08ESN3	¥63,000	33㎡/h	0Pa	3.3㎡	13.0W	76.0%	44.0%	28.5dB	245mm	520mm	185mm	5.0kg	Φ100mm	一過性脱臭 効率80%	
170				引き紐	100V	VL-16U3	¥53,300	93㎡/h	0Pa	9.3㎡	38.0W	78.0%	60.0%	38.5dB	265mm	550mm	185mm	6.0kg	Φ75mm	質量法82%	
171				準寒冷地・ 温暖地仕様	壁スイッチ	100V	VL-16EU3	¥57,600	105㎡/h	0Pa	10.5㎡	33.0W	70.0%	54.0%	38.5dB	265mm	620mm	185mm	6.0kg	Φ75mm	質量法82%
172					引き紐	100V	VL-16U3-D	¥57,000	103㎡/h	0Pa	10.3㎡	38.0W	67.0%	51.0%	39.0dB	285mm	620mm	185mm	6.5kg	Φ75mm	質量法82%
173					引き紐	100V	VL-16U3-BE-D	¥57,000	105㎡/h	0Pa	10.5㎡	33.0W	70.0%	54.0%	39.0dB	285mm	620mm	185mm	6.5kg	Φ75mm	質量法82%
174					壁スイッチ	100V	VL-16EU3-D	¥61,300	105㎡/h	0Pa	10.5㎡	33.0W	70.0%	54.0%	39.0dB	285mm	620mm	185mm	6.5kg	Φ75mm	質量法82%
175					壁スイッチ	100V	VL-16EU3-BE-D	¥61,300	105㎡/h	0Pa	10.5㎡	33.0W	70.0%	54.0%	39.0dB	285mm	620mm	185mm	6.5kg	Φ75mm	質量法82%
176					引き紐	100V	VL-18U3-D	¥63,10													