

格子ルーバ



L4962A (240mm幅用)  
L45112 (220mm幅用)

【受注】

▲希望小売価格 30,000円(税抜)

- 枠 鋼板・白色仕上
- ルーバ アルミ・白色仕上
- 質量 2.3kg (L4962A)  
2.0kg (L45112)

選定	横方向	45度
選定	縦方向	45度

乳白アクリルカバー



B4312A (240mm幅用)  
B4352 (220mm幅用)

【受注】


▲希望小売価格 16,500円(税抜)

- 枠 鋼板・白色仕上
- カバー アクリル・乳白仕上
- 質量 2.0kg

※非常灯には使用できません。

YS4082F+L45112の場合

■配光曲線




■照度率表

反射率 (%)		照度率 (×0.01)														
		室指数														
天井	壁	0.4	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0		
70	30	19	26	30	33	35	37	40	42	43	44	45	46	47		
	10	18	24	27	29	31	33	35	36	37	38	38	39	39		
	30	14	21	25	28	31	33	36	38	40	42	43	45	46		
80	30	14	20	23	26	28	30	32	34	35	36	37	38	39		
	10	12	17	21	24	26	28	31	32	33	35	36	37	38		
	30	10	15	19	22	24	26	29	31	32	34	35	37	38		
70	30	19	25	29	32	34	36	39	40	41	43	43	45	45		
	10	18	23	27	29	31	32	34	35	36	37	38	38	39		
	30	14	20	24	28	30	33	35	37	39	41	42	43	44		
80	30	12	17	21	25	28	30	33	35	37	39	40	42	44		
	10	11	17	21	23	26	28	30	32	33	35	36	37	38		
	30	10	15	19	22	24	26	29	31	32	34	35	36	37		
70	30	14	20	24	27	29	31	34	36	37	38	39	41	42		
	10	13	19	23	25	28	29	31	33	34	35	36	37	37		
	30	12	17	21	24	27	29	32	34	35	37	38	40	41		
80	30	11	17	21	24	27	29	31	32	33	34	35	36	37		
	10	10	15	19	21	24	26	29	30	32	33	34	36	37		
	30	10	15	19	21	24	26	28	30	31	33	34	35	36		
0	0	0	0	9	15	18	21	23	25	27	29	30	32	33	34	35

YS4082F+B4352の場合

■配光曲線



■照度率表

反射率 (%)		照度率 (×0.01)														
		室指数														
天井	壁	0.4	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0		
70	30	23	32	38	42	47	49	53	56	58	60	62	63	65		
	10	22	30	34	38	41	43	46	48	49	51	52	53	54		
	30	16	25	30	35	40	43	48	51	53	57	59	61	63		
80	30	16	24	28	32	36	39	42	45	47	49	50	52	53		
	10	12	20	24	28	30	33	35	39	42	44	47	49	51		
	30	10	12	20	25	30	35	38	43	47	50	53	56	59		
70	30	12	20	25	29	34	37	42	46	48	52	54	57	59		
	10	12	19	24	28	32	35	39	42	44	46	48	50	52		
	30	10	17	21	25	30	32	37	40	42	45	47	49	51		
80	30	16	24	28	32	36	38	42	45	46	48	50	51	52		
	10	12	20	25	29	34	37	42	46	48	52	54	57	59		
	30	10	12	20	24	28	32	35	39	42	44	46	48	50		
70	30	12	20	25	29	34	37	42	46	48	52	54	57	59		
	10	10	17	21	25	30	32	37	40	42	45	47	49	51		
	30	10	12	19	23	28	32	34	38	41	43	45	47	49		
80	30	16	24	28	32	36	38	42	45	46	48	50	51	52		
	10	15	23	27	31	35	37	41	43	45	47	48	50	51		
	30	10	12	20	24	29	33	36	41	44	46	49	51	54		
70	30	12	20	25	29	34	37	42	46	48	52	54	57	59		
	10	10	17	21	25	29	32	36	39	41	44	46	48	50		
	30	10	12	19	23	28	32	34	38	41	43	45	47	49		
80	30	16	24	28	32	36	38	42	45	46	48	50	51	52		
	10	10	17	21	25	29	32	36	39	41	44	46	48	50		
	30	10	12	19	23	27	31	34	38	41	42	45	46	48		
70	30	12	20	25	29	34	37	42	46	48	52	54	57	59		
	10	10	17	21	25	29	32	36	39	41	43	45	47	49		
	30	10	12	19	23	28	32	34	38	41	43	45	47	49		
80	30	16	24	28	32	36	38	42	45	46	48	50	51	52		
	10	10	16	20	24	28	30	34	38	39	42	44	46	47		
	30	10	12	19	23	27	31	34	38	39	41	43	45	47		
0	0	0	0	9	16	20	24	28	30	34	38	39	42	44	46	47

プリズムカバー



D4092A (240mm幅用)  
D4122 (220mm幅用)

【受注】


▲希望小売価格 18,000円(税抜)

- 枠 鋼板・白色仕上
- カバー プリズムアクリル・透明仕上
- 質量 2.0kg

※非常灯には使用できません。

YS4082F+D4122の場合

■配光曲線



■照度率表

反射率 (%)		照度率 (×0.01)												
		室指数												
天井	壁	0.4	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
70	30	26	35	40	44	48	50	53	56	57	59	60	61	63
	10	24	32	36	39	42	43	46	47	48	49	50	51	52
	30	19	29	33	38	42	45	49	52	53	56	58	60	61
80	30	19	27	31	35	39	40	43	46	47	48	49	51	51
	10	16	24	28	32	36	38	41	43	45	47	48	50	51
	30	10	13	22	25	29	34	35	39	42	43	45	47	49
70	30	25	34	39	43	47	49	52	54	55	57	58	59	60
	10	24	32	35	39	42	43	46	47	48	49	50	51	52
	30	19	28	33	37	41	44	47	50	52	54	56	58	59
80	30	18	27	31	35	38	40	43	45	46	48	49	50	51
	10	16	25	29	33	38	40	44	47	49	52	54	56	58
	30	10	15	24	28	32	36	37	41	43	44	46	48	50
70	30	13	22	25	29	33	35	39	41	43	45	47	48	50
	10	19	28	32	36	40	42	45	48	49	51	52	54	55
	30	10	18	27	30	34	38	39	42	44	45	47	48	49
80	30	16	24	28	32	37	39	42	45	47	49	51	53	54
	10	15	24	27	31	35	37	40	42	44	46	47	48	49
	30	10	13	22	25	29	33	35	38	41	42	44	46	47
70	30	15	24	28	32	36	38	41	44	45	47	48	50	51
	10	15	24	27	31	35	36	39	42	43	45	46	47	48
	30	10	13	22	25	29	33	35	38	40	42	44	45	47
80	30	10	13	21	24	28	32	34	37	39	41	43	44	45
	10	0	0	13	21	24	28	32	34	37	39	41	43	44
	30	0	0	13	21	24	28	32	34	37	39	41	43	44

EG=標準出力40W・出力固定形  
EDG=標準出力40W・25~100%連続調光形OFF機能付  
PH=高出力45W・出力固定形

PT=高出力45W・段調光形  
PX=高出力45W・25~100%連続調光形OFF機能付  
PZ=高出力45W・5~100%連続調光形OFF機能付

PN=定格出力PN形・出力固定形  
L=グロー式低力率  
H=グロー式高力率

EL=低力率形1灯用  
EH・ESH=高力率形  
EB=110W PS形