

水冷式チリングユニット 能力表

MCR-KE 冷媒R407C

Table with columns for unit type (MCR-SP40KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP100KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP50KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP120KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP60KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP150KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP80KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

Table with columns for unit type (MCR-SP180KE), inlet/outlet temperatures (20, 22, 25, 30, 32, 35, 37°C), and performance metrics (Cooling capacity, Power consumption, Water flow, etc.)

注1 MCR-SP150KE(60Hz)、冷水出口温度+11°Cの場合、冷水流量の制約により冷水出口温度差=6°Cとしています。
注2 冷水出口温度+11°C以上の性能は冷水出口温度=11°Cの性能と同じになります。
注3 冷却能力値及び消費電力値を記載していない箇所につきましては、機器の運転上の制約により自動的に圧縮機容量70%程度での運転となります。
この領域における性能値につきましては別途お問合せ下さい。
注4 この性能表は計画値です。予告なく変更することがあります。