



EL-C10041N

AHTN




○配光曲線図 (cd/1000lm)



○諸特性

光源		LED11000lm N(定格モード)				
最大 取付 間隔	高さ	4.0m	6.0m	8.0m	10.0m	
	A-A	5.43m	8.21m	10.67m	13.44m	
	B-B	5.00m	7.44m	10.04m	12.16m	
器具効率	上方光束	下方光束		計		
	2.8%	97.2%		100.0%		
保守率	良い	0.830	普通	0.810	悪い	0.770

○直射水平面照度



作業面照明率 (× 0.01)

反射率 (%)			室指数												
天井	壁	床	0.4	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
80	70	30	44	60	71	79	88	93	101	107	110	115	118	121	124
		10	41	56	64	71	78	82	88	92	95	98	100	102	104
	50	30	30	46	56	65	74	80	90	97	101	108	112	117	121
		10	29	43	52	60	68	73	80	85	89	93	96	99	102
70	70	30	42	58	68	77	85	90	97	102	106	110	113	117	119
		10	40	54	63	70	76	80	86	90	93	96	98	100	102
	50	30	30	45	54	63	72	78	87	94	98	104	108	112	116
		10	29	43	51	59	67	72	79	84	87	92	94	98	100
50	30	30	22	36	45	54	63	69	79	86	91	98	103	109	113
		10	22	35	43	51	60	65	73	79	83	88	91	95	98
	10	17	30	38	46	54	59	68	74	78	84	88	93	97	
30	30	30	29	43	52	60	69	74	82	88	92	97	101	105	108
		10	28	41	50	57	65	69	76	81	85	89	92	95	97
	10	21	34	43	50	58	63	71	77	81	86	89	93	96	
0	0	30	21	34	43	51	59	64	72	78	82	88	91	95	99
		10	17	29	37	44	52	57	66	72	75	81	84	89	92
0	0	0	15	27	34	42	50	55	62	68	72	78	81	85	89