


形名	EL-CP5012M 1HZ	電源		○諸特性
出力	連調調色	温度		
モード			(居室シーリング)全灯	光源
オプション1				LED
オプション2				最大 取付 間隔
オプション3				高さ
オプション4				A-A'
オプション5				B-B'
				器具効率
				上方光束
				下方光束
				計
				保守率




○配光曲線図 (cd/1000lm)



○直射水平面照度

(全光束 : 5000 × 1 = 5000lm/台)

照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率 : 1.00)



反射率 (%)																																						
天井	80								70								50								30								20	0				
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
室指数	作業面照度率 (× 0.01)																																					
0.60	61	56	46	44	37	36	31	30	59	54	45	43	36	35	31	30	55	51	43	41	35	35	30	30	51	49	41	40	34	34	30	29	29	27				
0.80	72	66	58	54	48	46	42	41	70	64	56	53	47	46	41	40	65	61	54	51	46	45	40	40	61	57	51	49	44	43	39	39	39	36				
1.00	81	72	66	62	57	54	50	48	78	70	65	60	56	53	49	47	72	67	61	58	54	52	48	47	67	63	58	56	52	50	47	46	45	43				
1.25	88	78	75	68	65	61	58	55	85	76	73	67	64	60	57	55	78	72	69	65	61	59	55	54	73	69	65	62	59	57	54	53	52	50				
1.50	94	82	81	73	72	66	64	61	90	80	79	72	70	65	63	60	83	76	74	69	67	64	61	59	77	73	70	67	64	62	59	58	57	55				
2.00	101	88	90	80	81	74	75	69	97	86	87	79	79	73	73	68	90	82	82	76	75	71	70	67	83	78	77	73	72	69	67	65	65	62				
2.50	106	92	96	85	88	80	82	75	102	89	93	83	86	78	80	74	94	85	87	80	81	76	76	72	87	82	82	77	74	73	71	70	67	67				
3.00	110	94	101	88	94	83	88	79	105	92	97	87	91	82	85	78	97	88	91	84	86	80	81	76	90	84	85	81	81	77	77	74	73	71				
4.00	114	97	107	93	101	89	95	85	109	95	103	91	98	87	93	84	101	91	96	88	91	85	88	82	93	87	89	85	86	82	83	79	78	76				
5.00	117	99	111	95	106	92	101	89	112	97	107	94	102	90	98	87	103	93	99	90	95	88	92	85	95	90	92	87	89	85	87	83	82	79				
7.00	121	101	116	99	112	96	108	93	115	99	111	97	108	94	104	92	106	96	103	93	100	91	97	89	98	92	96	90	93	88	91	87	86	83				
10.00	123	103	120	101	117	99	113	97	118	101	115	99	112	97	109	96	108	97	106	96	104	94	102	93	100	94	98	93	97	91	95	90	89	86				

JIS C 8030:2014

三菱電機照明株式会社