

形名	EL-D00/1 (152NM) AHN	電源		○諸特性 <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">光源</td> <td colspan="4" style="text-align: center;">LED</td> </tr> <tr> <td rowspan="3" style="writing-mode: vertical-rl; text-orientation: upright;">最大 取付 間隔</td> <td>高さ</td> <td colspan="4" style="text-align: center;">H</td> </tr> <tr> <td>A-A'</td> <td colspan="4" style="text-align: center;">1.2 H</td> </tr> <tr> <td>B-B'</td> <td colspan="4" style="text-align: center;">1.2 H</td> </tr> <tr> <td colspan="2" rowspan="2">器具効率</td> <td>上方光束</td> <td>下方光束</td> <td colspan="2">計</td> </tr> <tr> <td>0.0%</td> <td>100.0%</td> <td colspan="2">100.0%</td> </tr> <tr> <td colspan="2">保守率</td> <td>良い</td> <td>0.810</td> <td>普通</td> <td>0.770</td> <td>悪い</td> <td>0.680</td> </tr> </table>	光源		LED				最大 取付 間隔	高さ	H				A-A'	1.2 H				B-B'	1.2 H				器具効率		上方光束	下方光束	計		0.0%	100.0%	100.0%		保守率		良い	0.810	普通	0.770	悪い	0.680
光源		LED																																										
最大 取付 間隔	高さ	H																																										
	A-A'	1.2 H																																										
	B-B'	1.2 H																																										
器具効率		上方光束	下方光束		計																																							
		0.0%	100.0%	100.0%																																								
保守率		良い	0.810	普通	0.770	悪い	0.680																																					
出力	固定出力	温度																																										
モード																																												
オプション1																																												
オプション2																																												
オプション3																																												
オプション4																																												
オプション5																																												

○配光曲線図 (cd/1000lm)

○直射水平面照度 (全光束: 1540 × 1 = 1540lm/台)
 照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率: 1.00)

反射率 (%)																																										
天井	80				70				50				30				20	0																								
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0																				
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数	作業面照明率 (× 0.01)																																									
0.60	70	64	56	53	48	47	43	42	68	63	55	53	48	46	42	42	65	61	54	52	47	46	42	42	62	59	53	51	46	46	42	42	41	40								
0.80	82	75	69	65	61	59	55	54	80	73	68	64	60	58	55	54	76	71	66	63	59	58	54	53	73	69	64	62	58	57	54	53	53	51								
1.00	91	81	78	73	70	67	64	62	88	80	77	72	69	66	64	62	84	78	75	71	68	66	63	62	80	75	72	69	67	65	62	61	61	59								
1.25	98	87	87	79	79	74	73	69	95	86	85	79	78	73	72	69	90	83	82	77	76	72	71	69	86	81	79	76	74	72	70	68	68	66								
1.50	103	90	92	84	85	79	79	75	100	89	90	83	83	78	78	74	94	87	87	81	81	77	76	74	89	84	83	80	79	76	75	73	73	71								
2.00	109	95	100	90	94	85	88	82	106	94	98	89	92	85	87	81	100	91	94	87	88	83	84	80	94	89	90	85	85	82	82	80	79	77								
2.50	113	98	106	93	100	90	94	86	110	97	103	92	97	89	93	86	103	94	98	90	93	87	90	85	98	92	93	89	90	86	87	84	83	82								
3.00	116	100	109	96	104	92	99	90	112	98	106	95	101	92	97	89	106	96	101	93	97	90	93	88	100	94	96	91	93	89	90	87	86	84								
4.00	120	102	114	99	110	96	106	94	116	101	111	98	107	95	103	93	109	98	105	96	102	94	99	92	102	96	99	94	97	92	94	91	90	88								
5.00	122	103	118	101	113	99	110	97	118	102	114	100	110	98	107	96	110	100	107	98	104	96	102	94	104	97	101	96	99	94	97	93	92	90								
7.00	125	105	121	103	118	101	115	100	120	104	117	102	115	100	112	99	112	101	110	100	108	99	106	97	105	99	104	98	102	97	101	96	95	93								
10.00	127	106	124	105	122	104	120	102	122	105	120	104	118	103	116	101	114	102	112	101	111	101	109	100	107	100	106	99	104	99	103	98	97	95								

JIS C 8030:2014

三菱電機照明株式会社