



形名	EL-GT20510N/AM AHTJ	電源	
出力	段調光	温度	
モード	定格		
オプション1	EL-XGA005		
オプション2			
オプション3			
オプション4			
オプション5			



○諸特性

光源		LED					
最大 取付 間隔	高さ	H					
	A-A'	1.0 H					
	B-B'	1.0 H					
器具効率		上方光束	下方光束	計			
		0.2%	99.7%	99.9%			
保守率		良い	0.830	普通	0.810	悪い	0.770


○配光曲線図 (cd/1000lm)



○直射水平面照度

(全光束 : 19900 × 1 = 19900lm/台)

照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率 : 1.00)



反射率 (%)																																		
天井	80								70								50								30								20	0
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0				
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	作業面照明率 (× 0.01)																																	
0.60	86	79	76	72	69	67	65	64	85	78	75	72	69	67	65	64	82	77	74	71	68	67	65	64	80	75	73	70	68	67	64	64	64	63
0.80	95	86	85	80	79	76	74	72	93	85	84	79	78	75	74	72	90	84	82	79	77	75	73	72	87	82	81	78	76	74	73	72	72	70
1.00	101	91	92	85	85	81	81	78	99	90	90	84	84	81	80	78	95	88	88	83	83	80	79	77	91	86	86	82	81	79	78	77	77	75
1.25	106	94	97	89	91	85	87	83	104	93	96	89	90	85	86	82	99	91	93	87	88	84	84	82	95	89	90	86	86	83	83	81	81	80
1.50	110	97	102	92	96	89	91	86	107	96	100	91	94	88	90	85	102	93	96	90	92	87	88	85	97	92	93	89	89	86	86	84	84	82
2.00	115	100	107	96	102	93	98	90	111	99	105	95	100	92	96	90	105	96	101	94	97	91	93	89	100	94	97	92	93	90	91	88	88	86
2.50	118	101	111	98	106	96	102	93	114	100	109	97	104	95	100	93	108	98	104	96	100	94	97	92	102	96	99	94	96	92	94	91	90	89
3.00	120	103	114	100	110	98	106	96	116	101	111	99	107	97	104	95	109	99	106	97	102	95	100	94	103	97	101	96	98	94	96	93	92	90
4.00	122	104	118	102	114	100	111	98	118	103	115	101	111	99	108	98	111	101	108	99	106	98	103	96	105	99	103	97	101	96	99	95	94	93
5.00	124	105	120	103	117	102	114	100	120	104	117	102	114	101	111	100	113	102	110	100	108	99	106	98	106	100	104	98	103	97	101	96	96	94
7.00	126	106	123	105	121	104	118	102	122	105	119	104	117	103	115	102	114	103	112	102	110	101	109	100	107	100	106	100	104	99	103	98	97	96
10.00	128	107	126	106	124	105	122	104	123	106	121	105	120	104	118	103	115	103	114	103	112	102	111	101	108	101	107	101	106	100	105	100	99	97

JIS C 8030:2014

三菱電機照明株式会社