

器具情報

機種	EL-LF-HH4532A/3
ランプ	LDL40T・N/27/37・G3(非常灯)
光束	3700 lm
光束比	60%
保守率	0.86
廊下巾	2.00 m
照度範囲	2.00 lx

照度範囲

器具高さ(m)		2.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
単体配置	A1	6.3	6.5	6.5	6.6	6.7	6.8	6.9	6.9	7.0	7.1	7.2	7.2	7.3	7.4	7.4	7.5
	A'1	6.1	6.2	6.3	6.4	6.6	6.6	6.7	6.8	6.9	7.0	7.1	7.1	7.2	7.2	7.3	7.4
	B1	4.9	5.1	5.2	5.3	5.4	5.5	5.6	5.6	5.7	5.8	5.9	6.0	6.0	6.1	6.2	6.3
直線配置	A2	15.1	15.5	15.7	15.9	16.3	16.5	16.8	17.0	17.2	17.4	17.7	17.9	18.1	18.3	18.5	18.6
	B2	11.9	12.2	12.5	12.8	13.0	13.3	13.6	13.8	14.0	14.2	14.5	14.7	14.9	15.0	15.2	15.5
四角配置	A4	14.6	14.9	15.1	15.3	15.6	15.8	16.0	16.2	16.4	16.6	16.8	16.9	17.1	17.3	17.5	17.6
	B4	10.6	10.9	11.1	11.3	11.6	11.8	12.0	12.2	12.4	12.6	12.8	13.0	13.2	13.3	13.5	13.7
壁からの距離 (最大)	A0	4.8	4.9	5.0	5.0	5.1	5.2	5.2	5.3	5.3	5.4	5.4	5.4	5.5	5.5	5.5	5.5
	B0	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.8	2.9	3.0	3.0	3.1	3.1	3.2	3.2

器具高さ(m)		3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	4.6	4.7	4.8	4.9	5.0	5.1
単体配置	A1	7.5	7.6	7.6	7.7	7.8	7.8	7.8	7.9	7.9	7.9	8.0	8.0	8.0	8.1	8.1	8.1
	A'1	7.4	7.5	7.5	7.6	7.7	7.7	7.7	7.8	7.8	7.9	7.9	7.9	7.9	8.0	8.0	8.0
	B1	6.3	6.4	6.5	6.5	6.6	6.6	6.7	6.8	6.8	6.9	6.9	7.0	7.0	7.1	7.1	7.1
直線配置	A2	18.8	19.0	19.1	19.3	19.6	19.6	19.8	19.9	20.0	20.2	20.3	20.5	20.6	20.7	20.9	20.9
	B2	15.6	15.8	15.9	16.1	16.3	16.5	16.6	16.8	16.9	17.1	17.2	17.4	17.5	17.7	17.9	17.9
四角配置	A4	17.8	18.0	18.1	18.3	18.5	18.6	18.7	18.9	19.0	19.1	19.3	19.4	19.5	19.6	19.8	19.8
	B4	13.9	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	15.5	15.6	15.7	15.9	16.0
壁からの距離 (最大)	A0	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.7	5.7	5.7	5.7	5.7	5.7
	B0	3.2	3.2	3.3	3.3	3.3	3.3	3.4	3.4	3.4	3.4	3.4	3.5	3.5	3.5	3.6	3.6

器具高さ(m)		5.2	5.3	5.4	5.5	5.6	5.7	5.8	5.9	6.0	6.1	6.2	6.3	6.4	6.5	6.6	6.7
単体配置	A1	8.2	8.2	8.2	8.2	8.3	8.3	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
	A'1	8.0	8.1	8.1	8.1	8.1	8.1	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.3	8.3
	B1	7.2	7.2	7.2	7.3	7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.5	7.5	7.5	7.5	7.5
直線配置	A2	21.0	21.1	21.2	21.3	21.4	21.6	21.6	21.7	21.9	21.9	22.0	22.0	22.1	22.2	22.3	22.3
	B2	18.1	18.2	18.3	18.5	18.6	18.7	18.8	18.9	19.1	19.1	19.3	19.4	19.5	19.6	19.7	19.8
四角配置	A4	19.9	20.0	20.1	20.2	20.3	20.4	20.5	20.5	20.7	20.7	20.8	20.9	21.0	21.0	21.1	21.2
	B4	16.1	16.2	16.3	16.5	16.6	16.7	16.8	16.9	17.1	17.1	17.2	17.3	17.4	17.5	17.6	17.7
壁からの距離 (最大)	A0	5.7	5.7	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.9	5.9	5.9	5.9	5.9	6.0
	B0	3.6	3.6	3.7	3.7	3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.9	3.9	3.9

器具高さ(m)		6.8	6.9	7.0	7.1	7.2	7.3	7.4	7.5	7.6	7.7	7.8	7.9	8.0	8.1	8.2	8.3
単体配置	A1	8.4	8.4	8.5													
	A'1	8.3	8.3	8.3													
	B1	7.6	7.6	7.6													
直線配置	A2	22.4	22.5	22.7													
	B2	19.9	20.0	20.1													
四角配置	A4	21.3	21.3	21.5													
	B4	17.8	17.9	18.0													
壁からの距離 (最大)	A0	6.0	6.0	6.0													
	B0	3.9	3.9	3.9													