



	EL-LR-WF2600L/4
	TATE
	AHTN




○諸特性

光源		LED2780lm(定格モード)					
最大 取付 間隔	高さ	1.5m	2.0m	2.5m	3.0m		
	A-A	1.92m	2.55m	3.17m	3.79m		
	B-B	2.33m	2.95m	3.62m	4.31m		
器具効率		上方光束	下方光束	計			
		17.2%	82.9%	100.0%			
保守率		良い	0.830	普通	0.810	悪い	0.770

○配光曲線図 (cd/1000lm)



○直射水平面照度



作業面照明率(×0.01)															
反射率(%)			室指数												
天井	壁	床	0.4	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0
80	70	30	42	57	67	75	83	88	96	101	105	110	113	116	119
		10	39	53	61	67	74	78	83	87	90	93	95	98	100
	50	30	29	42	52	60	69	75	84	91	95	102	106	111	115
		10	28	40	49	56	63	68	75	80	83	88	91	94	97
70	30	30	21	34	42	50	59	65	75	82	87	95	100	106	112
		10	21	33	40	48	55	60	68	74	78	83	87	91	95
	10	10	16	27	34	41	49	54	62	69	73	79	83	88	93
		70	30	40	54	64	71	79	83	91	96	99	103	106	110
50	50	30	28	41	50	58	66	71	80	86	91	97	100	105	109
		10	27	39	47	54	61	66	73	78	81	85	88	92	94
	30	30	21	33	41	48	57	62	72	79	83	90	95	101	106
		10	20	32	39	46	54	58	66	72	76	81	84	89	92
30	50	30	26	38	46	53	61	65	73	78	82	87	91	95	98
		10	25	37	44	50	57	61	68	73	76	80	83	86	89
	30	30	19	31	38	45	53	58	66	72	77	82	87	92	96
		10	19	30	37	44	51	55	62	68	71	76	80	84	87
0	30	10	15	25	32	39	46	50	58	64	67	73	77	81	85
		30	18	29	36	42	49	54	61	67	70	75	79	83	87
	10	10	18	28	35	41	48	52	59	64	67	72	75	79	82
		10	14	24	31	37	44	48	55	60	64	69	73	77	80
0	0	0	12	21	27	33	39	43	49	54	58	62	66	70	73