


|        |                     |    |  |      |
|--------|---------------------|----|--|------|
| 形名     | EL-LR-Y7001N/4 AHTN | 電源 |  | ○諸特性 |
| 出力     | 段調光                 | 温度 |  |      |
| モード    | 定格                  |    |  |      |
| オプション1 |                     |    |  |      |
| オプション2 |                     |    |  |      |
| オプション3 |                     |    |  |      |
| オプション4 |                     |    |  |      |
| オプション5 |                     |    |  |      |




|        |      |       |       |        |       |    |       |
|--------|------|-------|-------|--------|-------|----|-------|
| 光源     |      | LED   |       |        |       |    |       |
| 最大取付間隔 | 高さ   | H     |       |        |       |    |       |
|        | A-A' | 1.3 H |       |        |       |    |       |
|        | B-B' | 1.2 H |       |        |       |    |       |
| 器具効率   |      | 上方光束  | 下方光束  | 計      |       |    |       |
|        |      | 4.6%  | 95.4% | 100.0% |       |    |       |
| 保守率    |      | 良い    | 0.830 | 普通     | 0.810 | 悪い | 0.770 |

○配光曲線図 (cd/1000lm)



○直射水平面照度 (全光束: 6700 × 1 = 6700lm/台)



| 反射率 (%) |                 |     |     |     |     |    |     |    |     |     |     |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |    |    |    |    |    |    |
|---------|-----------------|-----|-----|-----|-----|----|-----|----|-----|-----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|----|----|----|----|----|----|----|
| 天井      | 80              |     |     |     |     |    |     |    | 70  |     |     |    | 50  |    |     |    | 30  |    |     |    | 20  | 0  |     |    |     |    |    |    |    |    |    |    |    |    |
| 壁       | 70              | 50  | 30  | 10  | 70  | 50 | 30  | 10 | 70  | 50  | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 10  | 0  |     |    |     |    |    |    |    |    |    |    |    |    |
| 床       | 30              | 10  | 30  | 10  | 30  | 10 | 30  | 10 | 30  | 10  | 30  | 10 | 30  | 10 | 30  | 10 | 30  | 10 | 30  | 10 | 30  | 10 | 30  | 10 | 30  | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0  |    |
| 室指数     | 作業面照明率 (× 0.01) |     |     |     |     |    |     |    |     |     |     |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |    |    |    |    |    |    |
| 0.60    | 61              | 56  | 46  | 44  | 37  | 36 | 31  | 30 | 59  | 54  | 45  | 43 | 36  | 35 | 30  | 30 | 55  | 51 | 43  | 41 | 35  | 35 | 30  | 30 | 52  | 49 | 41 | 40 | 34 | 34 | 30 | 29 | 29 | 27 |
| 0.80    | 72              | 66  | 58  | 54  | 48  | 46 | 41  | 40 | 70  | 64  | 56  | 53 | 47  | 45 | 41  | 40 | 65  | 61 | 54  | 51 | 46  | 44 | 40  | 39 | 61  | 58 | 51 | 49 | 44 | 43 | 39 | 39 | 39 | 36 |
| 1.00    | 80              | 72  | 66  | 61  | 56  | 53 | 49  | 48 | 77  | 70  | 64  | 60 | 55  | 53 | 49  | 47 | 72  | 67 | 61  | 58 | 53  | 51 | 47  | 46 | 67  | 63 | 58 | 56 | 52 | 50 | 46 | 46 | 45 | 43 |
| 1.25    | 88              | 78  | 74  | 68  | 65  | 61 | 57  | 55 | 85  | 76  | 72  | 67 | 63  | 60 | 57  | 54 | 78  | 72 | 68  | 64 | 61  | 58 | 55  | 53 | 73  | 69 | 65 | 62 | 59 | 57 | 54 | 52 | 52 | 50 |
| 1.50    | 93              | 82  | 81  | 73  | 71  | 66 | 64  | 60 | 90  | 80  | 78  | 72 | 70  | 65 | 63  | 60 | 83  | 76 | 74  | 69 | 67  | 63 | 61  | 59 | 77  | 73 | 70 | 67 | 64 | 62 | 59 | 58 | 57 | 54 |
| 2.00    | 101             | 88  | 90  | 80  | 81  | 74 | 74  | 69 | 97  | 86  | 87  | 79 | 79  | 73 | 73  | 68 | 90  | 82 | 82  | 76 | 75  | 71 | 70  | 67 | 83  | 78 | 77 | 73 | 72 | 69 | 67 | 65 | 65 | 62 |
| 2.50    | 106             | 91  | 96  | 85  | 88  | 79 | 81  | 74 | 102 | 89  | 93  | 83 | 86  | 78 | 79  | 74 | 94  | 85 | 87  | 80 | 81  | 76 | 76  | 72 | 87  | 82 | 82 | 77 | 77 | 74 | 73 | 70 | 70 | 67 |
| 3.00    | 109             | 94  | 101 | 88  | 93  | 83 | 87  | 79 | 105 | 92  | 97  | 86 | 90  | 82 | 85  | 78 | 97  | 88 | 91  | 83 | 85  | 79 | 81  | 76 | 90  | 84 | 85 | 81 | 81 | 77 | 77 | 74 | 73 | 71 |
| 4.00    | 114             | 97  | 107 | 92  | 100 | 88 | 95  | 84 | 109 | 95  | 103 | 91 | 97  | 87 | 92  | 83 | 101 | 91 | 96  | 88 | 91  | 84 | 87  | 81 | 93  | 88 | 90 | 85 | 86 | 82 | 83 | 79 | 78 | 76 |
| 5.00    | 117             | 99  | 111 | 95  | 105 | 92 | 100 | 88 | 112 | 97  | 107 | 93 | 102 | 90 | 97  | 87 | 103 | 93 | 99  | 90 | 95  | 88 | 92  | 85 | 96  | 90 | 92 | 87 | 89 | 85 | 87 | 83 | 82 | 79 |
| 7.00    | 121             | 101 | 116 | 98  | 111 | 96 | 107 | 93 | 115 | 99  | 111 | 97 | 107 | 94 | 104 | 92 | 106 | 96 | 103 | 94 | 100 | 91 | 97  | 89 | 98  | 92 | 96 | 90 | 94 | 89 | 91 | 87 | 86 | 83 |
| 10.00   | 123             | 103 | 120 | 101 | 116 | 99 | 113 | 97 | 118 | 101 | 115 | 99 | 112 | 97 | 109 | 96 | 109 | 98 | 106 | 96 | 104 | 94 | 102 | 93 | 101 | 94 | 99 | 93 | 97 | 92 | 95 | 90 | 89 | 86 |

JIS C 8030:2014

三菱電機照明株式会社