

器具情報

機種	EL-LW-HH4102A/2
ランプ	LDL40T・N/17/25・G3(非常灯)
光束	2500 lm
光束比	88%
保守率	0.86
廊下巾	2.00 m
照度範囲	2.00 lx

照度範囲

器具高さ(m)		2.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
単体配置	A1	6.2	6.3	6.4	6.5	6.6	6.7	6.8	6.8	6.9	7.0	7.1	7.1	7.2	7.3	7.3	7.4
	A'1	6.2	6.3	6.4	6.5	6.6	6.7	6.8	6.8	6.9	7.0	7.1	7.1	7.2	7.2	7.3	7.4
	B1	4.9	5.0	5.1	5.2	5.3	5.4	5.5	5.5	5.6	5.7	5.8	5.9	5.9	6.0	6.1	6.2
直線配置	A2	15.1	15.5	15.7	16.0	16.2	16.5	16.8	16.9	17.2	17.4	17.6	17.8	18.0	18.2	18.4	18.6
	B2	11.8	12.0	12.3	12.6	12.9	13.1	13.3	13.6	13.8	14.0	14.2	14.4	14.6	14.8	15.0	15.2
四角配置	A4	14.7	15.0	15.2	15.4	15.7	15.9	16.1	16.3	16.4	16.6	16.8	17.0	17.1	17.3	17.5	17.6
	B4	10.5	10.8	11.0	11.2	11.4	11.6	11.9	12.1	12.3	12.5	12.7	12.8	13.0	13.2	13.4	13.5
壁からの距離 (最大)	A0	5.0	5.0	5.1	5.1	5.1	5.2	5.2	5.2	5.3	5.3	5.3	5.4	5.4	5.4	5.4	5.5
	B0	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.7	2.8	2.8	2.9	3.0	3.0	3.1	3.1

器具高さ(m)		3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	4.6	4.7	4.8	4.9	5.0	5.1
単体配置	A1	7.4	7.5	7.5	7.6	7.6	7.7	7.7	7.8	7.8	7.8	7.9	7.9	7.9	8.0	8.0	8.0
	A'1	7.4	7.5	7.5	7.6	7.7	7.7	7.8	7.8	7.8	7.9	7.9	8.0	8.0	8.0	8.1	8.1
	B1	6.2	6.3	6.4	6.4	6.5	6.5	6.6	6.6	6.7	6.7	6.8	6.8	6.9	6.9	7.0	7.0
直線配置	A2	18.7	18.9	19.1	19.2	19.4	19.5	19.7	19.8	19.9	20.1	20.2	20.3	20.5	20.6	20.7	20.8
	B2	15.4	15.6	15.7	15.9	16.0	16.2	16.3	16.5	16.7	16.8	17.0	17.1	17.2	17.4	17.6	17.7
四角配置	A4	17.8	18.0	18.1	18.2	18.4	18.5	18.7	18.8	18.9	19.1	19.2	19.3	19.4	19.5	19.7	19.8
	B4	13.7	13.9	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.0	15.2	15.3	15.4	15.6	15.7	15.8
壁からの距離 (最大)	A0	5.5	5.5	5.5	5.5	5.5	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.7	5.7	5.7	5.7
	B0	3.1	3.1	3.2	3.2	3.2	3.3	3.3	3.3	3.4	3.4	3.4	3.4	3.4	3.5	3.5	3.5

器具高さ(m)		5.2	5.3	5.4	5.5	5.6	5.7	5.8	5.9	6.0	6.1	6.2	6.3	6.4	6.5	6.6	6.7
単体配置	A1	8.0	8.1	8.1	8.1	8.1	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.3
	A'1	8.1	8.1	8.1	8.2	8.2	8.2	8.2	8.2	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
	B1	7.0	7.1	7.1	7.1	7.2	7.2	7.2	7.2	7.3	7.3	7.3	7.3	7.3	7.4	7.4	7.4
直線配置	A2	20.9	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	22.0	22.0	22.1	22.2	22.2
	B2	17.8	17.9	18.0	18.1	18.3	18.4	18.5	18.6	18.8	18.9	18.9	19.0	19.1	19.2	19.3	19.5
四角配置	A4	19.8	20.0	20.1	20.1	20.3	20.4	20.4	20.5	20.7	20.7	20.8	20.9	21.0	21.1	21.1	21.2
	B4	15.9	16.0	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	17.0	17.1	17.2	17.3	17.4	17.5
壁からの距離 (最大)	A0	5.7	5.7	5.7	5.7	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
	B0	3.5	3.6	3.6	3.6	3.6	3.6	3.6	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7

器具高さ(m)		6.8	6.9	7.0	7.1	7.2	7.3	7.4	7.5	7.6	7.7	7.8	7.9	8.0	8.1	8.2	8.3
単体配置	A1	8.3	8.3	8.3													
	A'1	8.3	8.3	8.4													
	B1	7.4	7.4	7.5													
直線配置	A2	22.3	22.4	22.5													
	B2	19.5	19.6	19.7													
四角配置	A4	21.3	21.4	21.5													
	B4	17.6	17.6	17.8													
壁からの距離 (最大)	A0	5.8	5.9	5.8													
	B0	3.7	3.7	3.8													