


形名	EL-S20041N/W VHJ	電源		○諸特性
出力	固定出力	温度		
モード				
オプション1	EL-XL002			
オプション2				
オプション3				
オプション4				
オプション5				




光源		LED				
最大 取付 間隔	高さ	H				
	A-A'	0.9 H				
	B-B'	0.9 H				
器具効率	上方光束	下方光束	計			
	0.0%	100.0%	100.0%			
保守率	良い	0.810	普通	0.770	悪い	0.680

○配光曲線図 (cd/1000lm)



○直射水平面照度 (全光束: 12000 × 1 = 12000lm/台)  
照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率: 1.00)



反射率 (%)																																		
天井	80								70				50				30				20	0												
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0												
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0						
室指数	作業面照明率 (× 0.01)																																	
0.60	85	78	74	71	68	66	64	63	84	77	74	70	68	66	64	63	81	76	73	70	67	66	63	63	79	74	71	69	66	65	63	62	62	61
0.80	94	86	84	79	78	74	73	71	92	85	83	79	77	74	73	71	89	83	81	78	76	74	72	71	86	81	80	77	75	73	71	71	70	69
1.00	100	90	91	84	84	80	80	77	98	89	90	84	83	80	79	77	94	87	87	83	82	79	78	76	91	86	85	81	80	78	77	76	76	74
1.25	106	94	97	89	90	85	86	82	103	93	95	88	89	84	85	81	99	91	92	87	87	84	83	81	95	89	89	86	85	83	82	80	80	79
1.50	109	96	101	92	95	88	90	85	107	95	99	91	94	88	89	85	101	93	96	89	91	87	87	84	97	91	92	88	89	86	85	83	83	82
2.00	114	99	107	96	101	92	97	90	111	98	105	95	100	92	96	89	105	96	100	93	96	91	93	89	100	94	96	92	93	90	90	88	87	86
2.50	117	101	111	98	106	95	102	93	114	100	108	97	104	95	100	93	108	98	103	96	100	93	97	91	102	96	99	94	96	92	94	90	90	88
3.00	120	103	114	100	109	97	105	95	116	101	111	99	107	97	103	95	109	99	105	97	102	95	99	93	103	97	101	95	98	94	96	92	92	90
4.00	122	104	118	102	114	100	110	98	118	103	114	101	111	99	108	98	111	101	108	99	106	98	103	96	105	99	103	97	101	96	99	95	94	93
5.00	124	105	120	103	117	102	114	100	120	104	117	102	114	101	111	99	113	102	110	100	108	99	106	98	106	100	104	98	102	97	101	96	96	94
7.00	126	106	123	105	121	104	118	102	122	105	119	104	117	103	115	102	114	103	112	102	110	101	109	100	107	101	106	100	104	99	103	98	97	96
10.00	128	107	126	106	124	105	122	104	123	106	121	105	120	104	118	103	115	104	114	103	112	102	111	101	108	101	107	101	106	100	105	100	99	97

JIS C 8030:2014

三菱電機照明株式会社