

形名	EL-SK12010N/5 AHTZ	電源	
出力	段調光	温度	
モード	定格		
オプション1			
オプション2			
オプション3			
オプション4			
オプション5			

○配光曲線図 (cd/1000lm)

○諸特性

光源		LED					
最大 取付 間隔	高さ	H					
	A-A'	1.2 H					
	B-B'	1.2 H					
器具効率		上方光束		下方光束		計	
		0.0%		100.0%		100.0%	
保守率		良い	0.830	普通	0.810	悪い	0.770

○直射水平面照度 (全光束 : 12050 × 1 = 12050lm/台)

照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - - H3.00m (保守率 : 1.00)

反射率 (%)																			
天井	80				70				50				30				20	0	
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0	
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	作業面照明率 (× 0.01)																		
0.60	64	59	50	47	41	40	35	34	62	58	49	47	40	39	35	34	59	55	47
0.80	76	69	62	58	53	51	46	45	74	68	61	57	52	50	46	45	70	65	59
1.00	84	76	71	66	61	58	55	53	82	74	69	65	61	58	54	53	77	71	67
1.25	92	82	79	73	70	66	63	60	89	80	77	72	69	65	63	60	84	77	74
1.50	97	86	85	78	77	71	70	66	94	84	83	77	75	71	69	66	88	81	80
2.00	105	91	95	84	87	79	80	74	101	90	92	83	85	78	79	74	95	87	88
2.50	110	95	101	89	93	84	87	80	106	93	98	88	91	83	86	79	99	90	93
3.00	113	97	105	92	98	88	93	84	109	96	102	91	96	87	91	83	102	93	96
4.00	118	100	111	96	105	93	101	89	113	99	108	95	103	92	98	89	106	96	101
5.00	120	102	115	99	110	96	106	93	116	100	111	97	107	95	103	92	108	98	104
7.00	123	104	119	101	116	99	112	97	119	102	115	100	112	98	109	96	111	100	108
10.00	126	105	123	104	120	102	117	100	121	104	119	102	116	101	114	99	113	101	111

JIS C 8030:2014

三菱電機照明株式会社