


形名	EL-SL30024W/W 1HTN	電源		○諸特性
出力	段調光	温度		
モード	省電力 (AK)			
オプション1				
オプション2				
オプション3				
オプション4				
オプション5				




光源		LED					
最大取付間隔	高さ	H					
	A-A'	0.8 H					
	B-B'	0.8 H					
器具効率		上方光束	下方光束	計			
		0.0%	100.0%	100.0%			
保守率		良い	0.670	普通	0.630	悪い	0.560

○配光曲線図 (cd/1000lm)



○直射水平面照度 (全光束 : 2490 × 1 = 2490lm/台)
照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率 : 1.00)



反射率 (%)																																										
天井	80								70								50								30								20	0								
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0												
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数	作業面照明率 (×0.01)																																									
0.60	102	94	94	90	90	87	87	85	100	93	94	89	89	87	87	85	98	92	93	89	89	87	86	85	96	91	91	89	88	87	86	85	85	84								
0.80	107	97	100	94	95	91	92	90	106	97	99	93	95	91	92	90	103	96	97	93	94	91	91	89	100	95	96	92	92	90	90	89	89	88								
1.00	111	100	104	96	99	94	96	92	109	99	103	96	98	94	95	92	105	98	100	95	97	93	94	92	102	97	98	94	95	93	93	92	91	91								
1.25	114	102	108	99	103	97	99	95	112	101	106	98	102	96	99	95	108	99	103	97	100	95	97	94	104	98	100	96	98	95	95	94	93	92								
1.50	117	103	110	100	106	98	102	97	114	102	109	100	104	98	101	96	109	100	105	98	102	97	99	96	105	99	102	97	99	96	97	95	95	94								
2.00	120	104	114	102	110	100	107	99	117	103	112	101	108	100	105	99	111	102	108	100	105	99	102	98	106	100	104	99	102	98	100	97	96	95								
2.50	122	105	117	103	113	102	110	101	119	104	114	103	111	101	108	100	113	102	109	101	107	100	105	99	107	101	105	100	103	99	101	98	98	96								
3.00	123	106	119	104	116	103	113	102	120	105	116	103	113	102	110	101	113	103	111	102	108	101	106	100	108	101	106	100	104	100	103	99	98	97								
4.00	125	107	122	105	119	104	116	103	121	106	118	104	116	103	114	103	114	104	112	103	110	102	109	101	108	102	107	101	105	100	104	100	99	98								
5.00	127	107	124	106	121	105	119	104	122	106	120	105	118	104	116	104	115	104	113	103	112	103	110	102	109	102	107	102	106	101	105	101	100	98								
7.00	128	108	126	107	124	106	122	106	124	107	122	106	120	105	118	105	116	104	115	104	113	103	112	103	109	103	108	102	107	102	106	101	101	99								
10.00	129	108	127	107	126	107	124	107	125	107	123	106	122	106	121	106	117	105	116	104	115	104	114	104	110	103	109	102	108	102	108	102	101	99								

JIS C 8030:2014

三菱電機照明株式会社