

| 形名 | EL-WC1000L/W AHN | 電源 | | ○諸特性 <table border="1"> <tr> <th colspan="2">光源</th> <th colspan="4">LED</th> </tr> <tr> <td rowspan="3">最大 取付 間隔</td> <td>高さ</td> <td colspan="4">H</td> </tr> <tr> <td>A-A'</td> <td colspan="4">1.3 H</td> </tr> <tr> <td>B-B'</td> <td colspan="4">1.3 H</td> </tr> <tr> <td colspan="2">器具効率</td> <td>上方光束</td> <td>下方光束</td> <td colspan="2">計</td> </tr> <tr> <td colspan="2"></td> <td>19.2%</td> <td>80.8%</td> <td colspan="2">100.0%</td> </tr> <tr> <td colspan="2">保守率</td> <td>良い</td> <td>0.690</td> <td>普通</td> <td>0.670</td> <td>悪い</td> <td>0.630</td> </tr> </table> | 光源 | | LED | | | | 最大 取付 間隔 | 高さ | H | | | | A-A' | 1.3 H | | | | B-B' | 1.3 H | | | | 器具効率 | | 上方光束 | 下方光束 | 計 | | | | 19.2% | 80.8% | 100.0% | | 保守率 | | 良い | 0.690 | 普通 | 0.670 | 悪い | 0.630 |
|----------------|------------------|-------|-------|---|-------|----|-------|--|--|--|----------------|----|---|--|--|--|------|-------|--|--|--|------|-------|--|--|--|------|--|------|------|---|--|--|--|-------|-------|--------|--|-----|--|----|-------|----|-------|----|-------|
| 光源 | | LED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 最大 取付 間隔 | 高さ | H | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | A-A' | 1.3 H | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | B-B' | 1.3 H | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 器具効率 | | 上方光束 | 下方光束 | | 計 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 19.2% | 80.8% | 100.0% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 保守率 | | 良い | 0.690 | 普通 | 0.670 | 悪い | 0.630 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 出力 | 固定出力 | 温度 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| モード | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| オプション1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| オプション2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| オプション3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| オプション4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| オプション5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

○配光曲線図 (cd/1000lm)

○直射水平面照度 (全光束: 1150 × 1 = 1150lm/台)

照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - · H3.00m (保守率: 1.00)

| 反射率 (%) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------|-----------------|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 天井 | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 20 | 0 | | | | | | | | | | | | | | | | |
| 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 | | | | | | | | | | | | | |
| 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0 | | | | | | | | | | | | | |
| 室指数 | 作業面照度率 (× 0.01) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.60 | 57 | 52 | 42 | 40 | 33 | 32 | 27 | 26 | 54 | 50 | 40 | 39 | 32 | 31 | 26 | 26 | 49 | 46 | 37 | 36 | 30 | 29 | 25 | 25 | 44 | 42 | 35 | 33 | 28 | 28 | 24 | 24 | 23 | 20 |
| 0.80 | 68 | 62 | 53 | 50 | 43 | 42 | 37 | 36 | 64 | 59 | 51 | 48 | 42 | 40 | 36 | 35 | 58 | 54 | 47 | 45 | 39 | 38 | 34 | 33 | 52 | 49 | 43 | 42 | 37 | 36 | 32 | 32 | 31 | 28 |
| 1.00 | 76 | 68 | 61 | 57 | 51 | 49 | 44 | 43 | 72 | 65 | 59 | 55 | 50 | 47 | 43 | 42 | 64 | 60 | 54 | 51 | 46 | 45 | 41 | 40 | 58 | 55 | 49 | 47 | 43 | 42 | 38 | 38 | 37 | 33 |
| 1.25 | 83 | 74 | 69 | 64 | 59 | 56 | 52 | 50 | 79 | 71 | 66 | 61 | 57 | 54 | 51 | 49 | 70 | 65 | 61 | 57 | 53 | 51 | 47 | 46 | 63 | 59 | 55 | 53 | 49 | 48 | 45 | 44 | 43 | 39 |
| 1.50 | 89 | 78 | 75 | 68 | 66 | 61 | 58 | 55 | 84 | 75 | 72 | 66 | 63 | 59 | 57 | 54 | 75 | 69 | 66 | 61 | 59 | 56 | 53 | 51 | 67 | 63 | 60 | 57 | 54 | 52 | 49 | 48 | 47 | 43 |
| 2.00 | 96 | 84 | 85 | 76 | 76 | 69 | 68 | 63 | 91 | 80 | 80 | 73 | 72 | 67 | 66 | 62 | 81 | 74 | 73 | 68 | 67 | 63 | 61 | 58 | 72 | 68 | 66 | 63 | 61 | 59 | 57 | 55 | 54 | 49 |
| 2.50 | 101 | 87 | 91 | 80 | 82 | 74 | 76 | 69 | 95 | 84 | 86 | 77 | 79 | 72 | 73 | 67 | 85 | 77 | 78 | 72 | 72 | 68 | 67 | 64 | 76 | 71 | 71 | 67 | 66 | 63 | 62 | 60 | 58 | 54 |
| 3.00 | 105 | 90 | 95 | 84 | 88 | 78 | 81 | 73 | 99 | 86 | 91 | 81 | 84 | 76 | 78 | 71 | 88 | 80 | 82 | 75 | 76 | 71 | 72 | 68 | 79 | 74 | 74 | 70 | 70 | 67 | 66 | 64 | 62 | 57 |
| 4.00 | 109 | 93 | 102 | 88 | 95 | 84 | 89 | 79 | 103 | 90 | 96 | 85 | 91 | 81 | 85 | 77 | 92 | 83 | 87 | 79 | 82 | 76 | 78 | 73 | 82 | 77 | 78 | 74 | 75 | 71 | 72 | 69 | 67 | 62 |
| 5.00 | 112 | 95 | 106 | 91 | 100 | 87 | 95 | 83 | 106 | 92 | 100 | 88 | 95 | 84 | 91 | 81 | 94 | 85 | 90 | 82 | 86 | 79 | 83 | 76 | 84 | 79 | 81 | 76 | 78 | 74 | 75 | 72 | 70 | 65 |
| 7.00 | 116 | 98 | 111 | 94 | 106 | 91 | 102 | 88 | 109 | 94 | 105 | 91 | 101 | 88 | 97 | 86 | 97 | 88 | 94 | 85 | 91 | 83 | 88 | 81 | 87 | 82 | 84 | 80 | 82 | 78 | 80 | 76 | 74 | 68 |
| 10.00 | 119 | 99 | 115 | 97 | 111 | 95 | 108 | 93 | 112 | 96 | 109 | 94 | 106 | 92 | 103 | 90 | 100 | 90 | 97 | 88 | 95 | 86 | 93 | 84 | 89 | 84 | 87 | 82 | 85 | 81 | 84 | 79 | 77 | 72 |

JIS C 8030:2014

三菱電機照明株式会社