

形名	EL-WVE1707C/H	電源		○諸特性																																								
出力	固定出力	温度																																										
モード																																												
オプション1																																												
オプション2																																												
オプション3																																												
オプション4																																												
オプション5																																												
○配光曲線図 (cd/1000lm)				<table border="1"> <tr> <td colspan="2">光源</td> <td colspan="4">LDA5L-G-E17/40/S</td> </tr> <tr> <td rowspan="3">最大 取付 間隔</td> <td>高さ</td> <td colspan="4">H</td> </tr> <tr> <td>A-A'</td> <td colspan="4">-</td> </tr> <tr> <td>B-B'</td> <td colspan="4">-</td> </tr> <tr> <td colspan="2" rowspan="2">器具効率</td> <td>上方光束</td> <td>下方光束</td> <td colspan="2">計</td> </tr> <tr> <td>9.8%</td> <td>7.9%</td> <td colspan="2">17.8%</td> </tr> <tr> <td colspan="2">保守率</td> <td>良い</td> <td>0.680</td> <td>普通</td> <td>0.660</td> <td>悪い</td> <td>0.630</td> </tr> </table>	光源		LDA5L-G-E17/40/S				最大 取付 間隔	高さ	H				A-A'	-				B-B'	-				器具効率		上方光束	下方光束	計		9.8%	7.9%	17.8%		保守率		良い	0.680	普通	0.660	悪い	0.630
光源		LDA5L-G-E17/40/S																																										
最大 取付 間隔	高さ	H																																										
	A-A'	-																																										
	B-B'	-																																										
器具効率		上方光束	下方光束	計																																								
		9.8%	7.9%	17.8%																																								
保守率		良い	0.680	普通	0.660	悪い	0.630																																					
				○直射水平面照度 (全光束: 470 × 1 = 470lm/台) 照度 (lx) — H1.50m --- H2.00m ---- H2.50m -.-.- H3.00m (保守率: 1.00) 																																								

反射率 (%)																					
天井	80				70				50				30				20	0			
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	作業面照明率 (× 0.01)																				
0.60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
0.80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
1.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
1.25	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
1.50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2.50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

JIS C 8030:2014

三菱電機照明株式会社