

形名	MY-B230233/N 2ACTZ	電源	
出力	段調光	温度	
モード	節電		
オプション1			
オプション2			
オプション3			
オプション4			
オプション5			

○配光曲線図 (cd/1000lm)

○諸特性

光源		LED					
最大 取付 間隔	高さ	H					
	A-A'	1.3 H					
	B-B'	1.2 H					
器具効率		上方光束		下方光束		計	
		0.0%		100.0%		100.0%	
保守率		良い	0.810	普通	0.770	悪い	0.680

○直射水平面照度 (全光束：2210 × 1 = 2210lm/台)

照度 (lx) — H1.50m --- H2.00m - - - H2.50m - · - - H3.00m (保守率：1.00)

反射率(%)																			
天井	80				70				50				30				20	0	
壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0	
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	作業面照明率(×0.01)																		
0.60	62	57	47	45	38	37	32	32	60	56	46	44	38	37	32	32	57	53	45
0.80	74	67	59	56	50	48	43	42	72	66	58	55	49	47	43	42	68	63	56
1.00	82	74	68	63	58	55	51	50	80	72	67	62	58	55	51	49	75	69	64
1.25	90	80	77	70	67	63	60	57	87	78	75	69	66	62	59	57	82	75	72
1.50	95	84	83	75	74	68	67	63	92	82	81	74	72	68	66	63	86	79	77
2.00	103	90	92	82	84	76	77	71	100	88	90	81	82	76	76	71	93	85	85
2.50	108	93	99	87	91	82	84	77	104	92	96	86	89	81	83	77	97	89	91
3.00	112	96	103	90	96	86	90	81	108	94	100	89	94	85	88	81	101	91	95
4.00	116	99	109	95	103	91	98	87	112	97	106	93	101	90	96	87	105	95	100
5.00	119	101	113	97	108	94	104	91	115	99	110	96	105	93	101	90	107	97	103
7.00	123	103	118	100	114	98	110	96	118	102	114	99	111	97	107	95	110	99	107
10.00	125	105	122	103	119	101	116	99	121	103	118	102	115	100	112	98	112	101	110

JIS C 8030:2014

三菱電機照明株式会社