

器具情報

機種	一般出カタイプ
ランプ	LED667lm(非常灯)
光束	667 lm
光束比	100.00%
保守率	0.93
廊下巾	2.00 m
照度範囲	2.00 lx

照度範囲

器具高さ(m)		2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	
単体配置	A1	5.5	5.6	5.7	5.8	5.9	5.9	6.0	6.1	6.1	6.0	6.0	6.0	6.0	5.9	5.8	5.7	5.6
	B1	5.3	5.4	5.5	5.6	5.7	5.6	5.7	5.8	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.2	5.2
直線配置	A2	13.0	13.2	13.6	13.9	14.2	14.5	14.8	15.0	15.2	15.4	15.7	15.9	16.0	16.3	16.4	16.6	
	B2	12.7	13.0	13.3	13.6	13.9	14.1	14.4	14.6	14.9	15.0	15.3	15.5	15.7	15.8	16.0	16.0	
四角配置	A4	11.8	11.9	12.1	12.3	12.5	12.7	12.9	13.1	13.2	13.4	13.6	13.9	14.1	14.4	14.6	14.8	
	B4	10.7	11.0	11.3	11.6	11.9	12.1	12.3	12.5	12.7	13.0	13.2	13.4	13.6	13.8	14.0	14.3	
壁からの距離 (最大)	A0	3.8	3.8	3.9	3.9	4.0	4.1	4.1	4.2	4.2	4.2	4.2	4.3	4.3	4.3	4.3	4.3	
	B0	3.0	3.1	3.3	3.4	3.6	3.7	3.8	3.9	3.9	4.0	4.0	4.0	4.0	4.0	4.0	4.0	

器具高さ(m)		3.7	3.8	3.9	4.0												
単体配置	A1	5.6	5.5	4.6	4.7												
	B1	5.1	4.8	4.9	5.0												
直線配置	A2	16.7	16.8	16.9	17.0												
	B2	15.9	16.0	16.2	16.2												
四角配置	A4	15.0	15.2	15.4	15.5												
	B4	14.4	14.6	14.8	14.9												
壁からの距離 (最大)	A0	4.3	4.2	4.2	4.1												
	B0	4.0	3.8	3.8	3.7												

器具高さ(m)																	
単体配置	A1																
	B1																
直線配置	A2																
	B2																
四角配置	A4																
	B4																
壁からの距離 (最大)	A0																
	B0																

器具高さ(m)																	
単体配置	A1																
	B1																
直線配置	A2																
	B2																
四角配置	A4																
	B4																
壁からの距離 (最大)	A0																
	B0																

器具高さ(m)																	
単体配置	A1																
	B1																
直線配置	A2																
	B2																
四角配置	A4																
	B4																
壁からの距離 (最大)	A0																
	B0																

器具高さ(m)																	
単体配置	A1																
	B1																
直線配置	A2																
	B2																
四角配置	A4																
	B4																
壁からの距離 (最大)	A0																
	B0																