

## 配管長別冷凍能力

インバータ：一体空冷

周囲温度：35℃

形式	冷媒	形名	蒸発温度 (℃)	配管相当長別能力(kW)									
				50Hz					60Hz				
				0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
スクロール 一体空冷 (インバータ)	R404A	ERAV-EP75A(出力周波数75Hz)	-5	26.85	24.91	24.06	22.89	22.23	26.85	24.91	24.06	22.89	22.23
		ERAV-EP110A(出力周波数90Hz)		36.07	33.98	33.11	31.85	31.13	36.07	33.98	33.11	31.85	31.13
		ERAV-EP110A(出力周波数80Hz)		32.31	30.73	30.11	29.19	28.66	32.31	30.73	30.11	29.19	28.66
		ECAV-EP150A(60Hz+定格運転時)		44.48	42.64	41.98	40.97	40.39	50.58	47.92	46.84	45.28	44.40
		ECAV-EP185A(90Hz+定格運転時)		56.39	54.30	53.54	52.36	51.69	60.48	57.91	56.99	55.58	54.78
		ECAV-EP185A(80Hz+定格運転時)		52.60	50.76	50.17	49.22	48.70	57.19	54.97	54.20	52.99	52.31
		ECAV-EP225A(60Hz+定格運転時)		62.65	60.07	59.15	57.71	56.90	71.21	67.67	66.27	64.19	63.01
		ECAV-EP260A(90Hz+定格運転時)		74.87	73.14	72.85	72.27	71.99	84.83	82.49	81.93	80.93	80.71
		ECAV-EP260A(80Hz+定格運転時)		71.10	69.54	69.33	68.85	68.64	79.27	77.28	76.90	76.16	75.80
		ECAV-EP300A-Q (90Hz+定格、サブクールユニット運転時)		86.65	84.72	84.44	83.84	83.58	95.07	92.69	92.21	91.31	90.86
		ECAV-EP335A-Q (90Hz+定格、サブクールユニット運転時)		92.69	90.63	90.34	89.69	89.41	100.48	97.97	97.46	96.51	96.03
		ECAV-EP150B(60Hz+定格運転時)		46.87	44.78	43.99	42.80	42.13	51.86	49.14	48.04	46.43	45.52
		ECAV-EP185B(90Hz+定格運転時)		58.56	56.28	55.49	54.24	53.54	62.45	59.74	58.73	57.20	56.32
		ECAV-EP225B(60Hz+定格運転時)		66.20	63.29	62.20	60.54	59.60	73.90	70.10	68.57	66.31	65.02
		ECAV-EP260B(90Hz+定格運転時)	79.05	77.11	76.75	76.04	75.69	85.67	83.38	82.86	81.91	81.42	
		ECAV-EP300B-Q (90Hz+定格、サブクールユニット運転時)	90.84	88.62	88.20	87.39	86.98	97.64	95.03	94.43	93.35	92.79	
		ECAV-EP335B-Q (90Hz+定格、サブクールユニット運転時)	96.98	94.61	94.16	93.29	92.86	102.97	100.21	99.59	98.45	97.86	
		ERAV-EP75A(出力周波数75Hz)	-10	23.23	21.49	20.72	19.67	19.08	23.23	21.49	20.72	19.67	19.08
		ERAV-EP110A(出力周波数90Hz)		31.12	29.15	28.36	27.42	26.61	31.12	29.15	28.36	27.42	26.61
		ERAV-EP110A(出力周波数80Hz)		27.81	26.40	25.84	25.01	24.54	27.81	26.40	25.84	25.01	24.54
		ECAV-EP150A(60Hz+定格運転時)		38.18	36.55	35.95	35.03	34.51	42.90	40.60	39.67	38.32	37.56
		ECAV-EP185A(90Hz+定格運転時)		48.65	46.49	45.81	44.76	44.17	52.19	49.81	48.98	47.70	46.98
		ECAV-EP185A(80Hz+定格運転時)		45.10	43.47	42.94	42.09	41.62	49.49	47.21	46.51	45.43	44.82
		ECAV-EP225A(60Hz+定格運転時)		54.00	51.68	50.83	49.53	48.79	61.37	58.19	56.91	55.03	53.96
		ECAV-EP260A(90Hz+定格運転時)		64.44	62.91	62.64	62.10	61.84	72.41	70.37	69.88	68.99	68.53
		ECAV-EP260A(80Hz+定格運転時)		61.19	59.82	59.62	59.18	58.98	68.15	66.42	66.06	65.39	65.05
		ECAV-EP300A-Q (90Hz+定格、サブクールユニット運転時)		74.58	72.88	72.62	72.07	71.81	81.99	79.88	79.44	78.62	78.20
		ECAV-EP335A-Q (90Hz+定格、サブクールユニット運転時)		79.97	78.15	77.87	77.27	77.00	86.82	84.58	84.12	83.24	82.80
ECAV-EP150B(60Hz+定格運転時)	40.22	38.36		37.65	36.58	35.98	44.39	41.99	41.01	39.59	38.78		
ECAV-EP185B(90Hz+定格運転時)	50.71	48.65		47.91	46.77	46.12	53.91	51.49	50.57	49.18	48.39		
ECAV-EP225B(60Hz+定格運転時)	57.23	54.60		53.59	52.08	51.21	63.97	60.52	59.11	57.04	55.87		
ECAV-EP260B(90Hz+定格運転時)	68.14	66.43	66.08	65.43	65.10	73.94	71.90	71.42	70.55	70.09			
ECAV-EP300B-Q (90Hz+定格、サブクールユニット運転時)	78.29	76.32	75.92	75.17	74.79	84.47	82.14	81.58	80.58	80.06			
ECAV-EP335B-Q (90Hz+定格、サブクールユニット運転時)	83.74	81.64	81.21	80.41	80.00	89.25	86.79	86.20	85.15	84.59			

配管長別能力表	WAN19-327R	
---------	------------	--

形式	冷媒	形名	蒸発温度 (℃)	配管相当長別能力(kW)									
				50Hz					60Hz				
				0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
スクロール 一体空冷（中・低温用）	R404A	ERAV-EP75A(出力周波数75Hz)	-12	21.87	20.21	19.47	18.47	17.91	21.87	20.21	19.47	18.47	17.91
		ERAV-EP110A(出力周波数90Hz)		29.11	27.34	26.59	25.52	24.92	29.11	27.34	26.59	25.52	24.92
		ERAV-EP110A(出力周波数80Hz)		26.11	24.78	24.24	23.45	23.00	26.11	24.78	24.24	23.45	23.00
		ECAV-EP150A(60Hz+定格運転時)		35.81	34.26	33.68	32.81	32.31	40.04	37.88	37.01	35.74	35.03
		ECAV-EP185A(90Hz+定格運転時)		45.40	43.57	42.92	41.91	41.35	48.90	46.77	45.97	44.76	44.07
		ECAV-EP185A(80Hz+定格運転時)		42.28	40.74	40.23	39.42	38.97	46.17	44.30	43.63	42.59	42.01
		ECAV-EP225A(60Hz+定格運転時)		50.74	48.53	47.72	46.47	45.76	57.67	54.63	53.40	51.61	50.58
		ECAV-EP260A(90Hz+定格運転時)		60.51	59.06	58.80	58.28	58.03	67.76	65.85	65.38	64.54	64.10
		ECAV-EP260A(80Hz+定格運転時)		57.46	56.16	55.96	55.54	55.35	63.97	62.33	61.99	61.35	61.02
		ECAV-EP300A-Q (90Hz+定格、サブクールユニット運転時)		70.04	68.43	68.18	67.63	67.39	77.05	75.05	74.63	73.84	73.43
		ECAV-EP335A-Q (90Hz+定格、サブクールユニット運転時)		75.15	73.42	73.15	72.57	72.31	81.63	79.52	79.06	78.23	77.80
		ECAV-EP150B(60Hz+定格運転時)		37.73	35.96	35.27	34.25	33.67	41.60	39.32	38.39	37.05	36.29
		ECAV-EP185B(90Hz+定格運転時)		47.73	45.76	45.05	43.95	43.33	50.70	48.38	47.50	46.17	45.41
		ECAV-EP225B(60Hz+定格運転時)		53.85	51.33	50.36	48.90	48.07	60.23	56.92	55.55	53.57	52.44
		ECAV-EP260B(90Hz+定格運転時)		64.03	62.40	62.07	61.44	61.12	69.52	67.58	67.11	66.27	65.82
		ECAV-EP300B-Q (90Hz+定格、サブクールユニット運転時)		73.56	71.69	71.31	70.58	70.21	79.49	77.27	76.73	75.77	75.26
		ECAV-EP335B-Q (90Hz+定格、サブクールユニット運転時)		78.75	76.75	76.34	75.56	75.17	84.05	81.70	81.13	80.12	79.58
		ERAV-EP75A(出力周波数75Hz)		19.92	18.37	17.69	16.76	16.25	19.92	18.37	17.69	16.76	16.25
		ERAV-EP110A(出力周波数90Hz)		26.35	24.74	24.05	23.07	22.51	26.35	24.74	24.05	23.07	22.51
		ERAV-EP110A(出力周波数80Hz)		23.68	22.45	21.95	21.22	20.81	23.68	22.45	21.95	21.22	20.81
		ECAV-EP150A(60Hz+定格運転時)		32.42	30.98	30.45	29.63	29.17	35.98	34.03	33.24	32.10	31.45
	ECAV-EP185A(90Hz+定格運転時)	41.05	39.37	38.78	37.85	37.33	44.30	42.41	41.67	40.54	39.90		
	ECAV-EP185A(80Hz+定格運転時)	38.23	36.82	36.35	35.61	35.19	41.85	40.13	39.51	38.55	38.01		
	ECAV-EP225A(60Hz+定格運転時)	46.08	44.03	43.26	42.10	41.44	52.37	49.54	48.39	46.72	45.77		
	ECAV-EP260A(90Hz+定格運転時)	54.88	53.55	53.30	52.81	52.58	61.14	59.40	58.97	58.21	57.80		
	ECAV-EP260A(80Hz+定格運転時)	52.12	50.92	50.73	50.34	50.15	57.99	56.48	56.16	55.56	55.25		
	ECAV-EP300A-Q (90Hz+定格、サブクールユニット運転時)	63.53	62.05	61.81	61.30	61.06	69.96	68.12	67.72	66.98	66.60		
	ECAV-EP335A-Q (90Hz+定格、サブクールユニット運転時)	68.28	66.68	66.43	65.88	65.62	74.21	72.26	71.84	71.05	70.65		
	ECAV-EP150B(60Hz+定格運転時)	34.15	32.51	31.88	30.93	30.40	37.62	35.53	34.68	33.44	32.74		
	ECAV-EP185B(90Hz+定格運転時)	43.45	41.62	40.95	39.91	39.33	46.08	43.93	43.11	41.87	41.17		
	ECAV-EP225B(60Hz+定格運転時)	49.00	46.65	45.74	44.37	43.59	54.85	51.75	50.46	48.60	47.54		
	ECAV-EP260B(90Hz+定格運転時)	58.13	56.63	56.32	55.73	55.42	63.17	61.37	60.93	60.14	59.72		
	ECAV-EP300B-Q (90Hz+定格、サブクールユニット運転時)	66.78	65.05	64.69	64.01	63.66	72.32	70.27	69.76	68.85	68.38		
	ECAV-EP335B-Q (90Hz+定格、サブクールユニット運転時)	71.57	69.73	69.34	68.61	68.24	76.56	74.38	73.84	72.89	72.38		
	ERAV-EP75A(出力周波数75Hz)	18.68	17.21	16.56	15.68	15.20	18.68	17.21	16.56	15.68	15.20		
	ERAV-EP110A(出力周波数90Hz)	24.65	23.10	22.44	21.52	20.99	24.65	23.10	22.44	21.52	20.99		
	ERAV-EP110A(出力周波数80Hz)	22.14	20.97	20.50	19.82	19.42	22.14	20.97	20.50	19.82	19.42		
	ECAV-EP150A(60Hz+定格運転時)	30.26	28.91	28.39	27.62	27.19	33.43	31.61	30.88	29.81	29.21		
	ECAV-EP185A(90Hz+定格運転時)	38.30	36.72	36.15	35.28	34.79	41.52	39.65	38.94	37.88	37.27		
	ECAV-EP185A(80Hz+定格運転時)	35.66	34.34	33.89	33.19	32.80	39.11	37.48	36.89	35.98	35.47		
	ECAV-EP225A(60Hz+定格運転時)	43.12	41.17	40.44	39.33	38.70	49.00	46.32	45.22	43.62	42.72		
	ECAV-EP260A(90Hz+定格運転時)	51.30	50.05	49.81	49.35	49.12	56.96	55.33	54.93	54.21	53.84		
ECAV-EP260A(80Hz+定格運転時)	48.72	47.60	47.41	47.03	46.86	54.19	52.77	52.46	51.89	51.60			
ECAV-EP300A-Q (90Hz+定格、サブクールユニット運転時)	59.38	57.99	57.76	57.28	57.05	65.44	63.71	63.32	62.62	62.26			
ECAV-EP335A-Q (90Hz+定格、サブクールユニット運転時)	63.86	62.36	62.11	61.59	61.35	69.46	67.61	67.21	66.46	66.08			
ECAV-EP150B(60Hz+定格運転時)	31.87	30.33	29.73	28.83	28.32	35.11	33.14	32.34	31.17	30.52			
ECAV-EP185B(90Hz+定格運転時)	40.72	38.98	38.33	37.35	36.79	43.14	41.11	40.32	39.15	38.48			
ECAV-EP225B(60Hz+定格運転時)	45.92	43.68	42.81	41.50	40.76	51.43	48.46	47.23	45.45	44.44			
ECAV-EP260B(90Hz+定格運転時)	54.38	52.97	52.66	52.10	51.81	59.12	57.43	57.00	56.24	55.84			
ECAV-EP300B-Q (90Hz+定格、サブクールユニット運転時)	62.46	60.83	60.48	59.83	59.50	67.76	65.81	65.32	64.46	64.00			
ECAV-EP335B-Q (90Hz+定格、サブクールユニット運転時)	67.00	65.25	64.88	64.18	63.83	71.78	69.72	69.20	68.28	67.80			
配管長別能力表			WAN19-327R										

形式	冷媒	形名	蒸発温度 (℃)	配管相当長別能力(kW)									
				50Hz					60Hz				
				0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
スクロール 一体空冷 (中・低温用)	R404A	ERAV-EP75A(出力周波数75Hz)	-20	16.91	15.56	14.97	14.16	13.71	16.91	15.56	14.97	14.16	13.71
		ERAV-EP110A(出力周波数90Hz)		22.07	20.76	20.16	19.32	18.85	22.07	20.76	20.16	19.32	18.85
		ERAV-EP110A(出力周波数80Hz)		19.94	18.87	18.44	17.82	17.46	19.94	18.87	18.44	17.82	17.46
		ECAV-EP150A(60Hz+定格運転時)		27.19	25.95	25.48	24.77	24.37	29.84	28.21	27.56	26.61	26.07
		ECAV-EP185A(90Hz+定格運転時)		34.23	32.94	32.42	31.63	31.19	37.22	35.71	35.07	34.09	33.53
		ECAV-EP185A(80Hz+定格運転時)		32.00	30.80	30.40	29.76	29.40	35.20	33.71	33.18	32.35	31.88
		ECAV-EP225A(60Hz+定格運転時)		38.90	37.11	36.43	35.41	34.83	44.19	41.72	40.70	39.24	38.40
		ECAV-EP260A(90Hz+定格運転時)		46.20	45.06	44.84	44.41	44.20	51.03	49.57	49.20	48.56	48.23
		ECAV-EP260A(80Hz+定格運転時)		43.87	42.85	42.68	42.33	42.16	48.76	47.48	47.19	46.67	46.40
		ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)		53.47	52.20	51.99	51.54	51.33	58.98	57.41	57.05	56.41	56.07
		ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)		57.60	56.23	56.00	55.52	55.29	62.68	61.01	60.63	59.94	59.58
		ECAV-EP150B(60Hz+定格運転時)		28.63	27.22	26.67	25.85	25.38	31.56	29.77	29.03	27.98	27.38
		ECAV-EP185B(90Hz+定格運転時)		36.81	35.20	34.60	33.68	33.16	38.94	37.08	36.35	35.27	34.65
		ECAV-EP225B(60Hz+定格運転時)		41.52	39.45	38.63	37.42	36.73	46.53	43.78	42.62	40.97	40.03
		ECAV-EP260B(90Hz+定格運転時)		49.03	47.74	47.45	46.93	46.66	53.34	51.79	51.39	50.69	50.32
		ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)		56.29	54.81	54.48	53.88	53.57	61.22	59.43	58.97	58.17	57.74
		ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)		60.46	58.86	58.51	57.86	57.53	64.93	63.04	62.55	61.70	61.24
		ERAV-EP75A(出力周波数75Hz)		14.21	13.05	12.53	11.84	11.46	14.21	13.05	12.53	11.84	11.46
		ERAV-EP110A(出力周波数90Hz)		18.28	17.19	16.68	15.98	15.58	18.28	17.19	16.68	15.98	15.58
		ECAV-EP150A(60Hz+定格運転時)		22.48	21.43	21.03	20.43	20.09	24.46	23.14	22.61	21.84	21.40
		ECAV-EP185A(90Hz+定格運転時)		28.20	27.17	26.74	26.08	25.70	30.97	29.70	29.14	28.31	27.84
		ECAV-EP225A(60Hz+定格運転時)		32.46	30.93	30.33	29.45	28.95	36.84	34.72	33.84	32.58	31.87
		ECAV-EP260A(90Hz+定格運転時)		38.39	37.43	37.24	36.87	36.69	42.07	40.87	40.56	40.04	39.76
		ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)		44.41	43.35	43.16	42.77	42.59	49.07	47.75	47.44	46.88	46.60
	ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)	47.95	46.81	46.60	46.18	45.99	52.24	50.83	50.50	49.91	49.61		
	ECAV-EP150B(60Hz+定格運転時)	23.69	22.49	22.02	21.32	20.93	26.20	24.70	24.08	23.19	22.69		
	ECAV-EP185B(90Hz+定格運転時)	30.77	29.38	28.86	28.06	27.61	32.51	30.92	30.29	29.36	28.84		
	ECAV-EP225B(60Hz+定格運転時)	34.79	33.00	32.28	31.22	30.63	39.00	36.60	35.59	34.15	33.33		
	ECAV-EP260B(90Hz+定格運転時)	40.82	39.73	39.48	39.03	38.80	44.47	43.14	42.79	42.19	41.87		
	ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)	46.85	45.59	45.31	44.79	44.52	51.14	49.62	49.22	48.53	48.16		
	ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)	50.42	49.07	48.76	48.20	47.92	54.34	52.72	52.29	51.56	51.16		
	ERAV-EP75A(出力周波数75Hz)	11.82	10.83	10.40	9.82	9.50	11.82	10.83	10.40	9.82	9.50		
	ERAV-EP110A(出力周波数90Hz)	14.99	14.04	13.63	13.05	12.73	14.99	14.04	13.63	13.05	12.73		
	ECAV-EP150A(60Hz+定格運転時)	18.31	17.44	17.11	16.61	16.33	19.86	18.80	18.38	17.77	17.43		
	ECAV-EP185A(90Hz+定格運転時)	22.95	22.08	21.73	21.20	20.90	25.52	24.38	23.92	23.24	22.85		
	ECAV-EP225A(60Hz+定格運転時)	26.76	25.47	24.97	24.22	23.80	30.33	28.54	27.80	26.74	26.14		
	ECAV-EP260A(90Hz+定格運転時)	31.46	30.67	30.51	30.21	30.06	34.96	33.97	33.73	33.30	33.08		
	ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)	36.36	35.50	35.34	35.03	34.87	40.25	39.15	38.90	38.44	38.20		
	ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)	39.35	38.41	38.24	37.90	37.73	42.93	41.76	41.49	41.00	40.74		
	ECAV-EP150B(60Hz+定格運転時)	19.30	18.32	17.92	17.35	17.03	21.54	20.30	19.79	19.07	18.66		
	ECAV-EP185B(90Hz+定格運転時)	25.33	24.17	23.72	23.05	22.67	26.78	25.45	24.92	24.15	23.71		
	ECAV-EP225B(60Hz+定格運転時)	28.82	27.29	26.67	25.77	25.26	32.28	30.22	29.35	28.12	27.43		
	ECAV-EP260B(90Hz+定格運転時)	33.52	32.61	32.40	32.02	31.83	36.54	35.44	35.15	34.64	34.37		
	ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)	38.44	37.40	37.16	36.73	36.51	42.12	40.86	40.51	39.93	39.62		
	ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)	41.45	40.33	40.07	39.61	39.37	44.84	43.49	43.12	42.51	42.17		

配管長別能力表	WAN19-327R
---------	------------

形式	冷媒	形名	蒸発温度 (℃)	配管相当長別能力(kW)									
				50Hz					60Hz				
				0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
スクロール 一体空冷 (中・低温用)	R404A	ERAV-EP75A(出力周波数75Hz)	-35	9.73	8.91	8.56	8.08	7.82	9.73	8.91	8.56	8.08	7.82
		ERAV-EP110A(出力周波数90Hz)		12.19	11.30	10.98	10.52	10.27	12.19	11.30	10.98	10.52	10.27
		ECAV-EP150A(60Hz+定格運転時)		14.67	13.97	13.70	13.30	13.08	16.02	15.20	14.88	14.41	14.15
		ECAV-EP185A(90Hz+定格運転時)		18.49	17.65	17.38	16.97	16.74	20.89	19.74	19.38	18.83	18.52
		ECAV-EP225A(60Hz+定格運転時)		21.81	20.74	20.32	19.71	19.36	24.64	23.17	22.56	21.69	21.20
		ECAV-EP260A(90Hz+定格運転時)		25.41	24.76	24.63	24.38	24.26	28.18	27.41	27.22	26.90	26.72
		ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)		29.33	28.62	28.50	28.26	28.14	32.50	31.62	31.43	31.06	30.88
		ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)		31.81	31.04	30.91	30.65	30.52	34.72	33.78	33.57	33.19	32.99
		ECAV-EP150B(60Hz+定格運転時)		15.48	14.69	14.38	13.92	13.66	17.60	16.59	16.18	15.59	15.27
		ECAV-EP185B(90Hz+定格運転時)		20.50	19.55	19.18	18.64	18.33	21.74	20.66	20.24	19.61	19.26
		ECAV-EP225B(60Hz+定格運転時)		23.59	22.31	21.79	21.04	20.61	26.36	24.64	23.90	22.88	22.30
		ECAV-EP260B(90Hz+定格運転時)		27.11	26.38	26.21	25.91	25.75	29.56	28.67	28.44	28.03	27.81
		ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)	31.10	30.26	30.07	29.72	29.54	34.16	33.14	32.86	32.39	32.14	
		ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)	33.60	32.69	32.48	32.11	31.92	36.43	35.33	35.04	34.54	34.27	
		ERAV-EP75A(出力周波数75Hz)	-40	7.94	7.28	6.99	6.61	6.40	7.94	7.28	6.99	6.61	6.40
		ERAV-EP110A(出力周波数90Hz)		9.88	8.96	8.72	8.37	8.18	9.88	8.96	8.72	8.37	8.18
		ECAV-EP150A(60Hz+定格運転時)		11.55	11.01	10.81	10.50	10.33	12.96	12.33	12.09	11.74	11.54
		ECAV-EP185A(90Hz+定格運転時)		14.81	13.89	13.69	13.38	13.21	17.08	15.78	15.50	15.07	14.84
		ECAV-EP225A(60Hz+定格運転時)		17.59	16.73	16.39	15.90	15.62	19.78	18.60	18.11	17.42	17.03
		ECAV-EP260A(90Hz+定格運転時)		20.83	20.32	20.22	20.03	19.93	22.80	22.20	22.06	21.83	21.70
		ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)		23.30	22.75	22.66	22.46	22.38	25.85	25.17	25.01	24.75	24.60
		ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)		25.32	24.73	24.63	24.42	24.33	27.66	26.94	26.77	26.48	26.33
		ECAV-EP150B(60Hz+定格運転時)		12.23	11.61	11.37	11.02	10.82	14.35	13.55	13.23	12.77	12.51
		ECAV-EP185B(90Hz+定格運転時)		16.27	15.53	15.24	14.82	14.58	17.41	16.56	16.23	15.74	15.46
		ECAV-EP225B(60Hz+定格運転時)		19.11	18.07	17.64	17.03	16.68	21.23	19.83	19.23	18.39	17.93
		ECAV-EP260B(90Hz+定格運転時)		21.60	21.03	20.90	20.67	20.55	23.54	22.84	22.66	22.34	22.17
		ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)	24.77	24.11	23.96	23.70	23.56	27.26	26.45	26.24	25.87	25.68	
		ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)	26.82	26.10	25.95	25.66	25.51	29.12	28.26	28.03	27.64	27.43	
		ERAV-EP75A(出力周波数75Hz)	-45	6.46	5.92	5.69	5.37	5.20	6.46	5.92	5.69	5.37	5.20
		ERAV-EP110A(出力周波数90Hz)		7.28	7.02	6.83	6.57	6.43	7.28	7.02	6.83	6.57	6.43
		ECAV-EP150A(60Hz+定格運転時)		8.97	8.56	8.41	8.18	8.06	10.66	10.19	10.02	9.77	9.64
		ECAV-EP185A(90Hz+定格運転時)		10.92	10.77	10.63	10.40	10.28	12.59	12.48	12.26	11.94	11.76
		ECAV-EP225A(60Hz+定格運転時)		14.11	13.43	13.17	12.78	12.57	15.76	14.83	14.45	13.91	13.61
		ECAV-EP260A(90Hz+定格運転時)		15.44	15.06	15.00	14.87	14.80	17.09	16.66	16.57	16.41	16.32
		ECAV-EP300A-Q (90Hz+定格、サブクーユニット運転時)		17.72	17.34	17.25	17.11	17.06	19.69	19.18	19.08	18.88	18.78
		ECAV-EP335A-Q (90Hz+定格、サブクーユニット運転時)		19.31	18.89	18.80	18.64	18.58	21.11	20.57	20.45	20.24	20.14
ECAV-EP150B(60Hz+定格運転時)	9.54	9.08		8.90	8.64	8.49	11.81	11.19	10.94	10.59	10.39		
ECAV-EP185B(90Hz+定格運転時)	12.65	12.07		11.86	11.53	11.35	13.77	13.11	12.85	12.47	12.26		
ECAV-EP225B(60Hz+定格運転時)	15.38	14.55		14.21	13.72	13.45	16.91	15.79	15.31	14.66	14.29		
ECAV-EP260B(90Hz+定格運転時)	17.00	16.56		16.47	16.31	16.22	18.46	17.93	17.80	17.57	17.45		
ECAV-EP300B-Q (90Hz+定格、サブクーユニット運転時)	19.49	18.99	18.89	18.69	18.60	21.43	20.82	20.67	20.40	20.26			
ECAV-EP335B-Q (90Hz+定格、サブクーユニット運転時)	21.13	20.59	20.48	20.27	20.17	22.94	22.28	22.12	21.84	21.69			

配管長別能力表	WAN19-327R
---------	------------