

## 配管長別冷凍能力

○インバータ：一体空冷

周囲温度：35℃

形式	冷媒	形名	蒸発温度 (℃)	配管相当長別能力(kW)										
				50Hz					60Hz					
				0m	30m	50m	80m	100m	0m	30m	50m	80m	100m	
スクロール 一体空冷 (インバータ)	R404A	ERAV-EP45HA(出力周波数60Hz)	+10	21.84	20.35	19.71	-	-	21.84	20.35	19.71	-	-	
		ERAV-EP45HA(出力周波数55Hz)		20.41	19.15	18.63	-	-	20.41	19.15	18.63	-	-	
		ERAV-EP45HA(出力周波数60Hz)	+5	19.00	17.69	17.13	-	-	19.00	17.69	17.13	-	-	
		ERAV-EP45HA(出力周波数55Hz)		17.76	16.65	16.18	-	-	17.76	16.65	16.18	-	-	
		ERAV-EP67HA(出力周波数50Hz)		27.23	25.97	25.49	24.76	24.35	27.23	25.97	25.49	24.76	24.35	
		ERAV-EP97HA(出力周波数70Hz)		37.63	36.21	35.72	34.96	34.53	37.63	36.21	35.72	34.96	34.53	
		ERAV-EP45HA(出力周波数60Hz)		0	16.42	15.27	14.77	-	-	16.42	15.27	14.77	-	-
		ERAV-EP67HA(出力周波数50Hz)			23.79	22.65	22.20	21.53	21.16	23.79	22.65	22.20	21.53	21.16
		ERAV-EP97HA(出力周波数70Hz)	32.97		31.67	31.22	30.52	30.12	32.97	31.67	31.22	30.52	30.12	
		ERAV-EP45HA(出力周波数60Hz)	-5	14.07	13.08	12.66	-	-	14.07	13.08	12.66	-	-	
		ERAV-EP67HA(出力周波数50Hz)		20.60	19.57	19.16	18.56	18.20	20.60	19.57	19.16	18.56	18.20	
		ERAV-EP97HA(出力周波数70Hz)		28.63	27.47	27.06	26.42	26.06	28.63	27.47	27.06	26.42	26.06	
		ERAV-EP45HA(出力周波数60Hz)	-10	11.97	11.14	10.78	-	-	11.97	11.14	10.78	-	-	
		ERAV-EP67HA(出力周波数50Hz)		17.66	16.75	16.39	15.85	15.55	17.66	16.75	16.39	15.85	15.55	
		ERAV-EP97HA(出力周波数70Hz)		24.63	23.60	23.23	22.66	22.33	24.63	23.60	23.23	22.66	22.33	
		ERAV-EP45HA(出力周波数60Hz)	-15	10.12	9.43	9.13	-	-	10.12	9.43	9.13	-	-	
		ERAV-EP67HA(出力周波数50Hz)		14.97	14.18	13.87	13.40	13.14	14.97	14.18	13.87	13.40	13.14	
		ERAV-EP97HA(出力周波数70Hz)		20.97	20.07	19.74	19.24	18.95	20.97	20.07	19.74	19.24	18.95	
		ERAV-EP45HA(出力周波数60Hz)	-20	8.51	7.95	7.72	-	-	8.51	7.95	7.72	-	-	
		ERAV-EP67HA(出力周波数50Hz)		12.53	11.86	11.59	11.19	10.97	12.53	11.86	11.59	11.19	10.97	
		ERAV-EP97HA(出力周波数70Hz)		17.64	16.87	16.58	16.15	15.90	17.64	16.87	16.58	16.15	15.90	
		ERAV-EP67HA(出力周波数50Hz)	-25	10.34	9.78	9.56	9.23	9.04	10.34	9.78	9.56	9.23	9.04	
		ERAV-EP97HA(出力周波数70Hz)		14.65	14.00	13.76	13.40	13.19	14.65	14.00	13.76	13.40	13.19	
		ERAV-EP67HA(出力周波数50Hz)	-30	8.41	7.95	7.77	7.50	7.35	8.41	7.95	7.77	7.50	7.35	
		ERAV-EP97HA(出力周波数70Hz)		11.99	11.47	11.27	10.97	10.81	11.99	11.47	11.27	10.97	10.81	
		ERAV-EP67HA(出力周波数50Hz)	-35	6.72	6.36	6.22	6.01	5.90	6.72	6.36	6.22	6.01	5.90	
		ERAV-EP97HA(出力周波数70Hz)		9.67	9.25	9.10	8.87	8.74	9.67	9.25	9.10	8.87	8.74	
		ERAV-EP67HA(出力周波数50Hz)	-40	5.28	5.01	4.90	4.75	4.66	5.28	5.01	4.90	4.75	4.66	
		ERAV-EP97HA(出力周波数70Hz)		7.68	7.35	7.24	7.06	6.96	7.68	7.35	7.24	7.06	6.96	
		ERAV-EP67HA(出力周波数50Hz)	-45	4.09	3.89	3.81	3.70	3.63	4.09	3.89	3.81	3.70	3.63	
ERAV-EP97HA(出力周波数70Hz)	6.03	5.78		5.69	5.55	5.48	6.03	5.78	5.69	5.55	5.48			

配管長別能力表	WAN19-327R	
---------	------------	--