

配管長別冷凍能力

○インバータ:リモート

凝縮温度:40℃

| 形式 | 冷媒 | 形名 | 蒸発温度 (℃) | 配管相当長別能力(kW) | | | | | | | | | |
|-----------------------------------------------------|-------|-----------------------------------------------------|-------------|--------------|--------|--------|-------|--------|--------|--------|--------|--------|--------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| スクロールリモート(インバータ) | R404A | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -5 | 39.41 | 36.63 | 35.43 | 33.78 | 32.85 | 39.41 | 36.63 | 35.43 | 33.78 | 32.85 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 49.32 | 46.77 | 45.75 | 44.27 | 43.43 | 55.90 | 52.35 | 50.85 | 48.76 | 47.58 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 62.72 | 59.81 | 58.70 | 57.03 | 56.09 | 67.70 | 64.11 | 62.66 | 60.55 | 59.36 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 69.95 | 66.29 | 64.82 | 62.68 | 61.47 | 80.09 | 74.87 | 72.65 | 69.55 | 67.82 |
| | | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | | 80.41 | 78.28 | 77.80 | 76.94 | 76.49 | 90.24 | 87.45 | 86.67 | 85.36 | 84.66 |
| | | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 91.37 | 88.95 | 88.40 | 87.43 | 86.92 | 102.67 | 99.49 | 98.60 | 97.11 | 96.32 |
| | | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 96.54 | 93.98 | 93.41 | 92.37 | 91.83 | 108.48 | 105.12 | 104.19 | 102.61 | 101.77 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 51.71 | 48.96 | 47.86 | 46.25 | 45.35 | 58.14 | 54.41 | 52.83 | 50.63 | 49.40 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 65.90 | 62.63 | 61.33 | 59.42 | 58.34 | 70.57 | 66.61 | 64.98 | 62.63 | 61.30 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 76.68 | 72.08 | 70.16 | 67.43 | 65.89 | 87.65 | 81.14 | 78.31 | 74.46 | 72.31 |
| | | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | | 89.23 | 86.57 | 85.86 | 84.65 | 84.00 | 96.82 | 93.62 | 92.67 | 91.09 | 90.22 |
| | | ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 100.56 | 97.57 | 96.77 | 95.40 | 94.67 | 108.82 | 105.23 | 104.16 | 102.39 | 101.41 |
| | | ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 105.83 | 102.68 | 101.84 | 100.40 | 99.62 | 114.98 | 111.19 | 110.06 | 108.18 | 107.16 | |
| | | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -10 | 33.48 | 31.08 | 30.04 | 28.62 | 27.82 | 33.48 | 31.08 | 30.04 | 28.62 | 27.82 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 41.65 | 39.47 | 38.60 | 37.33 | 36.61 | 47.05 | 44.04 | 42.77 | 41.00 | 40.01 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 53.42 | 50.89 | 49.91 | 48.45 | 47.63 | 57.40 | 54.31 | 53.06 | 51.25 | 50.22 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 59.25 | 56.10 | 54.83 | 52.98 | 51.94 | 67.66 | 63.19 | 61.29 | 58.64 | 57.16 |
| | | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | | 68.14 | 66.32 | 65.90 | 65.15 | 64.76 | 76.31 | 73.94 | 73.27 | 72.14 | 71.54 |
| | | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 77.71 | 75.64 | 75.16 | 74.30 | 73.86 | 86.86 | 84.17 | 83.40 | 82.12 | 81.43 |
| | | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 83.25 | 81.02 | 80.51 | 79.59 | 79.12 | 93.05 | 90.16 | 89.35 | 87.97 | 87.24 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 43.62 | 41.28 | 40.33 | 38.97 | 38.19 | 48.95 | 45.79 | 44.46 | 42.59 | 41.55 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 56.19 | 53.34 | 52.20 | 50.53 | 49.59 | 59.93 | 56.52 | 55.11 | 53.08 | 51.94 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 65.02 | 61.04 | 59.38 | 57.02 | 55.69 | 74.22 | 68.61 | 66.17 | 62.86 | 61.03 |
| | | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | | 75.88 | 73.59 | 72.97 | 71.90 | 71.33 | 82.45 | 79.68 | 78.84 | 77.46 | 76.70 |
| ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 85.58 | 82.99 | | 82.29 | 81.09 | 80.45 | 93.19 | 90.06 | 89.11 | 87.55 | 86.69 | | |
| ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 91.68 | 88.91 | 88.16 | 86.87 | 86.18 | 99.83 | 96.48 | 95.46 | 93.79 | 92.87 | | | |

| | | |
|--|-------------------|--|
| | WAN19-327R | |
|--|-------------------|--|

| 形式 | 冷媒 | 形名 | 蒸発温度 (°C) | 配管相当長別能力(kW) | | | | | | | | | |
|----|----|-------------------------------------------------------|--------------|--------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| | | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -12 | 31.27 | 29.02 | 28.04 | 26.70 | 25.95 | 31.27 | 29.02 | 28.04 | 26.70 | 25.95 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 38.80 | 36.76 | 35.94 | 34.76 | 34.09 | 43.77 | 40.97 | 39.79 | 38.14 | 37.22 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 49.94 | 47.55 | 46.63 | 45.25 | 44.48 | 53.56 | 50.67 | 49.49 | 47.80 | 46.84 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 55.27 | 52.32 | 51.12 | 49.39 | 48.42 | 63.04 | 58.86 | 57.08 | 54.61 | 53.23 |
| | | ECV-EP260A +RMW-P150A × 2 (90Hz+定格運転時) | | 63.57 | 61.86 | 61.47 | 60.77 | 60.40 | 71.13 | 68.91 | 68.28 | 67.24 | 66.67 |
| | | ECV-EP300A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 72.70 | 70.74 | 70.30 | 69.50 | 69.07 | 81.30 | 78.76 | 78.04 | 76.86 | 76.20 |
| | | ECV-EP335A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 78.00 | 75.90 | 75.42 | 74.56 | 74.11 | 87.30 | 84.57 | 83.80 | 82.52 | 81.82 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 40.62 | 38.43 | 37.55 | 36.27 | 35.55 | 45.55 | 42.61 | 41.36 | 39.63 | 38.66 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 52.56 | 49.87 | 48.79 | 47.22 | 46.33 | 55.96 | 52.76 | 51.43 | 49.53 | 48.46 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 60.67 | 56.94 | 55.38 | 53.16 | 51.92 | 69.22 | 63.96 | 61.67 | 58.57 | 56.86 |
| | | ECV-EP260B +RMW-P150A × 2 (90Hz+定格運転時) | | 70.89 | 68.74 | 68.15 | 67.15 | 66.61 | 77.07 | 74.47 | 73.67 | 72.37 | 71.65 |
| | | ECV-EP300B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 80.33 | 77.89 | 77.23 | 76.09 | 75.48 | 87.56 | 84.61 | 83.70 | 82.22 | 81.41 |
| | | ECV-EP335B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 86.39 | 83.76 | 83.04 | 81.83 | 81.17 | 94.15 | 90.98 | 90.00 | 88.41 | 87.54 |
| | | ERV-EP110A +RMW-P150A (出力周波数90Hz) | | -15 | 28.11 | 26.08 | 25.19 | 23.99 | 23.32 | 28.11 | 26.08 | 25.19 | 23.99 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | 34.76 | | 32.93 | 32.19 | 31.13 | 30.53 | 39.14 | 36.64 | 35.58 | 34.11 | 33.29 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | 44.96 | | 42.80 | 41.96 | 40.72 | 40.01 | 48.10 | 45.49 | 44.44 | 42.92 | 42.06 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | 49.62 | | 46.95 | 45.87 | 44.31 | 43.43 | 56.49 | 52.73 | 51.14 | 48.92 | 47.68 |
| | | ECV-EP260A +RMW-P150A × 2 (90Hz+定格運転時) | 57.06 | | 55.52 | 55.17 | 54.54 | 54.21 | 63.76 | 61.77 | 61.21 | 60.27 | 59.76 |
| | | ECV-EP300A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 65.39 | | 63.62 | 63.22 | 62.50 | 62.12 | 73.04 | 70.76 | 70.12 | 69.04 | 68.46 |
| | | ECV-EP335A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 70.70 | | 68.79 | 68.36 | 67.58 | 67.17 | 78.98 | 76.51 | 75.82 | 74.66 | 74.02 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | 36.36 | | 34.40 | 33.61 | 32.46 | 31.82 | 40.74 | 38.11 | 37.00 | 35.45 | 34.59 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | 47.36 | | 44.91 | 43.94 | 42.50 | 41.69 | 50.31 | 47.41 | 46.21 | 44.50 | 43.54 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | 54.50 | | 51.13 | 49.71 | 47.71 | 46.59 | 62.11 | 57.37 | 55.30 | 52.52 | 50.98 |
| | | ECV-EP260B +RMW-P150A × 2 (90Hz+定格運転時) | 63.78 | | 61.83 | 61.30 | 60.39 | 59.90 | 69.40 | 67.04 | 66.32 | 65.13 | 64.48 |
| | | ECV-EP300B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 72.79 | | 70.56 | 69.95 | 68.92 | 68.36 | 79.45 | 76.75 | 75.92 | 74.57 | 73.82 |
| | | ECV-EP335B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 78.71 | | 76.30 | 75.64 | 74.52 | 73.92 | 85.92 | 83.00 | 82.10 | 80.63 | 79.83 |

| |
|-------------------|
| WAN19-327R |
|-------------------|

| 形式 | 冷媒 | 形名 | 蒸発温度 (°C) | 配管相当長別能力(kW) | | | | | | | | | |
|-----------------------------------------------------|-----------------------------------------------------|-----------------------------------------------------|--------------|--------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| スクロールリモート(中・低温用) | R404A | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -17 | 26.12 | 24.22 | 23.41 | 22.29 | 21.66 | 26.12 | 24.22 | 23.41 | 22.29 | 21.66 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 32.22 | 30.52 | 29.84 | 28.86 | 28.30 | 36.23 | 33.92 | 32.95 | 31.60 | 30.84 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 41.82 | 39.80 | 39.02 | 37.85 | 37.20 | 44.66 | 42.24 | 41.26 | 39.85 | 39.06 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 46.07 | 43.58 | 42.58 | 41.13 | 40.31 | 52.38 | 48.89 | 47.41 | 45.36 | 44.21 |
| | | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | | 52.96 | 51.54 | 51.21 | 50.62 | 50.32 | 59.12 | 57.28 | 56.76 | 55.89 | 55.42 |
| | | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 60.90 | 59.27 | 58.89 | 58.21 | 57.86 | 68.00 | 65.88 | 65.29 | 64.28 | 63.74 |
| | | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 66.20 | 64.43 | 64.01 | 63.28 | 62.90 | 73.90 | 71.60 | 70.95 | 69.86 | 69.28 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 33.69 | 31.87 | 31.14 | 30.08 | 29.49 | 37.73 | 35.30 | 34.28 | 32.85 | 32.05 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 44.07 | 41.78 | 40.87 | 39.53 | 38.77 | 46.74 | 44.04 | 42.93 | 41.34 | 40.45 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 50.61 | 47.47 | 46.15 | 44.29 | 43.25 | 57.64 | 53.23 | 51.31 | 48.73 | 47.30 |
| | | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | | 59.29 | 57.47 | 56.97 | 56.13 | 55.67 | 64.55 | 62.35 | 61.67 | 60.57 | 59.96 |
| | | ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 67.85 | 65.77 | 65.20 | 64.23 | 63.71 | 74.15 | 71.62 | 70.84 | 69.57 | 68.88 |
| | ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 73.76 | 71.50 | 70.88 | 69.83 | 69.26 | 80.61 | 77.86 | 77.01 | 75.63 | 74.87 | | |
| | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -20 | 23.29 | 21.61 | 20.88 | 19.89 | 19.34 | 23.29 | 21.61 | 20.88 | 19.89 | 19.34 | |
| | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 28.65 | 27.14 | 26.54 | 25.67 | 25.18 | 32.16 | 30.12 | 29.27 | 28.08 | 27.42 | |
| | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 37.35 | 35.55 | 34.85 | 33.81 | 33.22 | 39.80 | 37.66 | 36.79 | 35.54 | 34.84 | |
| | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 41.05 | 38.83 | 37.94 | 36.65 | 35.92 | 46.58 | 43.49 | 42.18 | 40.36 | 39.35 | |
| | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | | 47.17 | 45.90 | 45.61 | 45.10 | 44.33 | 52.57 | 50.94 | 50.48 | 49.72 | 49.31 | |
| | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 54.20 | 52.74 | 52.41 | 51.82 | 50.94 | 60.40 | 58.52 | 58.00 | 57.12 | 56.65 | |
| | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 59.38 | 57.78 | 57.41 | 56.77 | 55.80 | 66.16 | 64.11 | 63.53 | 62.58 | 62.06 | |
| | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 29.93 | 28.32 | 27.67 | 26.74 | 26.22 | 33.50 | 31.36 | 30.46 | 29.20 | 28.51 | |
| | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 39.39 | 37.34 | 36.52 | 35.32 | 34.64 | 41.69 | 39.29 | 38.30 | 36.89 | 36.09 | |
| | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 45.13 | 42.32 | 41.14 | 39.48 | 38.56 | 51.34 | 47.41 | 45.70 | 43.40 | 42.14 | |
| | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | | 52.92 | 51.30 | 50.85 | 50.09 | 49.69 | 57.68 | 55.71 | 55.10 | 54.11 | 53.57 | |
| ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 60.82 | | 58.95 | 58.44 | 57.57 | 57.10 | 66.59 | 64.31 | 63.61 | 62.47 | 61.84 | | |
| ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 66.64 | 64.59 | 64.03 | 63.08 | 62.56 | 72.95 | 70.46 | 69.69 | 68.44 | 67.75 | | | |

WAN19-327R

| 形式 | 冷媒 | 形名 | 蒸発温度 (℃) | 配管相当長別能力(kW) | | | | | | | | | |
|----|----|-----------------------------------------------------|-------------|--------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| | | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -25 | 19.03 | 17.67 | 17.08 | 16.28 | 15.83 | 19.03 | 17.67 | 17.08 | 16.28 | 15.83 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 23.31 | 22.11 | 21.63 | 20.93 | 20.54 | 26.12 | 24.50 | 23.83 | 22.89 | 22.36 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 30.59 | 29.11 | 28.54 | 27.69 | 27.22 | 32.50 | 30.77 | 30.08 | 29.08 | 28.51 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 33.54 | 31.74 | 31.02 | 29.98 | 29.39 | 37.93 | 35.45 | 34.40 | 32.95 | 32.14 |
| | | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | | 38.46 | 37.43 | 37.21 | 36.79 | 36.58 | 42.74 | 41.44 | 41.08 | 40.48 | 40.16 |
| | | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 44.56 | 43.36 | 43.11 | 42.62 | 42.38 | 49.58 | 48.07 | 47.65 | 46.96 | 46.59 |
| | | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 49.44 | 48.12 | 47.84 | 47.30 | 47.03 | 55.01 | 53.34 | 52.88 | 52.11 | 51.69 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 24.32 | 23.03 | 22.52 | 21.78 | 21.36 | 27.23 | 25.53 | 24.82 | 23.83 | 23.27 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 32.30 | 30.62 | 29.95 | 28.97 | 28.42 | 34.08 | 32.14 | 31.34 | 30.21 | 29.57 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 36.90 | 34.61 | 33.66 | 32.32 | 31.57 | 41.89 | 38.71 | 37.34 | 35.49 | 34.47 |
| | | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | | 43.30 | 41.98 | 41.62 | 41.01 | 40.68 | 47.29 | 45.68 | 45.18 | 44.38 | 43.94 |
| | | ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 50.18 | 48.65 | 48.23 | 47.52 | 47.14 | 54.91 | 53.04 | 52.47 | 51.54 | 51.02 |
| | | ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | | 55.68 | 53.98 | 53.52 | 52.73 | 52.31 | 60.89 | 58.82 | 58.18 | 57.15 | 56.58 |
| | | ERV-EP110A +RMW-P150A (出力周波数90Hz) | | -30 | 15.33 | 14.26 | 13.80 | 13.18 | 12.83 | 15.33 | 14.26 | 13.80 | 13.18 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | 18.76 | | 17.82 | 17.45 | 16.91 | 16.61 | 21.01 | 19.76 | 19.24 | 18.52 | 18.12 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | 24.66 | | 23.50 | 23.05 | 22.39 | 22.02 | 26.20 | 24.85 | 24.32 | 23.54 | 23.11 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | 27.09 | | 25.66 | 25.10 | 24.28 | 23.82 | 30.54 | 28.60 | 27.79 | 26.66 | 26.03 |
| | | ECV-EP260A +RMW-P150A×2 (90Hz+定格運転時) | 30.98 | | 30.13 | 29.96 | 29.65 | 29.49 | 34.28 | 33.27 | 33.00 | 32.55 | 32.31 |
| | | ECV-EP300A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 36.37 | | 35.38 | 35.18 | 34.81 | 34.62 | 40.38 | 39.19 | 38.87 | 38.34 | 38.06 |
| | | ECV-EP335A-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 40.87 | | 39.75 | 39.52 | 39.11 | 38.90 | 45.37 | 44.04 | 43.68 | 43.08 | 42.77 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | 19.54 | | 18.53 | 18.14 | 17.57 | 17.25 | 21.93 | 20.61 | 20.07 | 19.30 | 18.88 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | 26.07 | | 24.74 | 24.21 | 23.44 | 23.00 | 27.48 | 25.95 | 25.34 | 24.45 | 23.96 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | 29.82 | | 28.00 | 27.25 | 26.19 | 25.60 | 33.78 | 31.27 | 30.19 | 28.74 | 27.94 |
| | | ECV-EP260B +RMW-P150A×2 (90Hz+定格運転時) | 34.91 | | 33.87 | 33.59 | 33.12 | 32.86 | 38.22 | 36.94 | 36.55 | 35.92 | 35.58 |
| | | ECV-EP300B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 40.93 | | 39.71 | 39.38 | 38.82 | 38.53 | 44.71 | 43.21 | 42.76 | 42.03 | 41.62 |
| | | ECV-EP335B-Q +RMW-P150A×2 (90Hz+定格、サブクールユニット運転時) | 45.99 | | 44.61 | 44.25 | 43.62 | 43.29 | 50.23 | 48.55 | 48.04 | 47.21 | 46.76 |

WAN19-327R

| 形式 | 冷媒 | 形名 | 蒸発温度 (°C) | 配管相当長別能力(kW) | | | | | | | | | |
|-------------------------------------------------------|-------------------------------------------------------|-------------------------------------------------------|--------------|--------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| スクロールリモート (中・低温用) | R404A | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -35 | 12.18 | 11.37 | 11.03 | 10.56 | 10.29 | 12.18 | 11.37 | 11.03 | 10.56 | 10.29 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 14.99 | 14.27 | 14.00 | 13.59 | 13.37 | 16.83 | 15.89 | 15.51 | 14.97 | 14.67 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 19.59 | 18.70 | 18.36 | 17.86 | 17.58 | 20.89 | 19.87 | 19.48 | 18.90 | 18.58 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 21.69 | 20.60 | 20.17 | 19.54 | 19.19 | 24.41 | 22.93 | 22.32 | 21.47 | 20.99 |
| | | ECV-EP260A +RMW-P150A × 2 (90Hz+定格運転時) | | 24.54 | 23.98 | 23.86 | 23.63 | 23.52 | 27.19 | 26.42 | 26.24 | 25.91 | 25.74 |
| | | ECV-EP300A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 29.50 | 28.83 | 28.68 | 28.41 | 28.27 | 32.69 | 31.76 | 31.55 | 31.15 | 30.94 |
| | | ECV-EP335A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 33.55 | 32.79 | 32.62 | 32.31 | 32.16 | 37.18 | 36.12 | 35.88 | 35.43 | 35.19 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 15.58 | 14.82 | 14.52 | 14.10 | 13.86 | 17.60 | 16.60 | 16.20 | 15.63 | 15.31 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 20.72 | 19.69 | 19.29 | 18.70 | 18.37 | 21.89 | 20.73 | 20.27 | 19.60 | 19.23 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 23.88 | 22.48 | 21.90 | 21.09 | 20.64 | 26.99 | 25.06 | 24.25 | 23.14 | 22.53 |
| | | ECV-EP260B +RMW-P150A × 2 (90Hz+定格運転時) | | 27.77 | 26.97 | 26.76 | 26.41 | 26.22 | 30.47 | 29.48 | 29.20 | 28.72 | 28.46 |
| | | ECV-EP300B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 32.52 | 31.58 | 31.34 | 30.93 | 30.71 | 35.89 | 34.73 | 34.39 | 33.83 | 33.53 |
| | ECV-EP335B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 36.99 | 35.92 | 35.65 | 35.18 | 34.93 | 40.82 | 39.50 | 39.11 | 38.47 | 38.13 | | |
| | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -40 | 9.58 | 8.99 | 8.74 | 8.40 | 8.21 | 9.58 | 8.99 | 8.74 | 8.40 | 8.21 | |
| | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 12.00 | 11.46 | 11.27 | 10.97 | 10.81 | 13.59 | 12.89 | 12.63 | 12.24 | 12.03 | |
| | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 15.36 | 14.70 | 14.46 | 14.09 | 13.89 | 16.59 | 15.84 | 15.56 | 15.15 | 14.92 | |
| | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 17.36 | 16.53 | 16.22 | 15.76 | 15.50 | 19.55 | 18.44 | 18.00 | 17.37 | 17.03 | |
| | ECV-EP260A +RMW-P150A × 2 (90Hz+定格運転時) | | 19.43 | 18.98 | 18.90 | 18.74 | 18.67 | 21.46 | 20.89 | 20.77 | 20.55 | 20.43 | |
| | ECV-EP300A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 23.96 | 23.40 | 23.30 | 23.10 | 23.02 | 26.39 | 25.69 | 25.54 | 25.27 | 25.12 | |
| | ECV-EP335A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 27.68 | 27.04 | 26.93 | 26.70 | 26.60 | 30.49 | 29.68 | 29.51 | 29.20 | 29.03 | |
| | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 12.44 | 11.88 | 11.67 | 11.36 | 11.19 | 14.24 | 13.50 | 13.21 | 12.80 | 12.57 | |
| | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 16.23 | 15.47 | 15.19 | 14.76 | 14.52 | 17.31 | 16.45 | 16.13 | 15.65 | 15.38 | |
| | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 19.08 | 18.02 | 17.60 | 17.00 | 16.66 | 21.53 | 20.09 | 19.49 | 18.67 | 18.22 | |
| | ECV-EP260B +RMW-P150A × 2 (90Hz+定格運転時) | | 21.87 | 21.27 | 21.13 | 20.88 | 20.75 | 24.05 | 23.31 | 23.11 | 22.77 | 22.59 | |
| ECV-EP300B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 25.77 | | 25.07 | 24.90 | 24.61 | 24.46 | 28.51 | 27.63 | 27.39 | 26.99 | 26.77 | | |
| ECV-EP335B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | 29.78 | 28.97 | 28.78 | 28.44 | 28.26 | 32.94 | 31.93 | 31.65 | 31.19 | 30.94 | | | |

| |
|------------|
| WAN19-327R |
|------------|

| 形式 | 冷媒 | 形名 | 蒸発温度 (°C) | 配管相当長別能力(kW) | | | | | | | | | |
|----------------------|-------|-------------------------------------------------------|--------------|--------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | | | 50Hz | | | | | 60Hz | | | | |
| | | | | 0m | 30m | 50m | 80m | 100m | 0m | 30m | 50m | 80m | 100m |
| スクロールリモート (中・低温用) | R404A | ERV-EP110A +RMW-P150A (出力周波数90Hz) | -45 | 7.54 | 7.11 | 6.94 | 6.69 | 6.56 | 7.54 | 7.11 | 6.94 | 6.69 | 6.56 |
| | | ECV-EP150A +RMW-P150A (60Hz+定格運転時) | | 9.79 | 9.49 | 9.31 | 9.07 | 8.92 | 11.29 | 10.79 | 10.61 | 10.36 | 10.23 |
| | | ECV-EP185A +RMW-P225A (90Hz+定格運転時) | | 11.97 | 11.49 | 11.32 | 11.06 | 10.92 | 13.29 | 12.74 | 12.54 | 12.25 | 12.09 |
| | | ECV-EP225A +RMW-P225A (60Hz+定格運転時) | | 14.09 | 13.48 | 13.26 | 12.93 | 12.75 | 15.94 | 15.13 | 14.83 | 14.40 | 14.17 |
| | | ECV-EP260A +RMW-P150A × 2 (90Hz+定格運転時) | | 15.46 | 15.12 | 15.07 | 14.97 | 14.93 | 17.09 | 16.67 | 16.60 | 16.45 | 16.38 |
| | | ECV-EP300A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 17.80 | 17.41 | 17.35 | 17.24 | 17.19 | 19.68 | 19.20 | 19.12 | 18.95 | 18.86 |
| | | ECV-EP335A-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 20.76 | 20.31 | 20.24 | 20.10 | 20.05 | 22.96 | 22.39 | 22.30 | 22.10 | 22.00 |
| | | ECV-EP150B +RMW-P150A (60Hz+定格運転時) | | 10.14 | 9.72 | 9.59 | 9.38 | 9.26 | 11.85 | 11.32 | 11.13 | 10.86 | 10.72 |
| | | ECV-EP185B +RMW-P225A (90Hz+定格運転時) | | 12.62 | 12.06 | 11.86 | 11.55 | 11.38 | 13.74 | 13.11 | 12.88 | 12.54 | 12.35 |
| | | ECV-EP225B +RMW-P225A (60Hz+定格運転時) | | 15.43 | 14.65 | 14.35 | 13.92 | 13.69 | 17.41 | 16.35 | 15.93 | 15.35 | 15.04 |
| | | ECV-EP260B +RMW-P150A × 2 (90Hz+定格運転時) | | 17.20 | 16.76 | 16.66 | 16.49 | 16.41 | 18.96 | 18.41 | 18.27 | 18.02 | 17.90 |
| | | ECV-EP300B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 20.65 | 20.12 | 20.01 | 19.80 | 19.70 | 22.90 | 22.23 | 22.06 | 21.77 | 21.62 |
| | | ECV-EP335B-Q +RMW-P150A × 2 (90Hz+定格、サブクールユニット運転時) | | 24.09 | 23.46 | 23.33 | 23.09 | 22.97 | 26.71 | 25.93 | 25.73 | 25.40 | 25.22 |

| | | |
|--|------------|--|
| | WAN19-327R | |
|--|------------|--|