

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

型名	吸入配管径 (mm)	蒸発温度 (°C)	配管相当長別能力(kW)					
			50Hz			60Hz		
			0m	30m	50m	0m	30m	50m
ECO V-EN37MA	φ 19.05	10	16.80	16.37	16.27	16.80	16.37	16.27
		5	16.32	15.84	15.69	16.32	15.84	15.69
		0	15.84	15.28	14.43	15.84	15.28	14.43
		-5	15.36	13.04	12.14	15.36	13.04	12.14
		-10	12.68	10.93	10.25	12.68	10.93	10.25
		-12	11.77	10.22	9.61	11.77	10.22	9.61
		-15	10.58	9.29	8.80	10.58	9.29	8.80
		-17	9.90	8.77	8.35	9.90	8.77	8.35
	-20	9.05	8.15	7.86	9.05	8.15	7.86	
	φ 22.2	10	16.80	16.52	16.52	16.80	16.52	16.52
		5	16.32	16.02	16.01	16.32	16.02	16.01
		0	15.84	15.52	15.47	15.84	15.52	15.47
		-5	15.36	14.13	13.61	15.36	14.13	13.61
		-10	12.68	11.76	11.37	12.68	11.76	11.37
		-12	11.77	10.95	10.61	11.77	10.95	10.61
		-15	10.58	9.89	9.62	10.58	9.89	9.62
		-17	9.90	9.29	9.06	9.90	9.29	9.06
	-20	9.05	8.56	8.38	9.05	8.56	8.38	
	φ 25.4	10	16.80	16.58	16.58	16.80	16.58	16.58
		5	16.32	16.09	16.09	16.32	16.09	16.09
		0	15.84	15.60	15.60	15.84	15.60	15.60
		-5	15.36	14.66	14.39	15.36	14.66	14.39
		-10	12.68	12.15	11.96	12.68	12.15	11.96
		-12	11.77	11.29	11.13	11.77	11.29	11.13
-15		10.58	10.18	10.05	10.58	10.18	10.05	
-17		9.90	9.54	9.43	9.90	9.54	9.43	
-20	9.05	8.75	8.67	9.05	8.75	8.67		
ECO V-EN45MA	φ 19.05	10	21.79	20.63	20.09	21.79	20.63	20.09
		5	20.74	19.43	18.78	20.74	19.43	18.78
		0	19.68	17.84	16.25	19.68	17.84	16.25
		-5	18.62	15.11	13.79	18.62	15.11	13.79
		-10	15.59	12.75	11.69	15.59	12.75	11.69
		-12	14.51	11.92	10.94	14.51	11.92	10.94
		-15	13.04	10.79	9.93	13.04	10.79	9.93
		-17	12.16	10.11	9.34	12.16	10.11	9.34
	-20	10.98	9.21	8.56	10.98	9.21	8.56	
	φ 22.2	10	21.79	21.17	21.00	21.79	21.17	21.00
		5	20.74	20.06	19.84	20.74	20.06	19.84
		0	19.68	18.93	18.65	19.68	18.93	18.65
		-5	18.62	16.73	15.93	18.62	16.73	15.93
		-10	15.59	14.07	13.42	15.59	14.07	13.42
		-12	14.51	13.13	12.53	14.51	13.13	12.53
		-15	13.04	11.84	11.32	13.04	11.84	11.32
		-17	12.16	11.06	10.60	12.16	11.06	10.60
	-20	10.98	10.03	9.64	10.98	10.03	9.64	
	φ 25.4	10	21.79	21.38	21.35	21.79	21.38	21.35
		5	20.74	20.30	20.25	20.74	20.30	20.25
		0	19.68	19.22	19.13	19.68	19.22	19.13
		-5	18.62	17.55	17.11	18.62	17.55	17.11
		-10	15.59	14.73	14.38	15.59	14.73	14.38
		-12	14.51	13.72	13.41	14.51	13.72	13.41
-15		13.04	12.36	12.09	13.04	12.36	12.09	
-17		12.16	11.53	11.29	12.16	11.53	11.29	
-20	10.98	10.44	10.23	10.98	10.44	10.23		

配管長別冷凍能力表

WAN20-547-A