

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

| 型名 | 吸入 配管径 (mm) | 蒸発温度 (°C) | 配管相当長別能力 (kW) | | | | | |
|------------------|-------------------|--------------|---------------|-------|-------|-------|-------|-------|
| | | | 50Hz | | | 60Hz | | |
| | | | 0m | 30m | 50m | 0m | 30m | 50m |
| ECOV-EN37MB(-SC) | φ19.05 | 10 | 16.80 | 16.37 | 16.27 | 16.80 | 16.37 | 16.27 |
| | | 5 | 16.32 | 15.84 | 15.69 | 16.32 | 15.84 | 15.69 |
| | | 0 | 15.84 | 15.28 | 14.43 | 15.84 | 15.28 | 14.43 |
| | | -5 | 15.36 | 13.04 | 12.14 | 15.36 | 13.04 | 12.14 |
| | | -10 | 12.68 | 10.93 | 10.25 | 12.68 | 10.93 | 10.25 |
| | | -12 | 11.77 | 10.22 | 9.61 | 11.77 | 10.22 | 9.61 |
| | | -15 | 10.58 | 9.29 | 8.80 | 10.58 | 9.29 | 8.80 |
| | | -17 | 9.90 | 8.77 | 8.35 | 9.90 | 8.77 | 8.35 |
| | -20 | 9.05 | 8.15 | 7.86 | 9.05 | 8.15 | 7.86 | |
| | φ22.2 | 10 | 16.80 | 16.52 | 16.52 | 16.80 | 16.52 | 16.52 |
| | | 5 | 16.32 | 16.02 | 16.01 | 16.32 | 16.02 | 16.01 |
| | | 0 | 15.84 | 15.52 | 15.47 | 15.84 | 15.52 | 15.47 |
| | | -5 | 15.36 | 14.13 | 13.61 | 15.36 | 14.13 | 13.61 |
| | | -10 | 12.68 | 11.76 | 11.37 | 12.68 | 11.76 | 11.37 |
| | | -12 | 11.77 | 10.95 | 10.61 | 11.77 | 10.95 | 10.61 |
| | | -15 | 10.58 | 9.89 | 9.62 | 10.58 | 9.89 | 9.62 |
| | | -17 | 9.90 | 9.29 | 9.06 | 9.90 | 9.29 | 9.06 |
| | -20 | 9.05 | 8.56 | 8.38 | 9.05 | 8.56 | 8.38 | |
| | φ25.4 | 10 | 16.80 | 16.58 | 16.58 | 16.80 | 16.58 | 16.58 |
| | | 5 | 16.32 | 16.09 | 16.09 | 16.32 | 16.09 | 16.09 |
| | | 0 | 15.84 | 15.60 | 15.60 | 15.84 | 15.60 | 15.60 |
| | | -5 | 15.36 | 14.66 | 14.39 | 15.36 | 14.66 | 14.39 |
| | | -10 | 12.68 | 12.15 | 11.96 | 12.68 | 12.15 | 11.96 |
| | | -12 | 11.77 | 11.29 | 11.13 | 11.77 | 11.29 | 11.13 |
| -15 | | 10.58 | 10.18 | 10.05 | 10.58 | 10.18 | 10.05 | |
| -17 | | 9.90 | 9.54 | 9.43 | 9.90 | 9.54 | 9.43 | |
| -20 | 9.05 | 8.75 | 8.67 | 9.05 | 8.75 | 8.67 | | |
| ECOV-EN45MB(-SC) | φ19.05 | 10 | 21.79 | 20.63 | 20.09 | 21.79 | 20.63 | 20.09 |
| | | 5 | 20.74 | 19.43 | 18.78 | 20.74 | 19.43 | 18.78 |
| | | 0 | 19.68 | 17.84 | 16.25 | 19.68 | 17.84 | 16.25 |
| | | -5 | 18.62 | 15.11 | 13.79 | 18.62 | 15.11 | 13.79 |
| | | -10 | 15.59 | 12.75 | 11.69 | 15.59 | 12.75 | 11.69 |
| | | -12 | 14.51 | 11.92 | 10.94 | 14.51 | 11.92 | 10.94 |
| | | -15 | 13.04 | 10.79 | 9.93 | 13.04 | 10.79 | 9.93 |
| | | -17 | 12.16 | 10.11 | 9.34 | 12.16 | 10.11 | 9.34 |
| | -20 | 10.98 | 9.21 | 8.56 | 10.98 | 9.21 | 8.56 | |
| | φ22.2 | 10 | 21.79 | 21.17 | 21.00 | 21.79 | 21.17 | 21.00 |
| | | 5 | 20.74 | 20.06 | 19.84 | 20.74 | 20.06 | 19.84 |
| | | 0 | 19.68 | 18.93 | 18.65 | 19.68 | 18.93 | 18.65 |
| | | -5 | 18.62 | 16.73 | 15.93 | 18.62 | 16.73 | 15.93 |
| | | -10 | 15.59 | 14.07 | 13.42 | 15.59 | 14.07 | 13.42 |
| | | -12 | 14.51 | 13.13 | 12.53 | 14.51 | 13.13 | 12.53 |
| | | -15 | 13.04 | 11.84 | 11.32 | 13.04 | 11.84 | 11.32 |
| | | -17 | 12.16 | 11.06 | 10.60 | 12.16 | 11.06 | 10.60 |
| | -20 | 10.98 | 10.03 | 9.64 | 10.98 | 10.03 | 9.64 | |
| | φ25.4 | 10 | 21.79 | 21.38 | 21.35 | 21.79 | 21.38 | 21.35 |
| | | 5 | 20.74 | 20.30 | 20.25 | 20.74 | 20.30 | 20.25 |
| | | 0 | 19.68 | 19.22 | 19.13 | 19.68 | 19.22 | 19.13 |
| | | -5 | 18.62 | 17.55 | 17.11 | 18.62 | 17.55 | 17.11 |
| | | -10 | 15.59 | 14.73 | 14.38 | 15.59 | 14.73 | 14.38 |
| | | -12 | 14.51 | 13.72 | 13.41 | 14.51 | 13.72 | 13.41 |
| -15 | | 13.04 | 12.36 | 12.09 | 13.04 | 12.36 | 12.09 | |
| -17 | | 12.16 | 11.53 | 11.29 | 12.16 | 11.53 | 11.29 | |
| -20 | 10.98 | 10.44 | 10.23 | 10.98 | 10.44 | 10.23 | | |

配管長別冷凍能力表

WAN20-652