

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

型名	吸入 配管径 (mm)	蒸発温度 (°C)	配管相当長別能力 (kW)							
			50Hz				60Hz			
			0m	30m	50m	80m	0m	30m	50m	80m
ECO-V-EN67MB (-SC)	φ19.05	10	25.44	23.00	21.35	—	25.44	23.00	21.35	—
		5	25.44	23.00	21.35		25.44	23.00	21.35	
		0	24.00	20.68	18.58		24.00	20.68	18.58	
		-5	22.66	17.90	15.82		22.66	17.90	15.82	
		-10	20.07	15.07	13.16		20.07	15.07	13.16	
		-12	18.95	13.95	12.14		18.95	13.95	12.14	
		-15	17.17	12.30	10.65		17.17	12.30	10.65	
		-17	15.92	11.21	9.70		15.92	11.21	9.70	
	-20	13.95	9.62	8.31	13.95	9.62	8.31			
	φ22.2	10	25.44	24.22	23.71	22.92	25.44	24.22	23.71	22.92
		5	25.44	24.22	23.71	22.92	25.44	24.22	23.71	22.92
		0	24.00	22.71	21.87	20.36	24.00	22.71	21.87	20.36
		-5	22.66	20.31	19.13	17.55	22.66	20.31	19.13	17.55
		-10	20.07	17.50	16.26	14.72	20.07	17.50	16.26	14.72
		-12	18.95	16.32	15.10	13.62	18.95	16.32	15.10	13.62
		-15	17.17	14.53	13.36	11.98	17.17	14.53	13.36	11.98
		-17	15.92	13.33	12.21	10.92	15.92	13.33	12.21	10.92
	-20	13.95	11.50	10.49	9.37	13.95	11.50	10.49	9.37	
	φ25.4	10	25.44	24.71	24.52	24.18	25.44	24.71	24.52	24.18
		5	25.44	24.71	24.52	24.18	25.44	24.71	24.52	24.18
		0	24.00	23.25	23.03	22.64	24.00	23.25	23.03	22.64
		-5	22.66	21.39	20.82	19.95	22.66	21.39	20.82	19.95
		-10	20.07	18.67	18.02	17.08	20.07	18.67	18.02	17.08
		-12	18.95	17.52	16.84	15.90	18.95	17.52	16.84	15.90
		-15	17.17	15.71	15.04	14.11	17.17	15.71	15.04	14.11
		-17	15.92	14.48	13.81	12.92	15.92	14.48	13.81	12.92
	-20	13.95	12.57	11.94	11.13	13.95	12.57	11.94	11.13	