

## 配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

型名	吸入 配管径 (mm)	蒸発温度 (°C)	配管相当長別能力(kW)							
			50Hz				60Hz			
			0m	30m	50m	80m	0m	30m	50m	80m
ECOV-EN55A(-SC)	φ 19.05	-15	17.1	12.5	11.0	—	17.1	12.5	11.0	—
		-17	15.8	11.6	10.2		15.8	11.6	10.2	
		-20	13.9	10.3	9.15		13.9	10.3	9.15	
		-25	11.2	8.48	7.60		11.2	8.48	7.60	
		-30	9.08	7.05	6.40		9.08	7.05	6.40	
		-35	7.49	6.03	5.57		7.49	6.03	5.57	
		-40	6.41	5.40	5.00		6.41	5.40	5.00	
		-45	5.77	4.89	4.49		5.77	4.89	4.49	
	φ 22.2	-15	17.1	14.5	13.5	—	17.1	14.5	13.5	—
		-17	15.8	13.4	12.5		15.8	13.4	12.5	
		-20	13.9	11.9	11.1		13.9	11.9	11.1	
		-25	11.2	9.69	9.06		11.2	9.69	9.06	
		-30	9.08	7.95	7.49		9.08	7.95	7.49	
		-35	7.49	6.67	6.35		7.49	6.67	6.35	
		-40	6.41	5.83	5.62		6.41	5.83	5.62	
	φ 25.4	-15	17.1	15.6	15.0	14.1	17.1	15.6	15.0	14.1
		-17	15.8	14.4	13.8	13.1	15.8	14.4	13.8	13.1
		-20	13.9	12.7	12.2	11.6	13.9	12.7	12.2	11.6
		-25	11.2	10.3	10.0	9.47	11.2	10.3	9.96	9.47
		-30	9.08	8.43	8.16	7.79	9.08	8.43	8.16	7.79
		-35	7.49	7.02	6.83	6.57	7.49	7.02	6.83	6.57
		-40	6.41	6.07	5.94	5.78	6.41	6.07	5.94	5.78
		-45	5.77	5.52	5.44	5.33	5.77	5.52	5.44	5.33

配管長別冷凍能力表

WAN20-724