

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

型名	吸入配管径 (mm)	蒸発温度 (°C)	配管相当長別能力(kW)									
			50Hz					60Hz				
			0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
ECO V-EN75MB	φ 25.4	10	26.58	24.93	24.06	22.68	21.84	26.58	24.93	24.06	22.68	21.84
		5	26.58	24.93	24.06	22.68	21.84	26.58	24.93	24.06	22.68	21.84
		0	26.58	24.93	24.06	22.68	21.84	26.58	24.93	24.06	22.68	21.84
		-5	26.58	24.93	24.06	22.68	21.84	26.58	24.93	24.06	22.68	21.84
		-10	24.02	21.85	20.74	19.20	18.34	24.02	21.85	20.74	19.20	18.34
		-12	22.76	20.45	19.29	17.76	16.92	22.76	20.45	19.29	17.76	16.92
		-15	20.61	18.16	17.00	15.54	14.77	20.61	18.16	17.00	15.54	14.77
		-17	19.00	16.56	15.45	14.08	13.37	19.00	16.56	15.45	14.08	13.37
	-20	16.33	14.03	13.03	11.84	11.23	16.33	14.03	13.03	11.84	11.23	
	φ 28.58	10	26.58	25.61	25.22	24.55	24.13	26.58	25.61	25.22	24.55	24.13
		5	26.58	25.61	25.22	24.55	24.13	26.58	25.61	25.22	24.55	24.13
		0	26.58	25.61	25.22	24.55	24.13	26.58	25.61	25.22	24.55	24.13
		-5	26.58	25.61	25.22	24.55	24.13	26.58	25.61	25.22	24.55	24.13
		-10	24.02	22.76	22.18	21.30	20.76	24.02	22.76	22.18	21.30	20.76
		-12	22.76	21.40	20.78	19.85	19.30	22.76	21.40	20.78	19.85	19.30
		-15	20.61	19.16	18.49	17.54	16.99	20.61	19.16	18.49	17.54	16.99
		-17	19.00	17.55	16.88	15.96	15.43	19.00	17.55	16.88	15.96	15.43
	-20	16.33	14.94	14.31	13.47	13.01	16.33	14.94	14.31	13.47	13.01	
	φ 31.75	10	26.58	25.90	25.74	25.42	25.22	26.58	25.90	25.74	25.42	25.22
		5	26.58	25.90	25.74	25.42	25.22	26.58	25.90	25.74	25.42	25.22
		0	26.58	25.90	25.74	25.42	25.22	26.58	25.90	25.74	25.42	25.22
		-5	26.58	25.90	25.74	25.42	25.22	26.58	25.90	25.74	25.42	25.22
		-10	24.02	23.18	22.88	22.38	22.09	24.02	23.18	22.88	22.38	22.09
		-12	22.76	21.86	21.53	20.98	20.66	22.76	21.86	21.53	20.98	20.66
-15		20.61	19.65	19.27	18.68	18.34	20.61	19.65	19.27	18.68	18.34	
-17		19.00	18.04	17.65	17.06	16.72	19.00	18.04	17.65	17.06	16.72	
-20	16.33	15.42	15.03	14.48	14.16	16.33	15.42	15.03	14.48	14.16		
ECO V-EN98MB	φ 28.58	10	29.86	28.49	27.87	26.87	26.24	29.86	28.49	27.87	26.87	26.24
		5	29.86	28.49	27.87	26.87	26.24	29.86	28.49	27.87	26.87	26.24
		0	29.86	28.49	27.87	26.87	26.24	29.86	28.49	27.87	26.87	26.24
		-5	29.86	28.49	27.87	26.87	26.24	29.86	28.49	27.87	26.87	26.24
		-10	26.88	25.17	24.36	23.15	22.43	26.88	25.17	24.36	23.15	22.43
		-12	25.46	23.66	22.80	21.56	20.84	25.46	23.66	22.80	21.56	20.84
		-15	23.10	21.20	20.30	19.06	18.37	23.10	21.20	20.30	19.06	18.37
		-17	21.36	19.46	18.58	17.39	16.73	21.36	19.46	18.58	17.39	16.73
	-20	18.52	16.70	15.87	14.80	14.21	18.52	16.70	15.87	14.80	14.21	
	φ 31.75	10	29.86	28.93	28.64	28.11	27.79	29.86	28.93	28.64	28.11	27.79
		5	29.86	28.93	28.64	28.11	27.79	29.86	28.93	28.64	28.11	27.79
		0	29.86	28.93	28.64	28.11	27.79	29.86	28.93	28.64	28.11	27.79
		-5	29.86	28.93	28.64	28.11	27.79	29.86	28.93	28.64	28.11	27.79
		-10	26.88	25.75	25.31	24.60	24.17	26.88	25.75	25.31	24.60	24.17
		-12	25.46	24.28	23.80	23.04	22.59	25.46	24.28	23.80	23.04	22.59
		-15	23.10	21.86	21.33	20.53	20.07	23.10	21.86	21.33	20.53	20.07
		-17	21.36	20.12	19.59	18.80	18.35	21.36	20.12	19.59	18.80	18.35
	-20	18.52	17.33	16.81	16.07	15.65	18.52	17.33	16.81	16.07	15.65	
	φ 34.92	10	29.86	29.18	29.07	28.82	28.68	29.86	29.18	29.07	28.82	28.68
		5	29.86	29.18	29.07	28.82	28.68	29.86	29.18	29.07	28.82	28.68
		0	29.86	29.18	29.07	28.82	28.68	29.86	29.18	29.07	28.82	28.68
		-5	29.86	29.18	29.07	28.82	28.68	29.86	29.18	29.07	28.82	28.68
		-10	26.88	26.09	25.87	25.49	25.26	26.88	26.09	25.87	25.49	25.26
		-12	25.46	24.64	24.39	23.96	23.72	25.46	24.64	24.39	23.96	23.72
-15		23.10	22.25	21.96	21.49	21.21	23.10	22.25	21.96	21.49	21.21	
-17		21.36	20.52	20.22	19.74	19.46	21.36	20.52	20.22	19.74	19.46	
-20	18.52	17.72	17.41	16.94	16.68	18.52	17.72	17.41	16.94	16.68		

配管長別冷凍能力表	WAN20-750	
-----------	-----------	--