

外気温度別能力表

項目	形名	液管断熱	周囲温度 [°C]	蒸発温度 [°C]											
				-45	-40	-35	-30	-25	-20	-15	-10	-5	0	5	10
能力 [kW]	ECOV-EN15WB	液管断熱有り	32	1.63	2.00	2.51	3.03	3.73	4.43	5.37	6.30	7.37	8.15	9.03	9.70
			43	1.58	1.99	2.44	3.02	3.63	4.29	5.02	5.80	6.66	7.33	8.00	8.68
			46	1.54	1.97	2.43	2.98	3.56	4.20	4.90	5.64	6.60	7.27	7.93	8.60
		液管断熱無し	32	1.26	1.56	2.05	2.55	3.28	4.01	4.99	5.97	7.10	7.99	8.89	9.51
			43	1.12	1.45	1.86	2.36	2.93	3.58	4.32	5.23	6.41	7.19	7.94	8.51
			46	1.07	1.40	1.80	2.27	2.82	3.43	4.12	4.98	6.35	7.13	7.90	8.43
	ECOV-EN22WB	液管断熱有り	32	2.05	2.60	3.34	4.08	5.08	6.08	7.29	8.50	9.77	10.4	11.0	11.8
			43	1.97	2.57	3.25	4.03	4.90	5.85	6.90	8.04	8.98	9.72	10.5	11.2
			46	1.95	2.53	3.20	3.97	4.83	5.78	6.82	7.95	8.90	9.63	10.4	11.1
		液管断熱無し	32	1.61	2.04	2.71	3.39	4.39	5.39	6.64	7.90	9.23	9.91	10.7	11.5
			43	1.43	1.88	2.44	3.12	3.91	4.82	5.84	6.97	8.49	9.24	10.1	10.9
			46	1.38	1.81	2.36	3.01	3.78	4.65	5.64	6.73	8.41	9.16	10.0	10.8
	ECOV-EN30WB	液管断熱有り	32	3.10	3.80	4.72	5.63	6.86	8.08	9.64	11.2	13.0	14.4	15.4	16.2
			43	2.97	3.61	4.41	5.36	6.46	7.72	9.13	10.7	11.4	12.3	13.1	14.0
			46	2.92	3.53	4.30	5.24	6.34	7.60	9.02	10.6	11.3	12.0	12.8	13.5
		液管断熱無し	32	2.49	3.10	3.96	4.82	6.01	7.21	8.73	10.3	12.0	13.4	14.4	15.2
			43	2.22	2.76	3.45	4.29	5.28	6.42	7.71	9.16	10.5	11.6	12.4	13.1
			46	2.13	2.64	3.30	4.11	5.07	6.17	7.42	8.83	10.4	11.4	12.1	12.6
	ECOV-EN37WB	液管断熱有り	32	3.51	4.35	5.40	6.44	7.80	9.15	10.8	12.5	14.5	15.8	16.9	17.6
			43	3.34	4.09	5.00	6.07	7.30	8.69	10.2	11.9	12.7	13.6	14.5	15.4
			46	3.25	4.00	4.89	5.94	7.13	8.47	10.0	11.6	11.9	12.4	13.0	13.5
		液管断熱無し	32	2.85	3.59	4.59	5.58	6.92	8.27	9.94	11.6	13.6	14.8	15.8	16.5
			43	2.53	3.16	3.96	4.92	6.04	7.33	8.78	10.4	11.9	12.9	13.9	14.4
			46	2.41	3.04	3.81	4.73	5.79	6.99	8.34	9.84	11.2	11.8	12.4	12.6
	ECOV-EN45WB	液管断熱有り	32	4.21	4.99	6.17	7.36	8.97	10.6	12.8	15.0	17.5	19.1	19.9	20.5
			43	4.07	4.86	5.87	7.11	8.57	10.3	12.2	14.3	16.1	17.4	17.9	18.3
			46	4.01	4.77	5.76	6.98	8.43	10.1	12.0	14.2	16.0	16.3	15.8	15.2
		液管断熱無し	32	3.41	4.04	5.15	6.27	7.93	9.59	11.9	14.2	16.9	18.6	19.4	20.1
			43	3.07	3.71	4.59	5.71	7.07	8.67	10.5	12.6	15.5	16.9	17.5	18.0
			46	2.96	3.57	4.42	5.50	6.82	8.36	10.1	12.2	15.1	15.8	15.4	15.0
	ECOV-EN55WB	液管断熱有り	32	5.69	6.80	8.20	9.60	11.4	13.2	15.6	18.0	21.1	22.5	22.5	22.5
			43	5.32	6.35	7.57	8.98	10.6	12.4	14.3	16.5	17.1	17.9	18.4	18.5
			46	5.15	6.21	7.43	8.80	10.3	12.0	13.8	15.7	16.2	16.2	15.9	15.2
		液管断熱無し	32	4.76	5.63	6.96	8.29	10.2	12.0	14.5	16.9	20.0	21.7	22.1	22.1
			43	4.14	5.01	6.08	7.35	8.83	10.5	12.4	14.5	16.1	17.7	18.1	18.2
			46	3.93	4.82	5.88	7.09	8.45	10.0	11.6	13.5	15.3	15.9	15.6	14.9
	ECOV-EN67WB	液管断熱有り	32	6.10	7.35	8.95	10.6	12.6	14.7	17.3	20.0	23.5	25.2	25.3	25.3
			43	5.50	6.98	8.50	10.0	11.6	13.2	14.9	16.5	17.4	18.1	18.6	18.5
			46	5.31	6.81	8.30	9.80	11.3	12.8	14.3	15.8	16.2	16.2	15.9	15.2
		液管断熱無し	32	5.06	6.17	7.69	9.21	11.3	13.3	16.1	18.8	22.2	23.6	24.8	24.8
			43	4.28	5.56	6.91	8.32	9.78	11.3	12.9	14.5	16.4	17.4	18.2	18.1
			46	4.05	5.34	6.66	7.99	9.34	10.7	12.1	13.5	15.3	15.5	15.6	14.9

注1. 各条件の能力は最大値を示しています。
 注2. 能力は吸入温度18°C条件です。
 注3. 能力を換算する係数は不要です。