

配管長別冷凍能力表

○定速：一体空冷

周囲温度：35℃

形名	吸入 配管径 (mm)	蒸発温度 (°C)	配管相当長別能力(kW)					
			50Hz			60Hz		
			0m	30m	50m	0m	30m	50m
ERA-EN22A	φ 15.88	-5	8.01	7.15	6.77	9.62	8.25	7.67
		-10	6.76	6.02	5.70	8.12	6.94	6.45
		-12	6.29	5.60	5.30	7.56	6.46	6.01
		-15	5.63	5.01	4.74	6.77	5.78	5.37
		-17	5.22	4.65	4.40	6.27	5.36	4.98
		-20	4.64	4.13	3.91	5.57	4.76	4.43
		-25	3.77	3.36	3.19	4.52	3.87	3.61
		-30	3.03	2.71	2.58	3.62	3.12	2.91
		-35	2.42	2.18	2.08	2.87	2.50	2.34
	-40	1.94	1.76	1.69	2.28	2.00	1.89	
	-45	1.58	1.46	1.41	1.83	1.64	1.56	
	φ 19.05	-5	8.01	7.62	7.47	9.62	9.00	8.74
		-10	6.76	6.42	6.29	8.12	7.59	7.36
		-12	6.29	5.98	5.86	7.56	7.07	6.85
		-15	5.63	5.35	5.24	6.77	6.32	6.13
		-17	5.22	4.96	4.86	6.27	5.86	5.68
		-20	4.64	4.41	4.32	5.57	5.20	5.05
		-25	3.77	3.58	3.51	4.52	4.23	4.10
		-30	3.03	2.89	2.83	3.62	3.39	3.30
		-35	2.42	2.31	2.27	2.87	2.70	2.63
	-40	1.94	1.85	1.83	2.28	2.15	2.10	
	-45	1.58	1.52	1.50	1.83	1.74	1.71	
	φ 22.2	-5	8.01	7.78	7.72	9.62	9.27	9.16
		-10	6.76	6.56	6.51	8.12	7.82	7.72
		-12	6.29	6.11	6.06	7.56	7.28	7.19
		-15	5.63	5.47	5.43	6.77	6.52	6.43
		-17	5.22	5.07	5.03	6.27	6.04	5.96
-20		4.64	4.50	4.47	5.57	5.36	5.29	
-25		3.77	3.66	3.63	4.52	4.35	4.30	
-30		3.03	2.94	2.92	3.62	3.49	3.45	
-35		2.42	2.35	2.34	2.87	2.78	2.75	
-40	1.94	1.89	1.88	2.28	2.20	2.18		
-45	1.58	1.54	1.54	1.83	1.78	1.77		