

配管長別冷凍能力表

○定速：一体空冷

周囲温度：35℃

形名	吸入 配管径 (mm)	蒸発温度 (°C)	配管相当長別能力(kW)					
			50Hz			60Hz		
			0m	30m	50m	0m	30m	50m
ERA-EN30A	φ 15.88	-5	10.16	8.58	7.93	12.09	9.68	8.76
		-10	8.56	7.21	6.66	10.19	8.14	7.37
		-12	7.96	6.71	6.20	9.49	7.57	6.85
		-15	7.12	6.00	5.54	8.49	6.77	6.13
		-17	6.59	5.55	5.13	7.86	6.27	5.68
		-20	5.85	4.93	4.56	6.98	5.58	5.05
		-25	4.74	4.01	3.72	5.66	4.54	4.12
		-30	3.79	3.23	3.00	4.53	3.66	3.34
		-35	3.01	2.59	2.42	3.59	2.94	2.69
	-40	2.39	2.08	1.96	2.84	2.37	2.19	
	-45	1.94	1.72	1.64	2.29	1.96	1.84	
	φ 19.05	-5	10.16	9.44	9.14	12.09	10.97	10.49
		-10	8.56	7.95	7.69	10.19	9.24	8.82
		-12	7.96	7.40	7.15	9.49	8.60	8.21
		-15	7.12	6.61	6.39	8.49	7.69	7.34
		-17	6.59	6.12	5.92	7.86	7.12	6.80
		-20	5.85	5.43	5.25	6.98	6.33	6.04
		-25	4.74	4.41	4.27	5.66	5.14	4.91
		-30	3.79	3.54	3.43	4.53	4.12	3.95
		-35	3.01	2.82	2.74	3.59	3.29	3.16
	-40	2.39	2.25	2.19	2.84	2.62	2.53	
	-45	1.94	1.84	1.80	2.29	2.13	2.07	
	φ 22.2	-5	10.16	9.76	9.62	12.09	11.48	11.23
		-10	8.56	8.22	8.10	10.19	9.67	9.46
		-12	7.96	7.65	7.53	9.49	9.00	8.81
		-15	7.12	6.84	6.74	8.49	8.05	7.88
		-17	6.59	6.33	6.24	7.86	7.46	7.29
-20		5.85	5.61	5.53	6.98	6.62	6.48	
-25		4.74	4.55	4.49	5.66	5.37	5.26	
-30		3.79	3.65	3.60	4.53	4.30	4.22	
-35		3.01	2.90	2.87	3.59	3.42	3.36	
-40	2.39	2.31	2.29	2.84	2.72	2.68		
-45	1.94	1.88	1.86	2.29	2.20	2.17		