

配管長別冷凍能力表

インバータ：一体空冷

周囲温度：35

型名	吸入配管径 (mm)	蒸発温度 (°C)	配管相当長別能力 (kW)							
			50Hz				60Hz			
			0m	30m	50m	80m	0m	30m	50m	80m
ECO V-EN30WA1	19.05	10	16.4	15.5	15.2		16.4	15.5	15.2	
		5	15.0	14.2	13.9		15.0	14.2	13.9	
		0	13.8	13.1	12.7		13.8	13.1	12.7	
		-5	12.7	11.4	10.9		12.7	11.4	10.9	
		-10	10.8	9.70	9.24		10.8	9.70	9.24	
		-12	10.1	9.07	8.64		10.1	9.07	8.64	
		-15	9.08	8.18	7.79		9.08	8.18	7.79	
		-17	8.46	7.63	7.26		8.46	7.63	7.26	
		-20	7.60	6.85	6.52		7.60	6.85	6.52	
		-25	6.33	5.70	5.42		6.33	5.70	5.42	
		-30	5.23	4.70	4.46		5.23	4.70	4.46	
		-35	4.28	3.84	3.64		4.28	3.84	3.64	
	-40	3.46	3.09	2.93		3.46	3.09	2.93		
	-45	2.75	2.44	2.31		2.75	2.44	2.31		
	22.2	10	16.4	15.9	15.8		16.4	15.9	15.8	
		5	15.0	14.6	14.5		15.0	14.6	14.5	
		0	13.8	13.4	13.3		13.8	13.4	13.3	
		-5	12.7	12.0	11.8		12.7	12.0	11.8	
		-10	10.8	10.2	10.0		10.8	10.2	10.0	
		-12	10.1	9.55	9.34		10.1	9.55	9.34	
		-15	9.08	8.61	8.43		9.08	8.61	8.43	
		-17	8.46	8.03	7.86		8.46	8.03	7.86	
		-20	7.60	7.21	7.06		7.60	7.21	7.06	
		-25	6.33	6.00	5.87		6.33	6.00	5.87	
		-30	5.23	4.95	4.84		5.23	4.95	4.84	
		-35	4.28	4.05	3.96		4.28	4.05	3.96	
	-40	3.46	3.27	3.19		3.46	3.27	3.19		
	-45	2.75	2.59	2.53		2.75	2.59	2.53		
	25.4	10	16.4	16.1	16.1	16.0	16.4	16.1	16.1	16.0
		5	15.0	14.7	14.7	14.6	15.0	14.7	14.7	14.6
		0	13.8	13.6	13.5	13.5	13.8	13.6	13.5	13.5
		-5	12.7	12.3	12.2	12.0	12.7	12.3	12.2	12.0
		-10	10.8	10.4	10.3	10.2	10.8	10.4	10.3	10.2
		-12	10.1	9.75	9.67	9.53	10.1	9.75	9.67	9.53
		-15	9.08	8.80	8.72	8.60	9.08	8.80	8.72	8.60
		-17	8.46	8.21	8.13	8.02	8.46	8.21	8.13	8.02
-20		7.60	7.37	7.31	7.20	7.60	7.37	7.31	7.20	
-25		6.33	6.13	6.08	5.99	6.33	6.13	6.08	5.99	
-30		5.23	5.06	5.02	4.94	5.23	5.06	5.02	4.94	
-35		4.28	4.14	4.11	4.04	4.28	4.14	4.11	4.04	
-40	3.46	3.35	3.32	3.26	3.46	3.35	3.32	3.26		
-45	2.75	2.66	2.63	2.59	2.75	2.66	2.63	2.59		

配管長別冷凍能力表	WAN33-679	
-----------	-----------	--