

配管長別冷凍能力表

インバータ：一体空冷

周囲温度：35

型名	吸入配管径 (mm)	蒸発温度 (°C)	配管相当長別能力 (kW)									
			50Hz					60Hz				
			0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
ECO V-EN150C1	34.92	-5	60.03	54.82	52.52	49.48	47.81	60.03	54.82	52.52	49.48	47.81
		-10	51.27	46.71	44.69	42.04	40.59	51.27	46.71	44.69	42.04	40.59
		-12	48.01	43.70	41.79	39.30	37.93	48.01	43.70	41.79	39.30	37.93
		-15	43.39	39.44	37.70	35.43	34.19	43.39	39.44	37.70	35.43	34.19
		-17	40.48	36.77	35.14	33.01	31.85	40.48	36.77	35.14	33.01	31.85
		-20	36.37	33.02	31.54	29.62	28.57	36.37	33.02	31.54	29.62	28.57
		-25	30.24	27.43	26.19	24.59	23.73	30.24	27.43	26.19	24.59	23.73
		-30	24.97	22.66	21.65	20.34	19.63	24.97	22.66	21.65	20.34	19.63
		-35	20.58	18.70	17.89	16.84	16.27	20.58	18.70	17.89	16.84	16.27
	-40	16.32	14.94	14.32	13.53	13.11	16.32	14.94	14.32	13.53	13.11	
	-45	14.41	13.24	12.77	12.19	11.91	14.41	13.24	12.77	12.19	11.91	
	38.1	-5	60.03	56.36	54.82	52.64	51.41	60.03	56.36	54.82	52.64	51.41
		-10	51.27	48.06	46.70	44.79	43.71	51.27	48.06	46.70	44.79	43.71
		-12	48.01	44.98	43.69	41.89	40.87	48.01	44.98	43.69	41.89	40.87
		-15	43.39	40.61	39.43	37.78	36.86	43.39	40.61	39.43	37.78	36.86
		-17	40.48	37.87	36.76	35.21	34.34	40.48	37.87	36.76	35.21	34.34
		-20	36.37	34.01	33.01	31.61	30.82	36.37	34.01	33.01	31.61	30.82
		-25	30.24	28.26	27.42	26.25	25.60	30.24	28.26	27.42	26.25	25.60
		-30	24.97	23.34	22.65	21.69	21.16	24.97	23.34	22.65	21.69	21.16
		-35	20.58	19.26	18.70	17.93	17.50	20.58	19.26	18.70	17.93	17.50
	-40	16.32	15.36	14.94	14.36	14.04	16.32	15.36	14.94	14.36	14.04	
	-45	14.41	13.58	13.25	12.80	12.57	14.41	13.58	13.25	12.80	12.57	
	41.28	-5	60.03	57.35	56.34	54.82	53.96	60.03	57.35	56.34	54.82	53.96
		-10	51.27	48.92	48.03	46.70	45.94	51.27	48.92	48.03	46.70	45.94
		-12	48.01	45.79	44.95	43.69	42.97	48.01	45.79	44.95	43.69	42.97
		-15	43.39	41.36	40.58	39.42	38.77	43.39	41.36	40.58	39.42	38.77
		-17	40.48	38.57	37.84	36.75	36.14	40.48	38.57	37.84	36.75	36.14
-20		36.37	34.65	33.99	33.00	32.44	36.37	34.65	33.99	33.00	32.44	
-25		30.24	28.79	28.23	27.41	26.94	30.24	28.79	28.23	27.41	26.94	
-30		24.97	23.78	23.32	22.64	22.26	24.97	23.78	23.32	22.64	22.26	
-35		20.58	19.61	19.24	18.70	18.39	20.58	19.61	19.24	18.70	18.39	
-40	16.32	15.63	15.35	14.94	14.71	16.32	15.63	15.35	14.94	14.71		
-45	14.41	13.80	13.58	13.26	13.09	14.41	13.80	13.58	13.26	13.09		
ECO V-EN185C1	38.1	-5	64.92	60.54	58.65	56.02	54.55	64.92	60.54	58.65	56.02	54.55
		-10	55.70	51.82	50.14	47.81	46.51	55.70	51.82	50.14	47.81	46.51
		-12	52.26	48.57	46.97	44.77	43.54	52.26	48.57	46.97	44.77	43.54
		-15	47.37	43.97	42.49	40.47	39.33	47.37	43.97	42.49	40.47	39.33
		-17	44.28	41.07	39.68	37.77	36.70	44.28	41.07	39.68	37.77	36.70
		-20	39.92	36.99	35.71	33.97	33.00	39.92	36.99	35.71	33.97	33.00
		-25	33.36	30.87	29.78	28.31	27.49	33.36	30.87	29.78	28.31	27.49
		-30	27.69	25.60	24.69	23.47	22.79	27.69	25.60	24.69	23.47	22.79
		-35	22.90	21.18	20.44	19.43	18.88	22.90	21.18	20.44	19.43	18.88
	-40	18.24	16.90	16.32	15.55	15.12	18.24	16.90	16.32	15.55	15.12	
	-45	15.99	14.87	14.40	13.78	13.45	15.99	14.87	14.40	13.78	13.45	
	41.28	-5	64.92	61.73	60.47	58.62	57.56	64.92	61.73	60.47	58.62	57.56
		-10	55.70	52.87	51.75	50.10	49.16	55.70	52.87	51.75	50.10	49.16
		-12	52.26	49.58	48.51	46.94	46.05	52.26	49.58	48.51	46.94	46.05
		-15	47.37	44.90	43.90	42.45	41.63	47.37	44.90	43.90	42.45	41.63
		-17	44.28	41.95	41.01	39.64	38.86	44.28	41.95	41.01	39.64	38.86
		-20	39.92	37.79	36.93	35.68	34.97	39.92	37.79	36.93	35.68	34.97
		-25	33.36	31.55	30.81	29.75	29.15	33.36	31.55	30.81	29.75	29.15
		-30	27.69	26.17	25.56	24.67	24.17	27.69	26.17	25.56	24.67	24.17
		-35	22.90	21.65	21.14	20.41	20.00	22.90	21.65	21.14	20.41	20.00
	-40	18.24	17.26	16.87	16.31	15.99	18.24	17.26	16.87	16.31	15.99	
	-45	15.99	15.17	14.85	14.39	14.14	15.99	15.17	14.85	14.39	14.14	
	44.45	-5	64.92	62.50	61.69	60.40	59.69	64.92	62.50	61.69	60.40	59.69
		-10	55.70	53.56	52.83	51.68	51.04	55.70	53.56	52.83	51.68	51.04
		-12	52.26	50.23	49.53	48.44	47.82	52.26	50.23	49.53	48.44	47.82
		-15	47.37	45.50	44.85	43.84	43.27	47.37	45.50	44.85	43.84	43.27
		-17	44.28	42.52	41.90	40.94	40.40	44.28	42.52	41.90	40.94	40.40
-20		39.92	38.31	37.74	36.86	36.37	39.92	38.31	37.74	36.86	36.37	
-25		33.36	31.99	31.51	30.76	30.34	33.36	31.99	31.51	30.76	30.34	
-30		27.69	26.54	26.14	25.51	25.16	27.69	26.54	26.14	25.51	25.16	
-35		22.90	21.96	21.62	21.10	20.82	22.90	21.96	21.62	21.10	20.82	
-40	18.24	17.50	17.24	16.84	16.62	18.24	17.50	17.24	16.84	16.62		
-45	15.99	15.37	15.16	14.83	14.65	15.99	15.37	15.16	14.83	14.65		

配管長別冷凍能力表	WAN33-686
-----------	-----------