

配管長別冷凍能力表(R449A/R448A時)

○一定速:一体空冷

周囲温度:35℃

型名	吸入配管径 [mm]	蒸発温度 [°C]	延長配管長									
			50Hz					60Hz				
			0m	10m	20m	30m	50m	0m	10m	20m	30m	50m
ERA-RT15HA	φ 19.05	10	6.18	6.12	6.08	6.02	5.99	7.31	7.24	7.17	7.09	7.03
		5	5.39	5.34	5.29	5.24	5.20	6.40	6.32	6.25	6.18	6.11
		0	4.58	4.53	4.49	4.44	4.40	5.43	5.36	5.30	5.22	5.15
		-5	3.74	3.70	3.66	3.62	3.58	4.42	4.36	4.30	4.24	4.17
		-10	2.88	2.85	2.82	2.79	2.76	3.37	3.32	3.27	3.22	3.16
	φ 15.88	10	6.18	6.07	5.98	5.88	5.76	7.31	7.16	7.01	6.86	6.66
		5	5.39	5.29	5.19	5.09	4.97	6.40	6.24	6.09	5.94	5.74
		0	4.58	4.48	4.39	4.30	4.18	5.43	5.28	5.14	5.00	4.80
		-5	3.74	3.65	3.58	3.49	3.39	4.42	4.28	4.16	4.03	3.86
		-10	2.88	2.81	2.75	2.68	2.60	3.37	3.26	3.16	3.06	2.92
	φ 22.2	10	6.18	6.14	6.11	6.07	6.08	7.31	7.27	7.23	7.18	7.17
		5	5.39	5.35	5.33	5.29	5.29	6.40	6.35	6.31	6.26	6.25
		0	4.58	4.55	4.52	4.49	4.48	5.43	5.39	5.35	5.31	5.29
		-5	3.74	3.72	3.69	3.67	3.66	4.42	4.39	4.36	4.32	4.30
		-10	2.88	2.86	2.85	2.82	2.82	3.37	3.34	3.32	3.29	3.27

配管長別冷凍能力表(R404A時)

○一定速:一体空冷

周囲温度:35℃

型名	吸入配管径 [mm]	蒸発温度 [°C]	延長配管長									
			50Hz					60Hz				
			0m	10m	20m	30m	50m	0m	10m	20m	30m	50m
ERA-RT15HA	φ 19.05	10	6.56	6.49	6.43	6.36	6.31	7.68	7.59	7.50	7.40	7.30
		5	5.77	5.70	5.64	5.57	5.51	6.77	6.68	6.59	6.49	6.38
		0	4.95	4.88	4.82	4.76	4.70	5.81	5.71	5.62	5.53	5.42
		-5	4.09	4.03	3.98	3.92	3.86	4.78	4.69	4.61	4.53	4.42
		-10	3.19	3.15	3.10	3.06	3.00	3.69	3.62	3.55	3.48	3.40
	φ 15.88	10	6.56	6.42	6.29	6.16	5.98	7.68	7.48	7.29	7.09	6.81
		5	5.77	5.63	5.50	5.37	5.19	6.77	6.56	6.37	6.17	5.89
		0	4.95	4.81	4.69	4.56	4.39	5.81	5.60	5.40	5.22	4.95
		-5	4.09	3.96	3.85	3.74	3.58	4.78	4.58	4.41	4.24	4.00
		-10	3.19	3.09	3.00	2.91	2.78	3.69	3.53	3.39	3.25	3.06
	φ 22.2	10	6.56	6.52	6.48	6.43	6.43	7.68	7.63	7.58	7.52	7.49
		5	5.77	5.73	5.69	5.65	5.64	6.77	6.72	6.67	6.61	6.58
		0	4.95	4.91	4.88	4.84	4.82	5.81	5.75	5.71	5.65	5.62
		-5	4.09	4.05	4.03	3.99	3.97	4.78	4.73	4.69	4.64	4.60
		-10	3.19	3.17	3.14	3.11	3.10	3.69	3.65	3.62	3.58	3.55