

配管長別冷凍能力表

○インバータ:リモート空冷

周囲温度:35℃

形名	吸入 配管径 (mm)	蒸発温度 (℃)	配管相当長別能力 (kW)									
			50Hz					60Hz				
			0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
ECV-D225A1 + RM-D165A×2 (R463A-J)	φ 41.28	-5	67.0	63.2	61.8	59.6	58.4	67.0	63.2	61.8	59.6	58.4
		-10	56.7	53.5	52.2	50.4	49.4	56.7	53.5	52.2	50.4	49.4
		-12	53.0	50.1	48.9	47.1	46.2	53.0	50.1	48.9	47.1	46.2
		-15	47.7	45.0	43.9	42.3	41.5	47.7	45.0	43.9	42.3	41.5
		-17	44.4	41.9	40.9	39.4	38.6	44.4	41.9	40.9	39.4	38.6
		-20	39.7	37.4	36.5	35.2	34.5	39.7	37.4	36.5	35.2	34.5
	φ 44.45 (標準径)	-5	67.0	64.2	63.2	61.6	60.8	67.0	64.2	63.2	61.6	60.8
		-10	56.7	54.3	53.4	52.1	51.4	56.7	54.3	53.4	52.1	51.4
		-12	53.0	50.8	50.0	48.8	48.1	53.0	50.8	50.0	48.8	48.1
		-15	47.7	45.6	44.9	43.8	43.2	47.7	45.6	44.9	43.8	43.2
		-17	44.4	42.5	41.8	40.8	40.2	44.4	42.5	41.8	40.8	40.2
	φ 50.8	-20	39.7	38.0	37.4	36.4	35.9	39.7	38.0	37.4	36.4	35.9
		-5	67.0	65.2	64.8	64.0	63.7	67.0	65.2	64.8	64.0	63.7
		-10	56.7	55.2	54.8	54.2	53.9	56.7	55.2	54.8	54.2	53.9
		-12	53.0	51.6	51.3	50.7	50.4	53.0	51.6	51.3	50.7	50.4
		-15	47.7	46.4	46.1	45.5	45.3	47.7	46.4	46.1	45.5	45.3
		-17	44.4	43.2	42.9	42.4	42.2	44.4	43.2	42.9	42.4	42.2
	-20	39.7	38.6	38.4	37.9	37.7	39.7	38.6	38.4	37.9	37.7	

配管長別冷凍能力表	WAN35-981	
-----------	-----------	--

三菱電機株式会社

配管長別冷凍能力表

○インバータ:リモート空冷

周囲温度:35℃

形名	吸入 配管径 (mm)	蒸発温度 (℃)	配管相当長別能力 (kW)									
			50Hz					60Hz				
			0m	30m	50m	80m	100m	0m	30m	50m	80m	100m
ECV-D225A1 + RM-D165A × 2 (R410A)	φ 41.28	-5	68.8	65.2	63.8	61.7	60.6	68.8	65.2	63.8	61.7	60.6
		-10	59.3	56.1	54.9	53.0	52.0	59.3	56.1	54.9	53.0	52.0
		-12	55.6	52.6	51.4	49.7	48.8	55.6	52.6	51.4	49.7	48.8
		-15	50.5	47.8	46.7	45.1	44.2	50.5	47.8	46.7	45.1	44.2
		-17	47.3	44.7	43.6	42.1	41.3	47.3	44.7	43.6	42.1	41.3
		-20	42.6	40.2	39.3	37.9	37.2	42.6	40.2	39.3	37.9	37.2
	φ 44.45 (標準径)	-5	68.8	66.1	65.1	63.7	62.9	68.8	66.1	65.1	63.7	62.9
		-10	59.3	56.9	56.0	54.8	54.0	59.3	56.9	56.0	54.8	54.0
		-12	55.6	53.4	52.6	51.4	50.7	55.6	53.4	52.6	51.4	50.7
		-15	50.5	48.5	47.7	46.6	46.0	50.5	48.5	47.7	46.6	46.0
		-17	47.3	45.3	44.6	43.6	43.0	47.3	45.3	44.6	43.6	43.0
		-20	42.6	40.8	40.2	39.2	38.7	42.6	40.8	40.2	39.2	38.7
	φ 50.8	-5	68.8	67.0	66.7	66.0	65.7	68.8	67.0	66.7	66.0	65.7
		-10	59.3	57.7	57.4	56.8	56.5	59.3	57.7	57.4	56.8	56.5
		-12	55.6	54.2	53.9	53.3	53.0	55.6	54.2	53.9	53.3	53.0
		-15	50.5	49.2	48.9	48.4	48.1	50.5	49.2	48.9	48.4	48.1
		-17	47.3	46.0	45.7	45.2	45.0	47.3	46.0	45.7	45.2	45.0
		-20	42.6	41.4	41.2	40.7	40.5	42.6	41.4	41.2	40.7	40.5

配管長別冷凍能力表	WAN35-981	
-----------	-----------	--