

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

| 形名 | 吸入 配管径 (mm) | 蒸発温度 (℃) | 配管相当長別能力 (kW) | | | | | | | |
|------------------------------------|-------------------|-------------|---------------|------|------|------|------|------|------|------|
| | | | 50Hz | | | | 60Hz | | | |
| | | | 0m | 30m | 50m | 80m | 0m | 30m | 50m | 80m |
| ECOV-D67WA1 液管断熱有り (R463A-J) | φ 19.05 | 10 | 24.8 | 20.9 | 19.3 | - | 24.8 | 20.9 | 19.3 | - |
| | | 5 | 23.9 | 19.5 | 17.9 | - | 23.9 | 19.5 | 17.9 | - |
| | | 0 | 23.1 | 18.1 | 16.3 | - | 23.1 | 18.1 | 16.3 | - |
| | | -5 | 22.3 | 17.5 | 15.7 | - | 22.3 | 17.5 | 15.7 | - |
| | | -10 | 19.2 | 14.9 | 13.3 | - | 19.2 | 14.9 | 13.3 | - |
| | | -12 | 18.1 | 14.0 | 12.4 | - | 18.1 | 14.0 | 12.4 | - |
| | | -15 | 16.5 | 12.6 | 11.2 | - | 16.5 | 12.6 | 11.2 | - |
| | | -17 | 15.4 | 11.7 | 10.4 | - | 15.4 | 11.7 | 10.4 | - |
| | | -20 | 13.9 | 10.5 | 9.30 | - | 13.9 | 10.5 | 9.30 | - |
| | | -25 | 11.7 | 8.70 | 7.67 | - | 11.7 | 8.70 | 7.67 | - |
| | | -30 | 9.67 | 7.12 | 6.27 | - | 9.67 | 7.12 | 6.27 | - |
| | | -35 | 7.92 | 5.78 | 5.08 | - | 7.92 | 5.78 | 5.08 | - |
| | -40 | 6.42 | 4.66 | 4.10 | - | 6.42 | 4.66 | 4.10 | - | |
| | -43 | 5.64 | 4.10 | 3.60 | - | 5.64 | 4.10 | 3.60 | - | |
| | φ 22.22 (標準径) | 10 | 24.8 | 22.7 | 21.8 | 20.7 | 24.8 | 22.7 | 21.8 | 20.7 |
| | | 5 | 23.9 | 21.6 | 20.6 | 19.3 | 23.9 | 21.6 | 20.6 | 19.3 |
| | | 0 | 23.1 | 20.4 | 19.2 | 17.8 | 23.1 | 20.4 | 19.2 | 17.8 |
| | | -5 | 22.3 | 19.8 | 18.7 | 17.2 | 22.3 | 19.8 | 18.7 | 17.2 |
| | | -10 | 19.2 | 17.0 | 15.9 | 14.7 | 19.2 | 17.0 | 15.9 | 14.7 |
| | | -12 | 18.1 | 15.9 | 14.9 | 13.7 | 18.1 | 15.9 | 14.9 | 13.7 |
| | | -15 | 16.5 | 14.4 | 13.5 | 12.4 | 16.5 | 14.4 | 13.5 | 12.4 |
| | | -17 | 15.4 | 13.4 | 12.6 | 11.5 | 15.4 | 13.4 | 12.6 | 11.5 |
| | | -20 | 13.9 | 12.1 | 11.3 | 10.3 | 13.9 | 12.1 | 11.3 | 10.3 |
| | | -25 | 11.7 | 10.1 | 9.36 | 8.53 | 11.7 | 10.1 | 9.36 | 8.53 |
| | | -30 | 9.67 | 8.27 | 7.68 | 6.98 | 9.67 | 8.27 | 7.68 | 6.98 |
| | | -35 | 7.92 | 6.74 | 6.24 | 5.66 | 7.92 | 6.74 | 6.24 | 5.66 |
| | -40 | 6.42 | 5.44 | 5.04 | 4.57 | 6.42 | 5.44 | 5.04 | 4.57 | |
| | -43 | 5.64 | 4.78 | 4.42 | 4.01 | 5.64 | 4.78 | 4.42 | 4.01 | |
| | φ 25.4 | 10 | 24.8 | 23.6 | 23.1 | 22.5 | 24.8 | 23.6 | 23.1 | 22.5 |
| | | 5 | 23.9 | 22.6 | 22.1 | 21.3 | 23.9 | 22.6 | 22.1 | 21.3 |
| | | 0 | 23.1 | 21.6 | 20.9 | 20.0 | 23.1 | 21.6 | 20.9 | 20.0 |
| | | -5 | 22.3 | 20.9 | 20.3 | 19.4 | 22.3 | 20.9 | 20.3 | 19.4 |
| | | -10 | 19.2 | 18.0 | 17.4 | 16.6 | 19.2 | 18.0 | 17.4 | 16.6 |
| | | -12 | 18.1 | 16.9 | 16.3 | 15.6 | 18.1 | 16.9 | 16.3 | 15.6 |
| | | -15 | 16.5 | 15.3 | 14.8 | 14.1 | 16.5 | 15.3 | 14.8 | 14.1 |
| | | -17 | 15.4 | 14.3 | 13.8 | 13.1 | 15.4 | 14.3 | 13.8 | 13.1 |
| -20 | | 13.9 | 12.9 | 12.4 | 11.8 | 13.9 | 12.9 | 12.4 | 11.8 | |
| -25 | | 11.7 | 10.8 | 10.4 | 9.81 | 11.7 | 10.8 | 10.4 | 9.81 | |
| -30 | | 9.67 | 8.88 | 8.53 | 8.06 | 9.67 | 8.88 | 8.53 | 8.06 | |
| -35 | | 7.92 | 7.25 | 6.95 | 6.56 | 7.92 | 7.25 | 6.95 | 6.56 | |
| -40 | 6.42 | 5.86 | 5.62 | 5.30 | 6.42 | 5.86 | 5.62 | 5.30 | | |
| -43 | 5.64 | 5.15 | 4.93 | 4.65 | 5.64 | 5.15 | 4.93 | 4.65 | | |

配管長別冷凍能力表

インバータ：一体空冷

周囲温度：35℃

| 形名 | 吸入配管径 (mm) | 蒸発温度 (°C) | 配管相当長別能力 (kW) | | | | | | | |
|------------------------------------|------------------|-----------|---------------|------|------|------|------|------|------|------|
| | | | 50Hz | | | | 60Hz | | | |
| | | | 0m | 30m | 50m | 80m | 0m | 30m | 50m | 80m |
| ECOV-D67WA1 液管断熱無し (R463A-J) | φ 19.05 | 10 | 24.3 | 20.6 | 19.1 | - | 24.3 | 20.6 | 19.1 | - |
| | | 5 | 23.2 | 19.1 | 17.6 | - | 23.2 | 19.1 | 17.6 | - |
| | | 0 | 22.1 | 17.6 | 16.0 | - | 22.1 | 17.6 | 16.0 | - |
| | | -5 | 21.0 | 16.7 | 15.0 | - | 21.0 | 16.7 | 15.0 | - |
| | | -10 | 18.0 | 14.1 | 12.6 | - | 18.0 | 14.1 | 12.6 | - |
| | | -12 | 16.8 | 13.1 | 11.7 | - | 16.8 | 13.1 | 11.7 | - |
| | | -15 | 15.1 | 11.7 | 10.5 | - | 15.1 | 11.7 | 10.5 | - |
| | | -17 | 14.0 | 10.9 | 9.71 | - | 14.0 | 10.9 | 9.71 | - |
| | | -20 | 12.5 | 9.65 | 8.62 | - | 12.5 | 9.65 | 8.62 | - |
| | | -25 | 10.2 | 7.84 | 7.01 | - | 10.2 | 7.84 | 7.01 | - |
| | | -30 | 8.17 | 6.30 | 5.65 | - | 8.17 | 6.30 | 5.65 | - |
| | | -35 | 6.46 | 5.02 | 4.51 | - | 6.46 | 5.02 | 4.51 | - |
| | -40 | 5.06 | 3.97 | 3.59 | - | 5.06 | 3.97 | 3.59 | - | |
| | -43 | 4.36 | 3.46 | 3.14 | - | 4.36 | 3.46 | 3.14 | - | |
| | φ 22.22 (標準径) | 10 | 24.3 | 22.3 | 21.5 | 20.4 | 24.3 | 22.3 | 21.5 | 20.4 |
| | | 5 | 23.2 | 21.0 | 20.1 | 18.9 | 23.2 | 21.0 | 20.1 | 18.9 |
| | | 0 | 22.1 | 19.7 | 18.7 | 17.4 | 22.1 | 19.7 | 18.7 | 17.4 |
| | | -5 | 21.0 | 18.9 | 17.8 | 16.5 | 21.0 | 18.9 | 17.8 | 16.5 |
| | | -10 | 18.0 | 15.9 | 15.0 | 13.9 | 18.0 | 15.9 | 15.0 | 13.9 |
| | | -12 | 16.8 | 14.8 | 14.0 | 12.9 | 16.8 | 14.8 | 14.0 | 12.9 |
| | | -15 | 15.1 | 13.3 | 12.5 | 11.5 | 15.1 | 13.3 | 12.5 | 11.5 |
| | | -17 | 14.0 | 12.3 | 11.6 | 10.7 | 14.0 | 12.3 | 11.6 | 10.7 |
| | | -20 | 12.5 | 11.0 | 10.3 | 9.48 | 12.5 | 11.0 | 10.3 | 9.48 |
| | | -25 | 10.2 | 8.92 | 8.37 | 7.71 | 10.2 | 8.92 | 8.37 | 7.71 |
| | | -30 | 8.17 | 7.16 | 6.73 | 6.20 | 8.17 | 7.16 | 6.73 | 6.20 |
| | | -35 | 6.46 | 5.68 | 5.34 | 4.94 | 6.46 | 5.68 | 5.34 | 4.94 |
| | -40 | 5.06 | 4.47 | 4.22 | 3.91 | 5.06 | 4.47 | 4.22 | 3.91 | |
| | -43 | 4.36 | 3.87 | 3.67 | 3.41 | 4.36 | 3.87 | 3.67 | 3.41 | |
| | φ 25.4 | 10 | 24.3 | 23.2 | 22.7 | 22.1 | 24.3 | 23.2 | 22.7 | 22.1 |
| | | 5 | 23.2 | 22.0 | 21.5 | 20.8 | 23.2 | 22.0 | 21.5 | 20.8 |
| | | 0 | 22.1 | 20.7 | 20.2 | 19.4 | 22.1 | 20.7 | 20.2 | 19.4 |
| | | -5 | 21.0 | 19.9 | 19.3 | 18.5 | 21.0 | 19.9 | 19.3 | 18.5 |
| | | -10 | 18.0 | 16.8 | 16.3 | 15.6 | 18.0 | 16.8 | 16.3 | 15.6 |
| | | -12 | 16.8 | 15.7 | 15.2 | 14.6 | 16.8 | 15.7 | 15.2 | 14.6 |
| | | -15 | 15.1 | 14.1 | 13.6 | 13.0 | 15.1 | 14.1 | 13.6 | 13.0 |
| | | -17 | 14.0 | 13.1 | 12.7 | 12.1 | 14.0 | 13.1 | 12.7 | 12.1 |
| | | -20 | 12.5 | 11.6 | 11.3 | 10.7 | 12.5 | 11.6 | 11.3 | 10.7 |
| | | -25 | 10.2 | 9.47 | 9.16 | 8.73 | 10.2 | 9.47 | 9.16 | 8.73 |
| | | -30 | 8.17 | 7.60 | 7.35 | 7.01 | 8.17 | 7.60 | 7.35 | 7.01 |
| | | -35 | 6.46 | 6.02 | 5.83 | 5.57 | 6.46 | 6.02 | 5.83 | 5.57 |
| | -40 | 5.06 | 4.72 | 4.58 | 4.39 | 5.06 | 4.72 | 4.58 | 4.39 | |
| | -43 | 4.36 | 4.08 | 3.97 | 3.81 | 4.36 | 4.08 | 3.97 | 3.81 | |
| | φ 28.58 | 10 | 24.3 | 23.6 | 23.4 | 23.1 | 24.3 | 23.6 | 23.4 | 23.1 |
| | | 5 | 23.2 | 22.4 | 22.2 | 21.8 | 23.2 | 22.4 | 22.2 | 21.8 |
| | | 0 | 22.1 | 21.3 | 21.0 | 20.5 | 22.1 | 21.3 | 21.0 | 20.5 |
| | | -5 | 21.0 | 20.4 | 20.1 | 19.7 | 21.0 | 20.4 | 20.1 | 19.7 |
| | | -10 | 18.0 | 17.3 | 17.0 | 16.6 | 18.0 | 17.3 | 17.0 | 16.6 |
| | | -12 | 16.8 | 16.1 | 15.9 | 15.5 | 16.8 | 16.1 | 15.9 | 15.5 |
| | | -15 | 15.1 | 14.5 | 14.2 | 13.9 | 15.1 | 14.5 | 14.2 | 13.9 |
| | | -17 | 14.0 | 13.4 | 13.2 | 12.9 | 14.0 | 13.4 | 13.2 | 12.9 |
| | | -20 | 12.5 | 12.0 | 11.8 | 11.5 | 12.5 | 12.0 | 11.8 | 11.5 |
| | | -25 | 10.2 | 9.74 | 9.58 | 9.33 | 10.2 | 9.74 | 9.58 | 9.33 |
| | | -30 | 8.17 | 7.82 | 7.69 | 7.49 | 8.17 | 7.82 | 7.69 | 7.49 |
| | | -35 | 6.46 | 6.19 | 6.09 | 5.94 | 6.46 | 6.19 | 6.09 | 5.94 |
| | -40 | 5.06 | 4.85 | 4.78 | 4.66 | 5.06 | 4.85 | 4.78 | 4.66 | |
| | -43 | 4.36 | 4.19 | 4.13 | 4.04 | 4.36 | 4.19 | 4.13 | 4.04 | |
| | φ 31.75 | 10 | 24.3 | 23.8 | 23.7 | - | 24.3 | 23.8 | 23.7 | - |
| | | 5 | 23.2 | 22.6 | 22.5 | - | 23.2 | 22.6 | 22.5 | - |
| | | 0 | 22.1 | 21.5 | 21.4 | - | 22.1 | 21.5 | 21.4 | - |
| | | -5 | 21.0 | 20.7 | 20.5 | - | 21.0 | 20.7 | 20.5 | - |
| | | -10 | 18.0 | 17.5 | 17.4 | - | 18.0 | 17.5 | 17.4 | - |
| | | -12 | 16.8 | 16.3 | 16.2 | - | 16.8 | 16.3 | 16.2 | - |
| | | -15 | 15.1 | 14.7 | 14.6 | - | 15.1 | 14.7 | 14.6 | - |
| | | -17 | 14.0 | 13.6 | 13.5 | - | 14.0 | 13.6 | 13.5 | - |
| | | -20 | 12.5 | 12.1 | 12.0 | - | 12.5 | 12.1 | 12.0 | - |
| | | -25 | 10.2 | 9.87 | 9.79 | - | 10.2 | 9.87 | 9.79 | - |
| | | -30 | 8.17 | 7.92 | 7.86 | - | 8.17 | 7.92 | 7.86 | - |
| | | -35 | 6.46 | 6.27 | 6.22 | - | 6.46 | 6.27 | 6.22 | - |
| | -40 | 5.06 | 4.91 | 4.88 | - | 5.06 | 4.91 | 4.88 | - | |
| | -43 | 4.36 | 4.24 | 4.21 | - | 4.36 | 4.24 | 4.21 | - | |

| | |
|-----------|-----------|
| 配管長別冷凍能力表 | WAN35-991 |
|-----------|-----------|

配管長別冷凍能力表

○インバータ：一体空冷

周囲温度：35℃

| 形名 | 吸入 配管径 (mm) | 蒸発温度 (℃) | 配管相当長別能力 (kW) | | | | | | | |
|---------------------------------|-------------------|-------------|---------------|------|------|------|------|------|------|------|
| | | | 50Hz | | | | 60Hz | | | |
| | | | 0m | 30m | 50m | 80m | 0m | 30m | 50m | 80m |
| ECOVD67WA1 液管断熱有り (R410A) | φ 19.05 | 10 | 24.4 | 20.9 | 19.5 | - | 24.4 | 20.9 | 19.5 | - |
| | | 5 | 23.8 | 19.8 | 18.2 | - | 23.8 | 19.8 | 18.2 | - |
| | | 0 | 23.2 | 18.5 | 16.8 | - | 23.2 | 18.5 | 16.8 | - |
| | | -5 | 22.6 | 18.0 | 16.2 | - | 22.6 | 18.0 | 16.2 | - |
| | | -10 | 19.4 | 15.4 | 13.9 | - | 19.4 | 15.4 | 13.9 | - |
| | | -12 | 18.2 | 14.4 | 13.0 | - | 18.2 | 14.4 | 13.0 | - |
| | | -15 | 16.6 | 13.1 | 11.7 | - | 16.6 | 13.1 | 11.7 | - |
| | | -17 | 15.6 | 12.2 | 11.0 | - | 15.6 | 12.2 | 11.0 | - |
| | | -20 | 14.1 | 11.0 | 9.88 | - | 14.1 | 11.0 | 9.88 | - |
| | | -25 | 11.9 | 9.25 | 8.27 | - | 11.9 | 9.25 | 8.27 | - |
| | | -30 | 10.0 | 7.72 | 6.89 | - | 10.0 | 7.72 | 6.89 | - |
| | | -35 | 8.38 | 6.43 | 5.74 | - | 8.38 | 6.43 | 5.74 | - |
| | -40 | 7.01 | 5.38 | 4.83 | - | 7.01 | 5.38 | 4.83 | - | |
| | -45 | 5.93 | 4.60 | 4.10 | - | 5.93 | 4.60 | 4.10 | - | |
| | φ 22.22 (標準径) | 10 | 24.4 | 22.5 | 21.8 | 20.7 | 24.4 | 22.5 | 21.8 | 20.7 |
| | | 5 | 23.8 | 21.7 | 20.7 | 19.6 | 23.8 | 21.7 | 20.7 | 19.6 |
| | | 0 | 23.2 | 20.7 | 19.6 | 18.3 | 23.2 | 20.7 | 19.6 | 18.3 |
| | | -5 | 22.6 | 20.1 | 19.1 | 17.7 | 22.6 | 20.1 | 19.1 | 17.7 |
| | | -10 | 19.4 | 17.3 | 16.3 | 15.2 | 19.4 | 17.3 | 16.3 | 15.2 |
| | | -12 | 18.2 | 16.2 | 15.3 | 14.2 | 18.2 | 16.2 | 15.3 | 14.2 |
| | | -15 | 16.6 | 14.7 | 13.9 | 12.9 | 16.6 | 14.7 | 13.9 | 12.9 |
| | | -17 | 15.6 | 13.8 | 13.0 | 12.0 | 15.6 | 13.8 | 13.0 | 12.0 |
| | | -20 | 14.1 | 12.5 | 11.8 | 10.9 | 14.1 | 12.5 | 11.8 | 10.9 |
| | | -25 | 11.9 | 10.5 | 9.87 | 9.09 | 11.9 | 10.5 | 9.87 | 9.09 |
| | | -30 | 10.0 | 8.78 | 8.24 | 7.58 | 10.0 | 8.78 | 8.24 | 7.58 |
| | | -35 | 8.38 | 7.32 | 6.87 | 6.32 | 8.38 | 7.32 | 6.87 | 6.32 |
| | -40 | 7.01 | 6.13 | 5.75 | 5.30 | 7.01 | 6.13 | 5.75 | 5.30 | |
| | -45 | 5.93 | 5.19 | 4.89 | 4.54 | 5.93 | 5.19 | 4.89 | 4.54 | |
| | φ 25.4 | 10 | 24.4 | 23.3 | 22.9 | 22.4 | 24.4 | 23.3 | 22.9 | 22.4 |
| | | 5 | 23.8 | 22.6 | 22.1 | 21.4 | 23.8 | 22.6 | 22.1 | 21.4 |
| | | 0 | 23.2 | 21.8 | 21.2 | 20.4 | 23.2 | 21.8 | 21.2 | 20.4 |
| | | -5 | 22.6 | 21.1 | 20.6 | 19.8 | 22.6 | 21.1 | 20.6 | 19.8 |
| | | -10 | 19.4 | 18.2 | 17.7 | 17.0 | 19.4 | 18.2 | 17.7 | 17.0 |
| | | -12 | 18.2 | 17.1 | 16.6 | 16.0 | 18.2 | 17.1 | 16.6 | 16.0 |
| | | -15 | 16.6 | 15.6 | 15.1 | 14.5 | 16.6 | 15.6 | 15.1 | 14.5 |
| | | -17 | 15.6 | 14.6 | 14.2 | 13.6 | 15.6 | 14.6 | 14.2 | 13.6 |
| -20 | | 14.1 | 13.2 | 12.8 | 12.3 | 14.1 | 13.2 | 12.8 | 12.3 | |
| -25 | | 11.9 | 11.1 | 10.8 | 10.3 | 11.9 | 11.1 | 10.8 | 10.3 | |
| -30 | | 10.0 | 9.32 | 9.02 | 8.60 | 10.0 | 9.32 | 9.02 | 8.60 | |
| -35 | | 8.38 | 7.78 | 7.52 | 7.17 | 8.38 | 7.78 | 7.52 | 7.17 | |
| -40 | 7.01 | 6.51 | 6.29 | 6.00 | 7.01 | 6.51 | 6.29 | 6.00 | | |
| -45 | 5.93 | 5.51 | 5.33 | 5.09 | 5.93 | 5.51 | 5.33 | 5.09 | | |

配管長別冷凍能力表

インバータ：一体空冷

周囲温度：35℃

| 形名 | 吸入配管径 (mm) | 蒸発温度 (°C) | 配管相当長別能力 (kW) | | | | | | | |
|---------------------------------|------------------|-----------|---------------|------|------|------|------|------|------|------|
| | | | 50Hz | | | | 60Hz | | | |
| | | | 0m | 30m | 50m | 80m | 0m | 30m | 50m | 80m |
| ECOVD67WA1 液管断熱無し (R410A) | φ 19.05 | 10 | 23.8 | 20.5 | 19.2 | - | 23.8 | 20.5 | 19.2 | - |
| | | 5 | 23.0 | 19.3 | 17.8 | - | 23.0 | 19.3 | 17.8 | - |
| | | 0 | 22.2 | 18.0 | 16.4 | - | 22.2 | 18.0 | 16.4 | - |
| | | -5 | 21.3 | 17.2 | 15.6 | - | 21.3 | 17.2 | 15.6 | - |
| | | -10 | 18.1 | 14.6 | 13.2 | - | 18.1 | 14.6 | 13.2 | - |
| | | -12 | 17.0 | 13.6 | 12.3 | - | 17.0 | 13.6 | 12.3 | - |
| | | -15 | 15.3 | 12.3 | 11.1 | - | 15.3 | 12.3 | 11.1 | - |
| | | -17 | 14.3 | 11.4 | 10.3 | - | 14.3 | 11.4 | 10.3 | - |
| | | -20 | 12.8 | 10.2 | 9.25 | - | 12.8 | 10.2 | 9.25 | - |
| | | -25 | 10.7 | 8.48 | 7.66 | - | 10.7 | 8.48 | 7.66 | - |
| | | -30 | 8.76 | 6.98 | 6.32 | - | 8.76 | 6.98 | 6.32 | - |
| | | -35 | 7.18 | 5.74 | 5.21 | - | 7.18 | 5.74 | 5.21 | - |
| | -40 | 5.89 | 4.76 | 4.35 | - | 5.89 | 4.76 | 4.35 | - | |
| | -45 | 4.91 | 4.04 | 3.78 | - | 4.91 | 4.04 | 3.78 | - | |
| | φ 22.22 (標準径) | 10 | 23.8 | 22.1 | 21.4 | 20.4 | 23.8 | 22.1 | 21.4 | 20.4 |
| | | 5 | 23.0 | 21.0 | 20.2 | 19.1 | 23.0 | 21.0 | 20.2 | 19.1 |
| | | 0 | 22.2 | 19.9 | 19.0 | 17.8 | 22.2 | 19.9 | 19.0 | 17.8 |
| | | -5 | 21.3 | 19.1 | 18.1 | 16.9 | 21.3 | 19.1 | 18.1 | 16.9 |
| | | -10 | 18.1 | 16.3 | 15.4 | 14.4 | 18.1 | 16.3 | 15.4 | 14.4 |
| | | -12 | 17.0 | 15.2 | 14.4 | 13.4 | 17.0 | 15.2 | 14.4 | 13.4 |
| | | -15 | 15.3 | 13.7 | 13.0 | 12.1 | 15.3 | 13.7 | 13.0 | 12.1 |
| | | -17 | 14.3 | 12.8 | 12.1 | 11.3 | 14.3 | 12.8 | 12.1 | 11.3 |
| | | -20 | 12.8 | 11.5 | 10.9 | 10.1 | 12.8 | 11.5 | 10.9 | 10.1 |
| | | -25 | 10.7 | 9.50 | 8.99 | 8.36 | 10.7 | 9.50 | 8.99 | 8.36 |
| | | -30 | 8.76 | 7.81 | 7.40 | 6.88 | 8.76 | 7.81 | 7.40 | 6.88 |
| | | -35 | 7.18 | 6.41 | 6.08 | 5.67 | 7.18 | 6.41 | 6.08 | 5.67 |
| | -40 | 5.89 | 5.28 | 5.02 | 4.70 | 5.89 | 5.28 | 5.02 | 4.70 | |
| | -45 | 4.91 | 4.44 | 4.24 | 4.01 | 4.91 | 4.44 | 4.24 | 4.01 | |
| | φ 25.4 | 10 | 23.8 | 22.8 | 22.5 | 21.9 | 23.8 | 22.8 | 22.5 | 21.9 |
| | | 5 | 23.0 | 21.9 | 21.4 | 20.8 | 23.0 | 21.9 | 21.4 | 20.8 |
| | | 0 | 22.2 | 20.9 | 20.4 | 19.7 | 22.2 | 20.9 | 20.4 | 19.7 |
| | | -5 | 21.3 | 20.0 | 19.5 | 18.8 | 21.3 | 20.0 | 19.5 | 18.8 |
| | | -10 | 18.1 | 17.1 | 16.6 | 16.0 | 18.1 | 17.1 | 16.6 | 16.0 |
| | | -12 | 17.0 | 16.0 | 15.6 | 15.0 | 17.0 | 16.0 | 15.6 | 15.0 |
| | | -15 | 15.3 | 14.4 | 14.0 | 13.5 | 15.3 | 14.4 | 14.0 | 13.5 |
| | | -17 | 14.3 | 13.4 | 13.1 | 12.6 | 14.3 | 13.4 | 13.1 | 12.6 |
| | | -20 | 12.8 | 12.1 | 11.7 | 11.3 | 12.8 | 12.1 | 11.7 | 11.3 |
| | | -25 | 10.7 | 10.0 | 9.72 | 9.34 | 10.7 | 10.0 | 9.72 | 9.34 |
| | | -30 | 8.76 | 8.22 | 8.00 | 7.68 | 8.76 | 8.22 | 8.00 | 7.68 |
| | | -35 | 7.18 | 6.74 | 6.56 | 6.31 | 7.18 | 6.74 | 6.56 | 6.31 |
| | -40 | 5.89 | 5.54 | 5.40 | 5.20 | 5.89 | 5.54 | 5.40 | 5.20 | |
| | -45 | 4.91 | 4.64 | 4.53 | 4.38 | 4.91 | 4.64 | 4.53 | 4.38 | |
| | φ 28.58 | 10 | 23.8 | 23.2 | 23.0 | 22.8 | 23.8 | 23.2 | 23.0 | 22.8 |
| | | 5 | 23.0 | 22.3 | 22.1 | 21.7 | 23.0 | 22.3 | 22.1 | 21.7 |
| | | 0 | 22.2 | 21.4 | 21.1 | 20.7 | 22.2 | 21.4 | 21.1 | 20.7 |
| | | -5 | 21.3 | 20.5 | 20.2 | 19.8 | 21.3 | 20.5 | 20.2 | 19.8 |
| | | -10 | 18.1 | 17.5 | 17.3 | 16.9 | 18.1 | 17.5 | 17.3 | 16.9 |
| | | -12 | 17.0 | 16.4 | 16.1 | 15.8 | 17.0 | 16.4 | 16.1 | 15.8 |
| | | -15 | 15.3 | 14.8 | 14.6 | 14.3 | 15.3 | 14.8 | 14.6 | 14.3 |
| | | -17 | 14.3 | 13.8 | 13.6 | 13.3 | 14.3 | 13.8 | 13.6 | 13.3 |
| | | -20 | 12.8 | 12.4 | 12.2 | 11.9 | 12.8 | 12.4 | 12.2 | 11.9 |
| | | -25 | 10.7 | 10.2 | 10.1 | 9.89 | 10.7 | 10.2 | 10.1 | 9.89 |
| | | -30 | 8.76 | 8.43 | 8.31 | 8.14 | 8.76 | 8.43 | 8.31 | 8.14 |
| | | -35 | 7.18 | 6.90 | 6.81 | 6.67 | 7.18 | 6.90 | 6.81 | 6.67 |
| | -40 | 5.89 | 5.67 | 5.60 | 5.49 | 5.89 | 5.67 | 5.60 | 5.49 | |
| | -45 | 4.91 | 4.73 | 4.68 | 4.60 | 4.91 | 4.73 | 4.68 | 4.60 | |
| | φ 31.75 | 10 | 23.8 | 23.3 | 23.3 | - | 23.8 | 23.3 | 23.3 | - |
| | | 5 | 23.0 | 22.5 | 22.4 | - | 23.0 | 22.5 | 22.4 | - |
| | | 0 | 22.2 | 21.6 | 21.5 | - | 22.2 | 21.6 | 21.5 | - |
| | | -5 | 21.3 | 20.7 | 20.6 | - | 21.3 | 20.7 | 20.6 | - |
| | | -10 | 18.1 | 17.7 | 17.6 | - | 18.1 | 17.7 | 17.6 | - |
| | | -12 | 17.0 | 16.5 | 16.4 | - | 17.0 | 16.5 | 16.4 | - |
| | | -15 | 15.3 | 14.9 | 14.8 | - | 15.3 | 14.9 | 14.8 | - |
| | | -17 | 14.3 | 13.9 | 13.8 | - | 14.3 | 13.9 | 13.8 | - |
| | | -20 | 12.8 | 12.5 | 12.4 | - | 12.8 | 12.5 | 12.4 | - |
| | | -25 | 10.7 | 10.4 | 10.3 | - | 10.7 | 10.4 | 10.3 | - |
| | | -30 | 8.76 | 8.53 | 8.47 | - | 8.76 | 8.53 | 8.47 | - |
| | | -35 | 7.18 | 6.98 | 6.94 | - | 7.18 | 6.98 | 6.94 | - |
| | -40 | 5.89 | 5.74 | 5.70 | - | 5.89 | 5.74 | 5.70 | - | |
| | -45 | 4.91 | 4.78 | 4.76 | - | 4.91 | 4.78 | 4.76 | - | |

| | |
|-----------|-----------|
| 配管長別冷凍能力表 | WAN35-991 |
|-----------|-----------|